



Chagans Technologies Limited

Partner PG API Documentation

v3.0 • Confidential • 2026

Base URL

<https://chagans.com>

All endpoints are relative to this base URL. Use HTTPS at all times. Never expose credentials in client-side code or version control.

1. Authentication & Headers

Every request to the PartnerPG API must include the following HTTP headers. Requests missing any required header will be rejected with a 4xx error.

Required Headers

Header	Example (Masked)	Notes
client-id	6854*****	Issued during onboarding. Treat as username.
client-secret	0db3*****	Secret key. Store in a secrets manager — never in source code.
Authorization	Bearer eyJhbGciOiJ.....LQ	Short-lived JWT access token. Rotate regularly.
Content-Type	application/json	Must be application/json for all POST requests.

⚠ Security Requirements

- Never commit client-secret or JWT tokens to source control or public documentation.
- Store client-secret in a secrets manager (Vault, AWS Secrets Manager, GCP Secret Manager, etc.)
- Log only masked tokens — show at most the first 4 and last 4 characters.

2. Endpoint: Create Payment Request

Method	POST
Path	/partnerPg/payRequest
Full URL	https://chagans.com/partnerPg/payRequest
Auth Required	Yes — all three credential headers

2.1 Request Body

Send a JSON body with the following fields:

Field	Type	Required	Description
amount	number	Yes	Transaction amount in INR. Must be > 0. Decimal supported.
pgType	string	Yes	Payment gateway type. Accepted values: chagans, chagans1,
txnId	string	Yes	Your unique transaction reference ID. Must be globally unique.
callback	string	Yes	Redirect URL after payment completion (success or failure).
mode	string	Yes	Settlement mode. Accepted values: t0, t1
webhook	string	No	URL to receive async payment status notifications.

2.2 pgType — Gateway Routing

The pgType parameter determines which underlying payment gateway processes the transaction and maps to internal gateway identifiers as follows:

pgType Value	Internal Gateway	Max Amount
chagans3	comet	₹40000

i Amount Limits

- chagans3 (comet) — maximum ₹40,000 per transaction. Requests exceeding these limits are rejected with HTTP 400.

2.3 mode — Settlement Type

mode	Settlement Timing	Requirement
t0	Same-day settlement (T+0)	partnerT0 flag must be enabled on the admin account.
t1	Next-day settlement (T+1)	partnerT1 flag must be enabled on the admin account.

2.4 Example Request

```
curl -X POST "https://chagans.com/partnerPg/payRequest" \  
-H "client-id: 6854*****" \  
-H "client-secret: 0db3*****" \  
-H "Authorization: Bearer <ACCESS_TOKEN>" \  
-H "Content-Type: application/json" \  
-d '{  
  "amount": 2000,  
  "pgType": "chagans3",  
  "txnId": "TXN_8923",  
  "callback": "https://yoursite.com/payment/result",  
  "mode": "t1",  
  "webhook": "https://yoursite.com/webhooks/pg",  
  "name": "Ravi Kumar",  
  "mobile": "9876543210",  
  "email": "ravi@example.com"  
}'
```

3. Response Reference

3.1 Success Response — 200 OK

```
{  
  "message": "Payment initiated successfully",  
  "code": 200,  
  "success": true,  
  "link": "https://chagans.com/partnerPg/chagansPg?data=<encrypted>",  
  "data": {  
    "orderId": "CPG_A1B2C3D4E5F6G7H8",  
    "amount": 1000.00,  
    "paymentType": "chagans3",  
    "gateway": "comet",  
    "txnId": "TXN_8923"  
  }  
}
```

```
}
```

Response Fields

Field	Type	Description
success	boolean	true if the payment was successfully initiated.
code	number	HTTP-equivalent status code (200 on success).
message	string	Human-readable status message.
link	string	Redirect this URL to the customer to complete payment.
data.orderId	string	System-generated order ID prefixed with CPG_.
data.amount	number	Parsed transaction amount (float).
data.paymentType	string	Echoes the pgType sent in the request.
data.gateway	string	Internal gateway name used (crown / ace).
data.txnId	string	Echoes your txnId for reconciliation.

3.2 Error Responses

HTTP Code	success	Scenario
400	false	Missing required fields (amount, pgType, txnId, callback, mode).
400	false	Invalid mode — must be t0 or t1.
400	false	Invalid pgType — must be chagans or chagans1 or chagans2.
400	false	Amount exceeds gateway limit (₹40,000).
200	false	pg service not active on a partner account.
200	false	Duplicate txnId — already exists in the system.
200	false	Internal server error during payment initiation.



Note on HTTP 200 with success: false

Some business-logic errors return HTTP 200 with success: false.

Always check the success field in the response body — do not rely solely on HTTP status code.

A 200 status does NOT guarantee the payment was initiated.

3.3 Error Response Examples

Missing Required Fields

```
{
```

```
{
  "message": "Missing required fields",
  "success": false,
  "code": 400,
  "fields": ["amount", "pgType", "txnId", "callback", "mode"]
}
```

Duplicate Transaction ID

```
{
  "message": "Transaction ID already exists",
  "success": false,
  "code": 200,
  "timestamp": "2025-06-01T10:30:00.000Z",
  "txnId": "TXN_8923"
}
```

Invalid Mode

```
{
  "message": "Invalid mode",
  "success": false,
  "code": 400,
  "fields": ["mode"],
  "values": ["t0", "t1"]
}
```

Duplicate Amount

```
{
  "message": "Amount already used",
  "success": false,
  "code": 400,
  "txnId": "TXN_8923"
}
```

4. Payment Flow

Follow these steps to integrate a complete end-to-end payment flow:

Step	Actor	Action
1	Your Server	Validate transaction on your end (amount, order validity).
2	Your Server	POST /partnerPg/payRequest with all required fields.
3	Chagans API	Returns success: true and a payment link.
4	Your Server	Redirect the customer browser to the returned link URL.

Step	Actor	Action
5	Customer	Completes payment on the Chagans-hosted payment page.
6	Chagans API	POSTs payment status to your webhook URL (async).
7	Chagans API	Redirects customers to your callback URL with status params.
8	Your Server	Verify payment status via webhook — never trust client-side redirect only.

✓ Best Practice: Always verify via Webhook

Never confirm a payment based only on the callback redirect — customers can manipulate URL parameters.
The webhook notification is the authoritative signal. Reconcile your txnId against it before fulfilling orders.

5. Customer KYC Requirements

All partners must collect and maintain adequate Know Your Customer (KYC) data for every transaction. This is required for regulatory compliance, dispute resolution, and chargebacks.

5.1 Minimum Data to Collect

Data Point	Field in API	Notes
Full Name	name	Legal name as per government-issued ID.
Mobile Number	mobile	10-digit Indian mobile number. Use for OTP verification.
Email Address	email	Valid email. Use for receipts and communication.
Aadhaar / PAN	—	Collect separately. Store masked (last 4 digits only).
Billing Address	—	Collect via your onboarding flow.
Transaction Details	—	Amount, date, orderId, txnId — auto-captured by system.
Customer Consent	—	Log explicit consent flag and timestamp.

5.2 Accepted Identity Documents

- Aadhaar Card
- PAN Card
- Passport
- Driving Licence

5.3 KYC Storage & Masking Rules

Rule	Requirement
Masking	Show only the last 4 digits of Aadhaar / PAN in any UI or log.
Encryption	Encrypt all PII at rest (AES-256 or equivalent).
Access Control	Limit PII access to authorised personnel only. Log access.
Retention	Retain KYC records for a minimum of 7 years.
Secure Deletion	Purge stale / expired data using certified deletion methods.

5.4 KYC for Chargebacks & Disputes

In the event of a dispute or chargeback, you must be able to provide:

- Full transaction record (orderId, txnId, amount, timestamp, gateway)
- Customer KYC documents on file
- OTP verification logs
- Customer consent record

Recommendation

Maintain a dedicated dispute folder per transaction with all supporting documents pre-organised. This significantly reduces chargeback resolution time.

6. Integration Security Checklist

#	Check	Status
1	HTTPS enforced on all API calls	☐ To Do
2	client-secret stored in secrets manager (not env file)	☐ To Do
3	JWT tokens are short-lived and refreshed regularly	☐ To Do
4	OTP verification enabled for customer transactions	☐ To Do
5	All PII encrypted at rest (AES-256 or equivalent)	☐ To Do
6	Aadhaar / PAN masked in all logs and UI	☐ To Do
7	7-year data retention policy documented and enforced	☐ To Do
8	Dispute / chargeback process documented and tested	☐ To Do

#	Check	Status
9	Webhook endpoint validates payload before processing	☐ To Do
10	txnId uniqueness enforced on your side before API call	☐ To Do
11	Payment confirmation done via webhook (not redirect URL)	☐ To Do
12	Server-side validation of amount before API call	☐ To Do

7. Quick Reference

7.1 Endpoint Summary

Method	Endpoint	Description
POST	/partnerPg/payRequest	Initiate a new partner payment transaction.

7.2 Valid Field Values

Field	Valid Values
pgType	chagans3
mode	t0, t1

7.3 Useful Contacts

Technical Support	developer@chagans.com
Support Mobile No	9211336188

© 2016- 26 Chagans Technologies Limited. All rights reserved. This document is confidential and intended solely for authorised integration partners.