

Same Day Solution — POS Transaction API

Enterprise POS Transaction API for B2B Partners | Powered by **Same Day Solution Pvt. Ltd.**

v2.0.0

Table of Contents

- 1. [Authentication](#)
- 2. [Base URL & Setup](#)
- 3. [Security & Rate Limits](#)
- 4. [Health Check](#)
- 5. [Get POS Transactions](#)
- 6. [Get Assigned POS Machines](#)
- 7. [Create Export Job](#)
- 8. [Check Export Status](#)
- 9. [Reversal Webhook \(Outbound\)](#)
- 10. [Error Codes](#)
- 11. [Code Samples](#)

1. Authentication

Every authenticated request requires **3 custom headers**:

HEADER	DESCRIPTION
<code>x-api-key</code>	Your public API key (starts with <code>pk_live_</code>)
<code>x-signature</code>	HMAC-SHA256 signature (see formula below)
<code>x-timestamp</code>	Current Unix timestamp in milliseconds

Signature Formula

For **POST requests** (with JSON body):

```
signature = HMAC_SHA256(api_secret, JSON.stringify(body) + timestamp)
```

For GET requests (no body):

```
signature = HMAC_SHA256(api_secret, "" + timestamp)
```

Important: The `api_secret` (starts with `sk_live_`) is used only for signing — never send it as a header or query parameter.

2. Base URL & Setup

ENVIRONMENT	BASE URL
Production	<code>https://api.samedaysolution.in</code>

Quick Start

1. Receive your `api_key` and `api_secret` from the Same Day Solution admin team.
2. Whitelist your server IP(s) — contact admin.
3. Import the Postman collection (attached) and set your keys in **Collection Variables**.
4. Make a [Health Check](#) call to verify connectivity.

3. Security & Rate Limits

- **IP Whitelisting:** Only whitelisted IPs can access authenticated endpoints. Contact admin to add IPs.
- **Timestamp Tolerance:** Requests must arrive within **5 minutes** (300 seconds) of the `x-timestamp` value.
- **HTTPS:** Required in production. Plain HTTP is rejected.
- **Rate Limit:** 100 requests/minute per API key. Exceeding returns `429` with `Retry-After` header.

4. Health Check

GET

Health Check

/pos-health

Check if the POS Partner API is running. **No authentication required.**

Response

200 Healthy

```
{
  "status": "healthy",
  "service": "pos-partner-api",
  "version": "1.0.0",
  "timestamp": "2026-02-17T10:00:00.000Z",
  "uptime": 86400,
  "database": {
    "status": "healthy",
    "latency_ms": 12
  }
}
```

5. Get POS Transactions

POST

Get POS Transactions

/api/partner/pos-transactions

Retrieve POS transactions for your assigned terminals with flexible filtering and pagination.

Request Headers

HEADER	VALUE
Content-Type	application/json
x-api-key	Your public API key
x-signature	HMAC_SHA256(api_secret, JSON.stringify(body) + timestamp)
x-timestamp	Current Unix timestamp in milliseconds

Request Body

FIELD	TYPE	REQUIRED	DESCRIPTION
date_from	ISO 8601	Yes	Start date (max 90 days range)
date_to	ISO 8601	Yes	End date
status	String	No	AUTHORIZED CAPTURED FAILED REFUNDED VOIDED
terminal_id	String	No	Filter by Terminal ID (TID)
payment_mode	String	No	CARD UPI NFC CASH WALLET NETBANKING BHARATQR
page	Integer	No	Page number (default: 1)
page_size	Integer	No	Records per page (default: 50, max: 100)

Example Request Body

```
{
  "date_from": "2026-02-01T00:00:00.000Z",
  "date_to": "2026-02-28T23:59:59.999Z",
  "status": null,
  "terminal_id": null,
```

```

"payment_mode": null,
"page": 1,
"page_size": 50
}

```

Response Fields (per transaction)

FIELD	TYPE	DESCRIPTION
id	String	Internal transaction UUID
razorpay_txn_id	String	Razorpay transaction ID
external_ref	String	External reference number
terminal_id	String	Terminal ID (TID)
amount	String	Amount in rupees (e.g. "49897.00")
status	String	AUTHORIZED CAPTURED FAILED REFUNDED VOIDED
rrn	String	Retrieval Reference Number
card_brand	String	VISA MasterCard RUPAY Diners Club Amex
card_type	String	CREDIT DEBIT
card_number	String	Masked card number (e.g. 4862-69XX-XXXX-3667)
issuing_bank	String	Card issuing bank (e.g. HDFC , SBI , AXIS)
card_classification	String null	Card tier. Values: PLATINUM , GOLD , STANDARD , CLASSIC , SIGNATURE , BUSINESS , TITANIUM , INFINITE , CORPORATE , PREPAID , etc. May be null .
card_txn_type	String null	Card entry mode: EMV with PIN , Contactless , Swipe , EMV , Manual Entry . May be null for UPI.
acquiring_bank	String	Acquiring bank (e.g. HDFC , AMEX , SBI)
payment_mode	String	CARD UPI NFC CASH , etc.
device_serial	String	POS device serial number
customer_name	String	Cardholder / consumer name
payer_name	String	Payer name
txn_type	String	Transaction type (e.g. CHARGE)
auth_code	String	Authorization code from card issuer

<code>mid</code>	String	Merchant ID
<code>currency</code>	String	Currency code (e.g. <code>INR</code>)
<code>receipt_url</code>	String	Customer receipt URL
<code>posting_date</code>	String	Posting date (ISO 8601)
<code>txn_time</code>	String	Transaction time (ISO 8601)
<code>created_at</code>	String	Record creation time (ISO 8601)
<code>reversed_at</code>	String null	Set when a previously- <code>CAPTURED</code> txn was later voided/reversed/refunded upstream. <code>null</code> for live transactions.
<code>reversal_reason</code>	String null	Why the txn was reversed (source status/type that triggered it, e.g. <code>pinelab:VOID</code>). <code>null</code> unless reversed.

⚠️ Voided / Reversed Transactions

A transaction reported as `CAPTURED` that is **later voided, reversed, or refunded** at the terminal is **retained** (never silently deleted). Its `status` becomes `VOIDED` (or `REFUNDED`), with `reversed_at` / `reversal_reason` populated. Query them with `status = VOIDED` / `status = REFUNDED` . If you have a webhook configured, you also receive a `pos.transaction.reversed` event (see [Reversal Webhook](#)) so you can remove/reverse it in your books. **Do not treat `VOIDED` / `REFUNDED` transactions as settleable.**

Pagination Object

FIELD	TYPE	DESCRIPTION
<code>page</code>	Integer	Current page number
<code>page_size</code>	Integer	Records per page
<code>total_records</code>	Integer	Total matching records
<code>total_pages</code>	Integer	Total pages available
<code>has_next</code>	Boolean	Whether more pages exist
<code>has_prev</code>	Boolean	Whether previous pages exist

Summary Object

FIELD	TYPE	DESCRIPTION
<code>total_transactions</code>	Integer	Total number of transactions in the response

total_amount	String	Sum of all transaction amounts
authorized_count	Integer	Count of AUTHORIZED transactions
captured_count	Integer	Count of CAPTURED transactions
failed_count	Integer	Count of FAILED transactions
refunded_count	Integer	Count of REFUNDED transactions
voided_count	Integer	Count of VOIDED transactions
captured_amount	String	Sum of CAPTURED transaction amounts
terminal_count	Integer	Number of unique terminals in results

Success Response

200 Transactions Found

```
{
  "success": true,
  "company": "Same Day Solution",
  "data": [
    {
      "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
      "razorpay_txn_id": "260217042251974E883523117",
      "external_ref": "EZ202602171503118508",
      "terminal_id": "96192751",
      "amount": "2850.00",
      "status": "CAPTURED",
      "rrn": "000000000070",
      "card_brand": "VISA",
      "card_type": "CREDIT",
      "payment_mode": "CARD",
      "device_serial": "2841155771",
      "txn_time": "2026-01-01T00:12:00.000Z",
      "created_at": "2026-01-01T00:12:01.000Z",
      "customer_name": "MR SHREYAS T",
      "payer_name": "MR SHREYAS T",
      "txn_type": "CHARGE",
      "auth_code": "007115",
      "card_number": "4862-69XX-XXXX-3667",
      "issuing_bank": "HDFC",
      "card_classification": "PLATINUM",
      "card_txn_type": "EMV with PIN",
      "acquiring_bank": "HDFC",
      "mid": "IDZ551",
      "currency": "INR",
      "receipt_url": "http://eze.cc/RZPPoS/t/a/DB120049",
      "posting_date": "2026-01-01T00:12:00.000Z"
    }
  ]
}
```

```
    }  
  ],  
  "pagination": {  
    "page": 1,  
    "page_size": 50,  
    "total_records": 1,  
    "total_pages": 1,  
    "has_next": false,  
    "has_prev": false  
  },  
  "summary": {  
    "total_transactions": 1,  
    "total_amount": "2850.00",  
    "authorized_count": 0,  
    "captured_count": 1,  
    "failed_count": 0,  
    "refunded_count": 0,  
    "voided_count": 0,  
    "captured_amount": "2850.00",  
    "terminal_count": 1  
  }  
}
```

6. Get Assigned POS Machines

GET

Get Assigned POS Machines

```
/api/partner/pos-machines?page=1&limit=50
```

Retrieve POS machines assigned to your partner account.

Query Parameters

PARAMETER	TYPE	REQUIRED	DESCRIPTION
<code>page</code>	Integer	No	Page number (default: 1)
<code>limit</code>	Integer	No	Records per page (default: 50, max: 100)
<code>status</code>	String	No	<code>active</code> <code>inactive</code> <code>maintenance</code> <code>decommissioned</code>
<code>machine_type</code>	String	No	Filter by machine model (e.g. <code>Razorpay POS</code>)
<code>search</code>	String	No	Search by <code>terminal_id</code> , <code>device_serial</code> , <code>machine_model</code>

Authentication Headers

HEADER	VALUE
<code>x-api-key</code>	Your public API key
<code>x-signature</code>	<code>HMAC_SHA256(api_secret, "" + timestamp)</code> (empty body for GET)
<code>x-timestamp</code>	Current Unix timestamp in milliseconds

Response Fields (per machine)

FIELD	TYPE	DESCRIPTION
<code>id</code>	String	Unique machine UUID
<code>terminal_id</code>	String	Razorpay Terminal ID (TID)
<code>device_serial</code>	String	Physical device serial number
<code>machine_model</code>	String	Machine model/type
<code>status</code>	String	<code>active</code> <code>inactive</code> <code>maintenance</code> <code>decommissioned</code>
<code>activated_at</code>	String	When the machine was activated (ISO 8601)
<code>last_txn_at</code>	String	Timestamp of last transaction (ISO 8601)

retailer_code	String	Assigned retailer code
retailer_name	String	Assigned retailer name
retailer_business_name	String	Retailer business name
retailer_city	String	Retailer city
retailer_state	String	Retailer state

Success Response

200 Machines Found

```
{
  "success": true,
  "company": "Same Day Solution",
  "data": [
    {
      "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
      "terminal_id": "29196333",
      "device_serial": "2841154268",
      "machine_model": "Razorpay POS",
      "status": "active",
      "activated_at": "2026-02-01T10:00:00.000Z",
      "last_txn_at": "2026-02-18T04:22:51.000Z",
      "retailer_code": "RET001",
      "retailer_name": "Example Retailer",
      "retailer_business_name": "Example Retail Pvt Ltd",
      "retailer_city": "new delhi",
      "retailer_state": "delhi"
    }
  ],
  "pagination": {
    "page": 1,
    "limit": 50,
    "total": 1,
    "total_pages": 1,
    "has_next_page": false,
    "has_prev_page": false
  }
}
```

7. Create Export Job

POST

Create Export Job

/api/partner/pos-transactions/export

Create an asynchronous export job to download transaction data in various formats.

Request Body

FIELD	TYPE	REQUIRED	DESCRIPTION
format	String	Yes	csv excel pdf zip
date_from	Date	Yes	Start date (YYYY-MM-DD)
date_to	Date	Yes	End date (YYYY-MM-DD)
status	String	No	Filter by transaction status
terminal_id	String	No	Filter by Terminal ID

Supported Formats

FORMAT	DESCRIPTION
csv	Comma-separated values (.csv)
excel	Microsoft Excel (.xlsx)
pdf	PDF report (.pdf)
zip	ZIP archive containing CSV + PDF

Daily Limit: 10 exports per day per API key. Contact admin to increase.

Example Request

```
{
  "format": "csv",
  "date_from": "2026-02-01",
  "date_to": "2026-02-28",
  "status": null,
  "terminal_id": null
}
```

Success Response

202 Export Job Created

```
{
  "success": true,
  "data": {
    "message": "Export job created. Use the job_id to check status.",
    "job_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
    "format": "csv",
    "status": "QUEUED",
    "remaining_exports_today": 9
  }
}
```

8. Check Export Status

GET

Check Export Status

/api/partner/export-status/{job_id}

Check the status of a previously created export job.

Path Parameter

PARAMETER	TYPE	DESCRIPTION
<code>job_id</code>	UUID	The job ID returned from the Create Export endpoint

Job Statuses

STATUS	DESCRIPTION
<code>QUEUED</code>	Waiting in queue to be processed
<code>PROCESSING</code>	Currently generating the file
<code>COMPLETED</code>	Ready for download (URL provided)
<code>FAILED</code>	Export failed — retry the job

When status is `COMPLETED`, the response includes a **signed S3 download URL** valid for **1 hour**. Download or store the URL promptly.

Success Response — Completed

200 Job Completed

```
{
  "success": true,
  "data": {
    "job": {
      "id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
      "status": "COMPLETED",
      "format": "csv",
      "file_url": "https://sameday-pos-exports.s3.ap-south-1.amazonaws.com/...",
      "file_size_bytes": 45670,
      "record_count": 150,
      "created_at": "2026-02-17T10:00:00.000Z",
      "completed_at": "2026-02-17T10:00:15.000Z",
      "expires_at": "2026-02-17T11:00:15.000Z"
    }
  }
}
```

```
}  
}
```

Response — Still Processing

200 Job Processing

```
{  
  "success": true,  
  "data": {  
    "job": {  
      "id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",  
      "status": "PROCESSING",  
      "format": "csv",  
      "file_url": null,  
      "created_at": "2026-02-17T10:00:00.000Z",  
      "completed_at": null  
    }  
  }  
}
```

9. Reversal Webhook (Outbound)

POST

pos.transaction.reversed → **your webhook_url**

POST {your_webhook_url}

This is an **OUTBOUND** webhook that Same Day Solution POSTs to your configured `webhook_url`. You do not call it — this documents the payload you receive. To enable it, share your `webhook_url` and receive a `webhook_secret` from the admin team.

When it fires: when a transaction previously delivered as `CAPTURED` is later **voided, reversed, or refunded** at the terminal. Reconcile by removing/reversing the matching `txn_id` (or `rrn` + `terminal_id`) in your system.

Request Headers (sent to you)

HEADER	DESCRIPTION
<code>X-Sameday-Event</code>	Event type. <code>pos.transaction</code> for live txns; <code>pos.transaction.reversed</code> for voids/reversals/refunds.
<code>X-Sameday-Timestamp</code>	Unix timestamp (seconds) of delivery.
<code>X-Sameday-Delivery</code>	Unique delivery id (stable across retries — use for idempotency/dedupe).
<code>X-Sameday-Signature</code>	HMAC-SHA256 over <code>timestamp + "." + rawBody</code> using your <code>webhook_secret</code> (hex).

Signature Verification

```
expected = HMAC_SHA256(webhook_secret, X-Sameday-Timestamp + "." + rawRequestBody)
// compare (constant-time) against the hex value in X-Sameday-Signature
```

Reject the delivery if the signature does not match, or if `X-Sameday-Timestamp` is older than a few minutes. Use `X-Sameday-Delivery` to dedupe retries — deliveries are retried with backoff until your endpoint returns `2xx`.

Events

X-SAMEDAY-EVENT	MEANING
-----------------	---------

<code>pos.transaction</code>	Normal transaction notification
<code>pos.transaction.reversed</code>	A prior capture was voided/reversed/refunded — remove/reverse it on your side

Payload

```
{
  "event": "pos.transaction.reversed",
  "action": "remove",
  "txn_id": "PL_7211256230",
  "rrn": "000000000076",
  "terminal_id": "43135139",
  "tid": "43135139",
  "device_serial": "1234567890",
  "mid": "IDZ551",
  "amount": 49897.00,
  "previous_status": "CAPTURED",
  "status": "VOIDED",
  "reversed_at": "2026-02-18T06:12:00.000Z",
  "reason": "pinelab:VOID",
  "was_settled": false,
  "_brand": "PINELAB"
}
```

Key Fields

FIELD	DESCRIPTION
<code>event</code>	<code>pos.transaction.reversed</code>
<code>action</code>	<code>remove</code> — void/reverse the txn on your side
<code>txn_id</code>	The transaction id you were previously sent
<code>previous_status</code>	Always <code>CAPTURED</code> (what you had)
<code>status</code>	<code>VOIDED</code> or <code>REFUNDED</code> (new terminal state)
<code>reversed_at</code>	When the reversal was detected (ISO 8601)
<code>reason</code>	Source status/type that triggered the reversal
<code>was_settled</code>	<code>true</code> if the amount had already been settled to a wallet (flag for manual reconciliation)

Expected Response

Return `2xx` once received. Any non-2xx (or timeout) triggers retries with backoff.

10. Error Codes

All error responses follow this structure:

```
{
  "success": false,
  "error": {
    "code": "ERROR_CODE",
    "message": "Human-readable description"
  }
}
```

HTTP CODE	ERROR CODE	DESCRIPTION
400	BAD_REQUEST	Missing or invalid parameters (e.g. <code>date_from</code> required)
401	UNAUTHORIZED	Invalid API key, bad signature, expired timestamp, or IP not whitelisted
404	NOT_FOUND	Resource not found (e.g. invalid export job_id)
429	RATE_LIMIT_EXCEEDED	Too many requests — check <code>Retry-After</code> header for wait time

Common 401 causes:

- API key not set or incorrect
- Signature computed incorrectly (double-check `JSON.stringify` order)
- Timestamp older than 5 minutes
- Server IP not whitelisted — if using Postman, disable cloud agent (Settings → General → "Use Postman's cloud agent" → OFF)

11. Code Samples

Node.js (JavaScript)

```
const crypto = require('crypto');

const API_KEY = 'pk_live_YOUR_API_KEY';
```

```

const API_SECRET = 'sk_live_YOUR_API_SECRET';
const BASE_URL = 'https://api.samedaysolution.in';

async function getTransactions(dateFrom, dateTo, options = {}) {
  const body = {
    date_from: dateFrom,
    date_to: dateTo,
    status: options.status || null,
    terminal_id: options.terminalId || null,
    payment_mode: options.paymentMode || null,
    page: options.page || 1,
    page_size: options.pageSize || 50
  };

  const timestamp = Date.now().toString();
  const payload = JSON.stringify(body) + timestamp;
  const signature = crypto
    .createHmac('sha256', API_SECRET)
    .update(payload)
    .digest('hex');

  const res = await fetch(`${BASE_URL}/api/partner/pos-transactions`, {
    method: 'POST',
    headers: {
      'Content-Type': 'application/json',
      'x-api-key': API_KEY,
      'x-signature': signature,
      'x-timestamp': timestamp
    },
    body: JSON.stringify(body)
  });

  return res.json();
}

// Usage
const data = await getTransactions(
  '2026-02-01T00:00:00.000Z',
  '2026-02-28T23:59:59.999Z',
  { status: 'CAPTURED', page: 1 }
);
console.log(data);

```

Python

```

import hmac, hashlib, json, time, requests

API_KEY      = "pk_live_YOUR_API_KEY"
API_SECRET   = "sk_live_YOUR_API_SECRET"
BASE_URL     = "https://api.samedaysolution.in"

```

```

def get_transactions(date_from, date_to, **kwargs):
    body = {
        "date_from": date_from,
        "date_to": date_to,
        "status": kwargs.get("status"),
        "terminal_id": kwargs.get("terminal_id"),
        "payment_mode": kwargs.get("payment_mode"),
        "page": kwargs.get("page", 1),
        "page_size": kwargs.get("page_size", 50),
    }

    timestamp = str(int(time.time() * 1000))
    payload = json.dumps(body, separators=(",", ":")) + timestamp
    signature = hmac.new(
        API_SECRET.encode(), payload.encode(), hashlib.sha256
    ).hexdigest()

    resp = requests.post(
        f"{BASE_URL}/api/partner/pos-transactions",
        json=body,
        headers={
            "Content-Type": "application/json",
            "x-api-key": API_KEY,
            "x-signature": signature,
            "x-timestamp": timestamp,
        },
    )
    return resp.json()

# Usage
data = get_transactions(
    "2026-02-01T00:00:00.000Z",
    "2026-02-28T23:59:59.999Z",
    status="CAPTURED",
)
print(data)

```

cURL

```

# Step 1: Generate signature (using Node.js one-liner)
TIMESTAMP=$(date +%s%3N)
BODY='{ "date_from": "2026-02-01T00:00:00.000Z", "date_to": "2026-02-28T23:59:59.999Z", "status": null, "terminal_id": null, "payment_mode": null, "page": 1, "page_size": 50 }'
SIGNATURE=$(echo -n "${BODY}${TIMESTAMP}" | openssl dgst -sha256 -hmac "sk_live_YOUR_SECRET" | awk '{print $2}')

# Step 2: Make the request
curl -X POST https://api.samedaysolution.in/api/partner/pos-transactions \
-H "Content-Type: application/json" \

```

```
-H "x-api-key: pk_live_YOUR_KEY" \
-H "x-signature: ${SIGNATURE}" \
-H "x-timestamp: ${TIMESTAMP}" \
-d "${BODY}"
```

Node.js — Verify Reversal Webhook

```
const crypto = require('crypto');
const express = require('express');
const app = express();

const WEBHOOK_SECRET = 'your_webhook_secret';
const seen = new Set(); // replace with a persistent store in production

// IMPORTANT: capture the RAW body for signature verification
app.post('/webhooks/sameday-pos', express.raw({ type: '*' }), (req, res) => {
  const rawBody = req.body.toString('utf8');
  const event = req.get('X-Sameday-Event');
  const timestamp = req.get('X-Sameday-Timestamp');
  const delivery = req.get('X-Sameday-Delivery');
  const signature = req.get('X-Sameday-Signature');

  // 1) Reject stale deliveries (older than 5 minutes)
  if (Math.abs(Date.now() / 1000 - Number(timestamp)) > 300) {
    return res.status(400).send('stale');
  }

  // 2) Verify signature (constant-time)
  const expected = crypto
    .createHmac('sha256', WEBHOOK_SECRET)
    .update(timestamp + '.' + rawBody)
    .digest('hex');
  const ok = crypto.timingSafeEqual(Buffer.from(expected), Buffer.from(signature || ''));
  if (!ok) return res.status(401).send('bad signature');

  // 3) Idempotency – dedupe on delivery id
  if (seen.has(delivery)) return res.status(200).send('duplicate');
  seen.add(delivery);

  const payload = JSON.parse(rawBody);
  if (event === 'pos.transaction.reversed') {
    // remove / reverse payload.txn_id (or payload.rrn + payload.terminal_id) in your books
    console.log('Reverse txn:', payload.txn_id, payload.status, payload.reason);
  }

  // 4) Always ack with 2xx once stored
  res.status(200).send('ok');
});
```

```
app.listen(3000);
```

Same Day Solution Pvt. Ltd.

API Version 2.0.0 | Document generated: August 2026

For API key provisioning, IP whitelisting, or support — contact your account manager or email the technical team.