

Same Day Solution — POS Transaction API

Enterprise POS Transaction API for B2B Partners | Powered by **Same Day Solution Pvt. Ltd.**

v2.0.0

Table of Contents

1. Authentication
2. Base URL & Setup
3. Security & Rate Limits
4. Health Check
5. Get POS Transactions
6. Get Assigned POS Machines
7. Create Export Job
8. Check Export Status
9. Error Codes
10. Code Samples

1. Authentication

Every authenticated request requires **3 custom headers**:

HEADER	DESCRIPTION
<code>x-api-key</code>	Your public API key (starts with <code>pk_live_</code>)
<code>x-signature</code>	HMAC-SHA256 signature (see formula below)
<code>x-timestamp</code>	Current Unix timestamp in milliseconds

Signature Formula

For **POST requests** (with JSON body):

```
signature = HMAC_SHA256(api_secret, JSON.stringify(body) + timestamp)
```

For GET requests (no body):

```
signature = HMAC_SHA256(api_secret, "" + timestamp)
```

Important: The `api_secret` (starts with `sk_live_`) is used only for signing — never send it as a header or query parameter.

2. Base URL & Setup

ENVIRONMENT	BASE URL
Production	<code>https://api.samedaysolution.in</code>

Quick Start

1. Receive your `api_key` and `api_secret` from the Same Day Solution admin team.
2. Whitelist your server IP(s) — contact admin.
3. Import the Postman collection (attached) and set your keys in **Collection Variables**.
4. Make a [Health Check](#) call to verify connectivity.

3. Security & Rate Limits

- **IP Whitelisting:** Only whitelisted IPs can access authenticated endpoints. Contact admin to add IPs.
- **Timestamp Tolerance:** Requests must arrive within **5 minutes** (300 seconds) of the `x-timestamp` value.
- **HTTPS:** Required in production. Plain HTTP is rejected.
- **Rate Limit:** 100 requests/minute per API key. Exceeding returns `429` with `Retry-After` header.

4. Health Check

GET

Health Check

/pos-health

Check if the POS Partner API is running. **No authentication required.**

Response

200 Healthy

```
{
  "status": "healthy",
  "service": "pos-partner-api",
  "version": "1.0.0",
  "timestamp": "2026-02-17T10:00:00.000Z",
  "uptime": 86400,
  "database": {
    "status": "healthy",
    "latency_ms": 12
  }
}
```

5. Get POS Transactions

POST

Get POS Transactions

/api/partner/pos-transactions

Retrieve POS transactions for your assigned terminals with flexible filtering and pagination.

Request Headers

HEADER	VALUE
Content-Type	application/json
x-api-key	Your public API key
x-signature	HMAC_SHA256(api_secret, JSON.stringify(body) + timestamp)
x-timestamp	Current Unix timestamp in milliseconds

Request Body

FIELD	TYPE	REQUIRED	DESCRIPTION
date_from	ISO 8601	Yes	Start date (max 90 days range)
date_to	ISO 8601	Yes	End date
status	String	No	AUTHORIZED CAPTURED FAILED REFUNDED VOIDED
terminal_id	String	No	Filter by Terminal ID (TID)
payment_mode	String	No	CARD UPI NFC CASH WALLET NETBANKING BHARATQR
page	Integer	No	Page number (default: 1)
page_size	Integer	No	Records per page (default: 50, max: 100)

Example Request Body

```
{
  "date_from": "2026-02-01T00:00:00.000Z",
  "date_to": "2026-02-28T23:59:59.999Z",
  "status": null,
```

```

"terminal_id": null,
"payment_mode": null,
"page": 1,
"page_size": 50
}

```

Response Fields (per transaction)

FIELD	TYPE	DESCRIPTION
<code>id</code>	String	Internal transaction UUID
<code>razorpay_txn_id</code>	String	Razorpay transaction ID
<code>external_ref</code>	String	External reference number
<code>terminal_id</code>	String	Terminal ID (TID)
<code>amount</code>	String	Amount in rupees (e.g. <code>"49897.00"</code>)
<code>status</code>	String	<code>AUTHORIZED</code> <code>CAPTURED</code> <code>FAILED</code> <code>REFUNDED</code> <code>VOIDED</code>
<code>rrn</code>	String	Retrieval Reference Number
<code>card_brand</code>	String	<code>VISA</code> <code>MasterCard</code> <code>RUPAY</code> <code>Diners Club</code> <code>Amex</code>
<code>card_type</code>	String	<code>CREDIT</code> <code>DEBIT</code>
<code>card_number</code>	String	Masked card number (e.g. <code>4862-69XX-XXXX-3667</code>)
<code>issuing_bank</code>	String	Card issuing bank (e.g. <code>HDFC</code> , <code>SBI</code> , <code>AXIS</code>)
<code>card_classification</code>	String null	Card tier. Values: <code>PLATINUM</code> , <code>GOLD</code> , <code>STANDARD</code> , <code>CLASSIC</code> , <code>SIGNATURE</code> , <code>BUSINESS</code> , <code>TITANIUM</code> , <code>INFINITE</code> , <code>CORPORATE</code> , <code>PREPAID</code> , etc. May be <code>null</code> .
<code>card_txn_type</code>	String null	Card entry mode: <code>EMV with PIN</code> , <code>Contactless</code> , <code>Swipe</code> , <code>EMV</code> , <code>Manual Entry</code> . May be <code>null</code> for UPI.
<code>acquiring_bank</code>	String	Acquiring bank (e.g. <code>HDFC</code> , <code>AMEX</code> , <code>SBI</code>)
<code>payment_mode</code>	String	<code>CARD</code> <code>UPI</code> <code>NFC</code> <code>CASH</code> , etc.
<code>device_serial</code>	String	POS device serial number
<code>customer_name</code>	String	Cardholder / consumer name
<code>payer_name</code>	String	Payer name

txn_type	String	Transaction type (e.g. CHARGE)
auth_code	String	Authorization code from card issuer
mid	String	Merchant ID
currency	String	Currency code (e.g. INR)
receipt_url	String	Customer receipt URL
posting_date	String	Posting date (ISO 8601)
txn_time	String	Transaction time (ISO 8601)
created_at	String	Record creation time (ISO 8601)

Pagination Object

FIELD	TYPE	DESCRIPTION
page	Integer	Current page number
page_size	Integer	Records per page
total_records	Integer	Total matching records
total_pages	Integer	Total pages available
has_next	Boolean	Whether more pages exist
has_prev	Boolean	Whether previous pages exist

Summary Object

FIELD	TYPE	DESCRIPTION
total_transactions	Integer	Total number of transactions in the response
total_amount	String	Sum of all transaction amounts
authorized_count	Integer	Count of AUTHORIZED transactions
captured_count	Integer	Count of CAPTURED transactions
failed_count	Integer	Count of FAILED transactions
refunded_count	Integer	Count of REFUNDED transactions
captured_amount	String	Sum of CAPTURED transaction amounts

terminal_count

Integer

Number of unique terminals in results

Success Response

200 Transactions Found

```
{
  "success": true,
  "company": "Same Day Solution",
  "data": [
    {
      "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
      "razorpay_txn_id": "260217042251974E883523117",
      "external_ref": "EZ202602171503118508",
      "terminal_id": "96192751",
      "amount": "2850.00",
      "status": "CAPTURED",
      "rrn": "000000000070",
      "card_brand": "VISA",
      "card_type": "CREDIT",
      "payment_mode": "CARD",
      "device_serial": "2841155771",
      "txn_time": "2026-01-01T00:12:00.000Z",
      "created_at": "2026-01-01T00:12:01.000Z",
      "customer_name": "MR SHREYAS T",
      "payer_name": "MR SHREYAS T",
      "txn_type": "CHARGE",
      "auth_code": "007115",
      "card_number": "4862-69XX-XXXX-3667",
      "issuing_bank": "HDFC",
      "card_classification": "PLATINUM",
      "card_txn_type": "EMV with PIN",
      "acquiring_bank": "HDFC",
      "mid": "IDZ551",
      "currency": "INR",
      "receipt_url": "http://eze.cc/RZPPoS/t/a/DB120049",
      "posting_date": "2026-01-01T00:12:00.000Z"
    }
  ],
  "pagination": {
    "page": 1,
    "page_size": 50,
    "total_records": 1,
    "total_pages": 1,
    "has_next": false,
    "has_prev": false
  },
  "summary": {
    "total_transactions": 1,
  }
}
```

```
"total_amount": "2850.00",  
"authorized_count": 0,  
"captured_count": 1,  
"failed_count": 0,  
"refunded_count": 0,  
"captured_amount": "2850.00",  
"terminal_count": 1  
}  
}
```

6. Get Assigned POS Machines

GET

Get Assigned POS Machines

```
/api/partner/pos-machines?page=1&limit=50
```

Retrieve POS machines assigned to your partner account.

Query Parameters

PARAMETER	TYPE	REQUIRED	DESCRIPTION
<code>page</code>	Integer	No	Page number (default: 1)
<code>limit</code>	Integer	No	Records per page (default: 50, max: 100)
<code>status</code>	String	No	<code>active</code> <code>inactive</code> <code>maintenance</code> <code>decommissioned</code>
<code>machine_type</code>	String	No	Filter by machine model (e.g. <code>Razorpay POS</code>)
<code>search</code>	String	No	Search by <code>terminal_id</code> , <code>device_serial</code> , <code>machine_model</code>

Authentication Headers

HEADER	VALUE
<code>x-api-key</code>	Your public API key
<code>x-signature</code>	<code>HMAC_SHA256(api_secret, "" + timestamp)</code> (empty body for GET)
<code>x-timestamp</code>	Current Unix timestamp in milliseconds

Response Fields (per machine)

FIELD	TYPE	DESCRIPTION
<code>id</code>	String	Unique machine UUID
<code>terminal_id</code>	String	Razorpay Terminal ID (TID)
<code>device_serial</code>	String	Physical device serial number
<code>machine_model</code>	String	Machine model/type
<code>status</code>	String	<code>active</code> <code>inactive</code> <code>maintenance</code> <code>decommissioned</code>
<code>activated_at</code>	String	When the machine was activated (ISO 8601)

<code>last_txn_at</code>	String	Timestamp of last transaction (ISO 8601)
<code>retailer_code</code>	String	Assigned retailer code
<code>retailer_name</code>	String	Assigned retailer name
<code>retailer_business_name</code>	String	Retailer business name
<code>retailer_city</code>	String	Retailer city
<code>retailer_state</code>	String	Retailer state

Success Response

200 Machines Found

```
{
  "success": true,
  "company": "Same Day Solution",
  "data": [
    {
      "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",
      "terminal_id": "29196333",
      "device_serial": "2841154268",
      "machine_model": "Razorpay POS",
      "status": "active",
      "activated_at": "2026-02-01T10:00:00.000Z",
      "last_txn_at": "2026-02-18T04:22:51.000Z",
      "retailer_code": "RET001",
      "retailer_name": "Example Retailer",
      "retailer_business_name": "Example Retail Pvt Ltd",
      "retailer_city": "new delhi",
      "retailer_state": "delhi"
    }
  ],
  "pagination": {
    "page": 1,
    "limit": 50,
    "total": 1,
    "total_pages": 1,
    "has_next_page": false,
    "has_prev_page": false
  }
}
```

7. Create Export Job

POST

Create Export Job

/api/partner/pos-transactions/export

Create an asynchronous export job to download transaction data in various formats.

Request Body

FIELD	TYPE	REQUIRED	DESCRIPTION
format	String	Yes	csv excel pdf zip
date_from	Date	Yes	Start date (YYYY-MM-DD)
date_to	Date	Yes	End date (YYYY-MM-DD)
status	String	No	Filter by transaction status
terminal_id	String	No	Filter by Terminal ID

Supported Formats

FORMAT	DESCRIPTION
csv	Comma-separated values (.csv)
excel	Microsoft Excel (.xlsx)
pdf	PDF report (.pdf)
zip	ZIP archive containing CSV + PDF

Daily Limit: 10 exports per day per API key. Contact admin to increase.

Example Request

```
{
  "format": "csv",
  "date_from": "2026-02-01",
  "date_to": "2026-02-28",
  "status": null,
  "terminal_id": null
}
```

Success Response

202 Export Job Created

```
{
  "success": true,
  "data": {
    "message": "Export job created. Use the job_id to check status.",
    "job_id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
    "format": "csv",
    "status": "QUEUED",
    "remaining_exports_today": 9
  }
}
```

8. Check Export Status

GET

Check Export Status

/api/partner/export-status/{job_id}

Check the status of a previously created export job.

Path Parameter

PARAMETER	TYPE	DESCRIPTION
<code>job_id</code>	UUID	The job ID returned from the Create Export endpoint

Job Statuses

STATUS	DESCRIPTION
<code>QUEUED</code>	Waiting in queue to be processed
<code>PROCESSING</code>	Currently generating the file
<code>COMPLETED</code>	Ready for download (URL provided)
<code>FAILED</code>	Export failed — retry the job

When status is `COMPLETED`, the response includes a **signed S3 download URL** valid for **1 hour**. Download or store the URL promptly.

Success Response — Completed

200 Job Completed

```
{
  "success": true,
  "data": {
    "job": {
      "id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",
      "status": "COMPLETED",
      "format": "csv",
      "file_url": "https://sameday-pos-exports.s3.ap-south-1.amazonaws.com/...",
      "file_size_bytes": 45670,
      "record_count": 150,
      "created_at": "2026-02-17T10:00:00.000Z",
      "completed_at": "2026-02-17T10:00:15.000Z",
      "expires_at": "2026-02-17T11:00:15.000Z"
    }
  }
}
```

```
}  
}  
}
```

Response — Still Processing

200 Job Processing

```
{  
  "success": true,  
  "data": {  
    "job": {  
      "id": "f47ac10b-58cc-4372-a567-0e02b2c3d479",  
      "status": "PROCESSING",  
      "format": "csv",  
      "file_url": null,  
      "created_at": "2026-02-17T10:00:00.000Z",  
      "completed_at": null  
    }  
  }  
}
```

9. Error Codes

All error responses follow this structure:

```
{  
  "success": false,  
  "error": {  
    "code": "ERROR_CODE",  
    "message": "Human-readable description"  
  }  
}
```

HTTP CODE	ERROR CODE	DESCRIPTION
400	BAD_REQUEST	Missing or invalid parameters (e.g. <code>date_from</code> required)
401	UNAUTHORIZED	Invalid API key, bad signature, expired timestamp, or IP not whitelisted
404	NOT_FOUND	Resource not found (e.g. invalid export job_id)

Common 401 causes:

- API key not set or incorrect
- Signature computed incorrectly (double-check `JSON.stringify` order)
- Timestamp older than 5 minutes
- Server IP not whitelisted — if using Postman, disable cloud agent (Settings → General → "Use Postman's cloud agent" → OFF)

10. Code Samples

Node.js (JavaScript)

```
const crypto = require('crypto');

const API_KEY = 'pk_live_YOUR_API_KEY';
const API_SECRET = 'sk_live_YOUR_API_SECRET';
const BASE_URL = 'https://api.samedaysolution.in';

async function getTransactions(dateFrom, dateTo, options = {}) {
  const body = {
    date_from: dateFrom,
    date_to: dateTo,
    status: options.status || null,
    terminal_id: options.terminalId || null,
    payment_mode: options.paymentMode || null,
    page: options.page || 1,
    page_size: options.pageSize || 50
  };

  const timestamp = Date.now().toString();
  const payload = JSON.stringify(body) + timestamp;
  const signature = crypto
    .createHmac('sha256', API_SECRET)
    .update(payload)
    .digest('hex');

  const res = await fetch(`${BASE_URL}/api/partner/pos-transactions`, {
    method: 'POST',
    headers: {
      'Content-Type': 'application/json',
      'x-api-key': API_KEY,
      'x-signature': signature,
    },
  });
}
```



```

        'x-timestamp': timestamp
    },
    body: JSON.stringify(body)
});

return res.json();
}

// Usage
const data = await getTransactions(
    '2026-02-01T00:00:00.000Z',
    '2026-02-28T23:59:59.999Z',
    { status: 'CAPTURED', page: 1 }
);
console.log(data);

```

Python

```

import hmac, hashlib, json, time, requests

API_KEY    = "pk_live_YOUR_API_KEY"
API_SECRET = "sk_live_YOUR_API_SECRET"
BASE_URL   = "https://api.samedaysolution.in"

def get_transactions(date_from, date_to, **kwargs):
    body = {
        "date_from": date_from,
        "date_to": date_to,
        "status": kwargs.get("status"),
        "terminal_id": kwargs.get("terminal_id"),
        "payment_mode": kwargs.get("payment_mode"),
        "page": kwargs.get("page", 1),
        "page_size": kwargs.get("page_size", 50),
    }

    timestamp = str(int(time.time() * 1000))
    payload = json.dumps(body, separators=(",", ":")) + timestamp
    signature = hmac.new(
        API_SECRET.encode(), payload.encode(), hashlib.sha256
    ).hexdigest()

    resp = requests.post(
        f"{BASE_URL}/api/partner/pos-transactions",
        json=body,
        headers={
            "Content-Type": "application/json",
            "x-api-key": API_KEY,
            "x-signature": signature,
            "x-timestamp": timestamp,

```

```

    },
  )
  return resp.json()

# Usage
data = get_transactions(
    "2026-02-01T00:00:00.000Z",
    "2026-02-28T23:59:59.999Z",
    status="CAPTURED",
)
print(data)

```

cURL

```

# Step 1: Generate signature (using Node.js one-liner)
TIMESTAMP=$(date +%s%3N)
BODY='{"date_from":"2026-02-01T00:00:00.000Z","date_to":"2026-02-28T23:59:59.999Z","status":null,"terminal_id":null,"payment_mode":null,"page":1,"page_size":100}'
SIGNATURE=$(echo -n "${BODY}${TIMESTAMP}" | openssl dgst -sha256 -hmac "sk_live_YOUR_SECRET" | awk '{print $2}')

# Step 2: Make the request
curl -X POST https://api.samedaysolution.in/api/partner/pos-transactions \
  -H "Content-Type: application/json" \
  -H "x-api-key: pk_live_YOUR_KEY" \
  -H "x-signature: ${SIGNATURE}" \
  -H "x-timestamp: ${TIMESTAMP}" \
  -d "${BODY}"

```

Same Day Solution Pvt. Ltd.

API Version 2.0.0 | Document generated: July 2026

For API key provisioning, IP whitelisting, or support — contact your account manager or email the technical team.