

Pine Labs POS — Webhook Callback Integration Guide SameDay Solution

Per-transaction notification setup for Pine Labs POS terminals

Integration Guidance
v1.0 · Sep 2026

1 What this is

Pine Labs POS terminals push an HTTP **POST** to your server for each transaction. You host a single endpoint; Pine Labs calls it on every transaction. This enables real-time per-transaction notifications — no polling required.

Note: The authoritative field names and signature scheme come from **your Pine Labs onboarding / integration contact**. Naming differs slightly per integration type (PlutusSmart / Online Callback / Cloud API). The format below is what we receive in production and is a safe reference to build against.

2 Setup (one-time)

- Stand up a **public HTTPS** endpoint, e.g. `https://api.paymatrix.in/pinelab/notification`.
- Share that URL with Pine Labs and ask them to enable **transaction notifications / callbacks** for your MID(s) / TID(s).
- Ask Pine Labs whether callbacks are signed and, if so, request the **shared secret** and the **signature header name** (we have seen `x-pinelab-signature` / `x-signature`).

3 Endpoint requirements

Property	Requirement
Method	POST
Body	JSON
Response	Return HTTP 200 quickly to acknowledge; process asynchronously
Timeout	Keep the handler fast; do DB / business work after acking
Idempotency	Deduplicate on <code>TransactionNumber</code> / <code>PlutusTransactionReferenceID</code> (retries can repeat the same txn)

4 Signature verification IF SECRET PROVIDED

HMAC-SHA256 over the **raw request body**, hex-encoded, compared timing-safely:

```
const expected = crypto
  .createHmac('sha256', PINELAB_WEBHOOK_SECRET)
  .update(rawBody)           // exact bytes, before JSON.parse
  .digest('hex');

// compare against header x-pinelab-signature / x-signature (timing-safe)
```

5 Payload fields (what Pine Labs sends)

Field names vary by integration; accept the alternates.

Purpose	Primary field	Alternates / Notes
Transaction id	TransactionNumber	PlutusTransactionReferenceID , TransactionId
Amount	Amount	TransactionAmount — often in paise
Result code	HostResponse	ResponseCode (00 / APPROVED = success; 05 / 51 / DECLINED = fail)
Status	TransactionStatus	Approved / Declined / Void
Type	TransactionType	REFUND / VOID / REVERSAL / CHARGE
Terminal id	TerminalId	TID
Merchant id	MerchantId	MID
RRN	RRN	RetrievalReferenceNumber
Auth code	ApprovalCode	AuthCode
Card (masked)	CardNumber	MaskedCardNumber
Card type	CardType	CREDIT / DEBIT
Card scheme	CardScheme	CardBrand (VISA / MASTERCARD / RUPAY / AMEX)
Payment mode	PaymentMode	TransactionType
Batch / invoice	BatchNumber	InvoiceNumber
Timestamp	TransactionDateTime	TransactionDate
Issuing bank	IssuingBank	—
Currency	Currency	default INR

6 Parsing rules (important)

- **Amount is usually in paise** → divide by 100 to get rupees.
- **Status mapping:** HostResponse == "00" or APPROVED → success; 05 / 51 / DECLINED → failed; VOID / REVERSAL → voided; REFUND → refunded.
- **Act on success only** for settlement; expect PENDING / FAILED callbacks too.
- **Auto-reversals** may arrive as a later VOID / REFUND (or even FAILED) for a txn you already saw approved — handle the reversal.
- Store the **entire raw payload** for audit.

7 Sample callback payload

```
{
  "TransactionNumber": "7142059434",
  "PlutusTransactionReferenceID": "308626",
  "Amount": "10449400",
  "HostResponse": "00",
  "TransactionStatus": "Approved",
  "TransactionType": "CHARGE",
  "TerminalId": "43133658",
  "MerchantId": "JZQ992",
  "RRN": "000000000030",
  "ApprovalCode": "308626",
  "CardNumber": "*****2014",
  "CardType": "CREDIT",
  "CardScheme": "VISA",
  "PaymentMode": "CARD",
  "IssuingBank": "ICICI BANK LTD",
  "BatchNumber": "12",
  "InvoiceNumber": "1045",
  "TransactionDateTime": "2026-07-11 13:54:05",
  "Currency": "INR"
}
```

8 Go-live checklist

1. HTTPS endpoint returns 200 to Pine Labs' test call.
2. Signature verification working (if secret provided).
3. Amount-in-paise conversion verified against a terminal receipt.
4. Idempotency + status mapping tested (success, fail, void / refund).
5. Pine Labs enables callbacks for your live MID / TIDs.

Shared as integration guidance based on our production experience. Please confirm the exact field names and signature scheme with your Pine Labs integration SPOC before go-live.