

Same Day Solution — Settlement API

Partner API for Bank Settlements & Payouts | Powered by **Same Day Solution Pvt. Ltd.**

v1.0.0

Table of Contents

- 1. [Pre-requisites & Setup](#)
- 2. [Authentication](#)
- 3. [Settlement Flow](#)
- 4. [Get Balance](#)
- 5. [Add & Verify Account](#)
- 6. [List Accounts](#)
- 7. [Get Charges](#)
- 8. [Transfer \(Settlement\)](#)
- 9. [Check Status](#)
- 10. [List Transactions](#)
- 11. [Delete Account](#)
- 12. [Error Codes](#)
- 13. [Code Samples](#)

1. Pre-requisites & Setup

- 1. **API Key & Secret** — Generated by admin from the Partner API panel
- 2. **IP Whitelist** — Your server IP must be whitelisted by admin
- 3. **Settlement Enabled** — Admin must enable the Settlement toggle for your partner account
- 4. **Wallet Balance** — Admin must credit your partner wallet before use

ENVIRONMENT	BASE URL
Production	<code>https://api.samedaysolution.in</code>

2. Authentication

Every request requires **3 custom headers**:

HEADER	DESCRIPTION
<code>x-api-key</code>	Your partner API key
<code>x-signature</code>	HMAC-SHA256 signature
<code>x-timestamp</code>	Current Unix timestamp in milliseconds

Signature Formula

For **POST** requests:

```
signature = HMAC_SHA256(api_secret, JSON.stringify(body) + timestamp)
```

For **GET / DELETE** requests:

```
signature = HMAC_SHA256(api_secret, "" + timestamp)
```

IMPORTANT — Compact JSON Required:

The signature **MUST** be computed on the **compact (minified) JSON body** — no extra whitespace, no newlines, no indentation. The server parses and re-serializes your body before verifying the signature.

`JSON.stringify(bodyObject)` produces compact JSON. If you sign formatted/indented JSON, the signature **WILL fail** and your partner scheme charges will not be applied correctly.

Security:

- IP whitelisting enforced — requests from non-whitelisted IPs get `401`
- Timestamp must be within **5 minutes** of server time
- `api_secret` is used only for signing — never send it in headers

3. Settlement Flow

1 Get Balance — Check wallet balance



2 Add & Verify Account — Penny-drop verification (₹4 charge)



3 List Accounts — View verified accounts



4 Get Charges — Check transfer charges for a given amount



5 Transfer — Initiate settlement bank transfer



6 Check Status — Track transaction status & get UTR

Key Points:

- All transfers go to **pre-verified accounts** only
- Account verification uses **penny-drop** (₹1 transfer) and costs **₹4**
- Transfer charges are resolved from your **partner scheme** (check via Get Charges endpoint)
- Duplicate prevention: **2-minute cooldown** per account
- If transfer fails, amount is **auto-refunded** to partner wallet

4. Get Balance

GET

Get Wallet Balance

/api/partner/settlement/balance

Check your partner wallet balance. No request body required.

Response Fields

FIELD	TYPE	DESCRIPTION
success	Boolean	Request success status
balance	Number	Available wallet balance (in rupees)
is_frozen	Boolean	Whether wallet is frozen
freeze_reason	String null	Reason if wallet is frozen

Example Response

200

```
{
  "success": true,
  "balance": 125000.50,
  "is_frozen": false,
  "freeze_reason": null
}
```

5. Add & Verify Account

POST

Add & Verify Bank Account

/api/partner/settlement/accounts

Add a bank account and verify via penny-drop (₹1 transfer). **Verification charge: ₹4** (debited from wallet).

Request Body

FIELD	TYPE	REQUIRED	DESCRIPTION
account_number	String	Yes	Bank account number
ifsc_code	String	Yes	IFSC code (11 chars, format: XXXX0XXXXXX)
account_holder_name	String	Yes	Account holder name
contact_name	String	No	Contact person name
contact_email	String	No	Contact email address
contact_mobile	String	No	Contact mobile (10 digits)

Example Request

```
{
  "account_number": "50100104420821",
  "ifsc_code": "HDFC0003756",
  "account_holder_name": "Manish Kumar Shah",
  "contact_name": "Manish",
  "contact_email": "manish@example.com",
  "contact_mobile": "9971969046"
}
```

Response Fields

FIELD	TYPE	DESCRIPTION
success	Boolean	Request success status
verified	Boolean	Whether account was verified
verification_status	String	SUCCESS PENDING FAILED
verified_name	String	Name returned by bank
account.id	String	Account ID — use this for transfers

charge_deducted

Number

₹4

Example Response

200 Account Verified

```
{
  "success": true,
  "verified": true,
  "verification_status": "SUCCESS",
  "verified_name": "MANISH KUMAR SHAH",
  "account": {
    "id": "acc_a1b2c3d4e5f6",
    "account_number": "50100104420821",
    "ifsc_code": "HDFC0003756",
    "account_holder_name": "Manish Kumar Shah"
  },
  "charge_deducted": 4
}
```

If `verification_status` is `PENDING`, the account will be verified shortly. Use **List Accounts** to check the updated status.

6. List Accounts

GET

List Settlement Accounts

/api/partner/settlement/accounts

List all verified and active settlement accounts. No request body required.

Response Fields

FIELD	TYPE	DESCRIPTION
success	Boolean	Request success status
accounts[]	Array	List of account objects
accounts[].id	String	Account ID (use for transfers)
accounts[].account_number	String	Bank account number
accounts[].ifsc_code	String	IFSC code
accounts[].account_holder_name	String	Registered name
accounts[].is_verified	Boolean	Verification status
accounts[].verified_name	String	Name returned by bank
count	Integer	Total number of accounts

Example Response

200

```
{
  "success": true,
  "accounts": [
    {
      "id": "acc_a1b2c3d4e5f6",
      "account_number": "50100104420821",
      "ifsc_code": "HDFC0003756",
      "account_holder_name": "Manish Kumar Shah",
      "is_verified": true,
      "verified_name": "MANISH KUMAR SHAH"
    }
  ],
  "count": 1
}
```

7. Get Charges

GET

Get Transfer Charges

/api/partner/settlement/charges?amount=5000&mode=IMPS

Check settlement charges for a given amount and transfer mode.

Query Parameters

PARAMETER	TYPE	REQUIRED	DESCRIPTION
amount	Integer	Yes	Transfer amount in rupees
mode	String	No	IMPS (default) NEFT RTGS

Response Fields

FIELD	TYPE	DESCRIPTION
success	Boolean	Request success status
scheme_name	String	Applied partner commission scheme name
charges	Number	Additional charges as per your partner scheme
gst_amount	Number	GST on service charge (18%)
total_charge	Number	Total charge (charges + GST)
total_debit	Number	Total amount that will be debited from wallet (amount + total_charge)

Note: Charges are resolved from your **partner scheme**. The `total_debit` = transfer `amount` + `total_charge`. Use this endpoint to verify charges before initiating a transfer.

Example Response

200

```
{
  "success": true,
  "amount": 5000,
  "mode": "IMPS",
  "scheme_name": "Default Settlement Scheme",
  "charges": 10,
  "gst_amount": 1.80,
  "total_charge": 11.80,
```

```
"total_debit": 5011.80  
}
```

8. Transfer (Settlement)

POST

Initiate Settlement Transfer

/api/partner/settlement/transfer

Initiate a bank transfer to a pre-verified settlement account.

Request Body

FIELD	TYPE	REQUIRED	DESCRIPTION
account_id	String	Yes	Verified account ID from Add & Verify or List Accounts
amount	Integer	Yes	Transfer amount in rupees
mode	String	No	IMPS (default) NEFT RTGS
narration	String	No	Optional remark/narration

Example Request

```
{
  "account_id": "acc_a1b2c3d4e5f6",
  "amount": 5000,
  "mode": "IMPS",
  "narration": "Settlement transfer"
}
```

Response Fields

FIELD	TYPE	DESCRIPTION
success	Boolean	Request success status
transaction.id	String	Internal transaction ID
transaction.reference_id	String	Reference ID — use for status check
transaction.order_id	String	Provider order ID
transaction.utr	String null	UTR number (if available immediately)
transaction.status	String	SUCCESS PENDING FAILED
transaction.amount	Number	Transfer amount
transaction.charges	Number	Service charge applied (per partner scheme)

`transaction.total_debited`

Number

Total debited from wallet (amount + charges + GST)

Example Response

200 Transfer Initiated

```
{
  "success": true,
  "transaction": {
    "id": "txn_x1y2z3w4",
    "reference_id": "ref_abc123def456",
    "order_id": "ORD_20260708_001",
    "utr": "HDFC26070812345",
    "status": "SUCCESS",
    "amount": 5000,
    "charges": 11.80,
    "total_debited": 5011.80
  }
}
```

Duplicate Prevention: A 2-minute cooldown is enforced per account. If you try to transfer to the same account within 2 minutes, the request will be rejected.

If status is PENDING: Use the **Check Status** API to track. If transfer fails, the amount is **auto-refunded** to your partner wallet.

9. Check Status

GET

Check Transaction Status

/api/partner/settlement/status?reference_id={reference_id}

Check the status of a settlement transaction. If PENDING, the API also checks with the provider for live status updates.

Query Parameters

PARAMETER	TYPE	REQUIRED	DESCRIPTION
reference_id	String	Yes	Reference ID from the Transfer response

Transaction Statuses

STATUS	DESCRIPTION	ACTION
SUCCESS	Transfer completed — UTR available	No action needed
PENDING	Transfer is processing	Wait and check again
FAILED	Transfer failed — amount auto-refunded	May retry the transfer

Response Fields

FIELD	TYPE	DESCRIPTION
transaction.status	String	SUCCESS PENDING FAILED
transaction.utr	String null	UTR number (available on success)
transaction.order_id	String	Provider order ID
transaction.amount	Number	Transfer amount
transaction.status_message	String	Status description

Example Response

200

```
{
  "success": true,
  "transaction": {
    "reference_id": "ref_abc123def456",
```

```
"order_id": "ORD_20260708_001",  
"status": "SUCCESS",  
"utr": "HDFC26070812345",  
"amount": 5000,  
"charges": 11.80,  
"total_debited": 5011.80,  
"status_message": "Transfer completed successfully"  
}  
}
```

If a **PENDING** transaction is found to be **FAILED** on status check, the amount is **automatically refunded** to your wallet.

10. List Transactions

GET

List Recent Transactions

/api/partner/settlement/status?list=true&limit=20

List recent settlement transactions.

Query Parameters

PARAMETER	TYPE	REQUIRED	DESCRIPTION
list	Boolean	Yes	Set to <code>true</code> to enable list mode
limit	Integer	No	Number of transactions (default: 20, max: 50)

Response Fields (per transaction)

FIELD	TYPE	DESCRIPTION
id	String	Transaction ID
reference_id	String	Reference ID
order_id	String	Provider order ID
utr	String null	UTR number
amount	Number	Transfer amount
charges	Number	Charges applied
total_debited	Number	Total amount debited
mode	String	IMPS NEFT RTGS
status	String	SUCCESS PENDING FAILED
account_number	String	Destination account
account_holder_name	String	Beneficiary name
created_at	String	Transaction timestamp (ISO 8601)

Example Response

200

```
{
  "success": true,
  "transactions": [
    {
      "id": "txn_x1y2z3w4",
      "reference_id": "ref_abc123def456",
      "order_id": "ORD_20260708_001",
      "utr": "HDFC26070812345",
      "amount": 5000,
      "charges": 11.80,
      "total_debited": 5011.80,
      "mode": "IMPS",
      "status": "SUCCESS",
      "account_number": "50100104420821",
      "account_holder_name": "Manish Kumar Shah",
      "created_at": "2026-07-08T10:30:00.000Z"
    }
  ],
  "count": 1
}
```

11. Delete Account

DELETE

Deactivate Settlement Account

/api/partner/settlement/accounts?id={account_id}

Soft-delete (deactivate) a settlement account. Deactivated accounts cannot be used for transfers.

Query Parameters

PARAMETER	TYPE	REQUIRED	DESCRIPTION
id	String	Yes	Account ID to deactivate

Example Response

200

```
{
  "success": true,
  "message": "Account deactivated successfully"
}
```

12. Error Codes

All error responses follow this structure:

```
{
  "success": false,
  "error": {
    "code": "ERROR_CODE",
    "message": "Human-readable description"
  }
}
```

HTTP	ERROR CODE	DESCRIPTION
401	INVALID_API_KEY	API key not found or disabled
401	INVALID_SIGNATURE	Signature mismatch
401	TIMESTAMP_EXPIRED	Timestamp older than 5 minutes

401	IP_NOT_WHITELISTED	Request IP not in whitelist
400	INSUFFICIENT_BALANCE	Wallet balance too low for transfer
400	WALLET_FROZEN	Wallet is frozen by admin
400	ACCOUNT_NOT_VERIFIED	Account not yet verified
400	DUPLICATE_TRANSFER	Transfer to same account within 2-minute cooldown
404	ACCOUNT_NOT_FOUND	Account ID not found
404	TRANSACTION_NOT_FOUND	Transaction reference not found

13. Code Samples

Node.js — Complete Flow

```
const crypto = require('crypto');

const API_KEY    = 'pk_live_YOUR_API_KEY';
const API_SECRET = 'sk_live_YOUR_API_SECRET';
const BASE_URL   = 'https://api.samedaysolution.in';

function getHeaders(body = null) {
  const timestamp = Date.now().toString();
  const payload = (body ? JSON.stringify(body) : '') + timestamp;
  const signature = crypto.createHmac('sha256', API_SECRET)
    .update(payload).digest('hex');
  return {
    'Content-Type': 'application/json',
    'x-api-key': API_KEY,
    'x-signature': signature,
    'x-timestamp': timestamp
  };
}

// 1. Check Balance
async function getBalance() {
  const res = await fetch(`${BASE_URL}/api/partner/settlement/balance`, {
    headers: getHeaders()
  });
  return res.json();
}

// 2. Add & Verify Account
async function addAccount(accountNumber, ifsc, holderName, mobile) {
```

```

const body = {
  account_number: accountNumber,
  ifsc_code: ifsc,
  account_holder_name: holderName,
  contact_name: holderName,
  contact_mobile: mobile
};
const res = await fetch(`${BASE_URL}/api/partner/settlement/accounts`, {
  method: 'POST', headers: getHeaders(body), body: JSON.stringify(body)
});
return res.json();
}

// 3. List Accounts
async function listAccounts() {
  const res = await fetch(`${BASE_URL}/api/partner/settlement/accounts`, {
    headers: getHeaders()
  });
  return res.json();
}

// 4. Transfer
async function transfer(accountId, amount, mode = 'IMPS') {
  const body = { account_id: accountId, amount, mode };
  const res = await fetch(`${BASE_URL}/api/partner/settlement/transfer`, {
    method: 'POST', headers: getHeaders(body), body: JSON.stringify(body)
  });
  return res.json();
}

// 5. Check Status
async function checkStatus(referenceId) {
  const res = await fetch(
    `${BASE_URL}/api/partner/settlement/status?reference_id=${referenceId}`,
    { headers: getHeaders() }
  );
  return res.json();
}

```

Python

```

import hmac, hashlib, json, time, requests

API_KEY    = "pk_live_YOUR_API_KEY"
API_SECRET = "sk_live_YOUR_API_SECRET"
BASE_URL   = "https://api.samedaysolution.in"

def call_api(method, path, body=None, params=None):
    timestamp = str(int(time.time() * 1000))
    body_str = json.dumps(body, separators=(",", ":")) if body else ""

```

```
payload = body_str + timestamp
signature = hmac.new(
    API_SECRET.encode(), payload.encode(), hashlib.sha256
).hexdigest()

hdrs = {
    "Content-Type": "application/json",
    "x-api-key": API_KEY,
    "x-signature": signature,
    "x-timestamp": timestamp,
}

url = f"{BASE_URL}{path}"
if method == "GET":
    return requests.get(url, headers=hdrs, params=params).json()
elif method == "DELETE":
    return requests.delete(url, headers=hdrs, params=params).json()
return requests.post(url, data=body_str, headers=hdrs).json()

# Check Balance
balance = call_api("GET", "/api/partner/settlement/balance")

# Add Account
account = call_api("POST", "/api/partner/settlement/accounts", {
    "account_number": "50100104420821",
    "ifsc_code": "HDFC0003756",
    "account_holder_name": "Manish Kumar Shah",
    "contact_mobile": "9971969046"
})

# Transfer
txn = call_api("POST", "/api/partner/settlement/transfer", {
    "account_id": account["account"]["id"],
    "amount": 5000,
    "mode": "IMPS"
})

# Check Status
status = call_api("GET", "/api/partner/settlement/status",
    params={"reference_id": txn["transaction"]["reference_id"]})
```

Same Day Solution Pvt. Ltd.

Settlement API | Document generated: July 2026

For API key provisioning, IP whitelisting, wallet top-up, or support — contact your account manager.