



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Name	Manish Shashikant Jadhav
UID	2023301005
Subject	Design and Analysis of Algorithms (DAA)
Experiment No.	2
Aim	Experiment based on divide and conquer approach.
Code	<pre>#include <stdio.h> #include <stdlib.h> #include <time.h> void merge(int arr[], int l, int m, int r) { int i, j, k; int n1 = m - l + 1; int n2 = r - m; int L[n1], R[n2]; for (i = 0; i < n1; i++) L[i] = arr[l + i]; for (j = 0; j < n2; j++) R[j] = arr[m + 1 + j]; i = 0; j = 0; k = l; while (i < n1 && j < n2) { if (L[i] <= R[j]) { arr[k] = L[i]; i++; } else</pre>



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

```
        {
            arr[k] = R[j];
            j++;
        }
        k++;
    }

    while (i < n1)
    {
        arr[k] = L[i];
        i++;
        k++;
    }

    while (j < n2)
    {
        arr[k] = R[j];
        j++;
        k++;
    }
}

void mergeSort(int arr[], int l, int r)
{
    if (l < r)
    {
        int m = l + (r - l) / 2;

        mergeSort(arr, l, m);
        mergeSort(arr, m + 1, r);

        merge(arr, l, m, r);
    }
}

void quickSort(int arr[], int low, int high)
{

```



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

```
if (low < high)
{
    int pi = partition(arr, low, high);

    quickSort(arr, low, pi - 1);
    quickSort(arr, pi + 1, high);
}

int partition(int arr[], int low, int high)
{
    int pivot = arr[high];
    int i = (low - 1);

    for (int j = low; j <= high - 1; j++)
    {
        if (arr[j] < pivot)
        {
            i++;
            swap(&arr[i], &arr[j]);
        }
    }

    swap(&arr[i + 1], &arr[high]);
    return (i + 1);
}


void swap(int *a, int *b)
{
    int temp = *a;
    *a = *b;
    *b = temp;
}

void main()
{
    srand(time(NULL));
```





BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering


```
FILE *fileptr;
FILE *fileptr1;
int n = 100000;
fileptr = fopen("inp.txt", "w");
int arr[n];
for (int j = 0; j < n; j++)
{
    arr[j] = rand() % 100000 + 1;
    fprintf(fileptr, "%d\n", arr[j]);
}
fclose(fileptr);
fileptr1 = fopen("time.csv", "w");
printf("Block Size\tMerge Sort\tQuick Sort\n");
fileptr = fopen("inp.txt", "r");
for (int p = 99; p < n; p = p + 100)
{
    int array[p + 1];
    int array1[p + 1];
    for (int j = 0; j < p; j++)
    {
        array[j] = arr[j];
        fscanf(fileptr, "%d", &array1[j]);
    }
    clock_t begin = clock();
    mergeSort(array, 0, p);
    clock_t mid = clock();
    quickSort(array1, 0, p);
    clock_t end = clock();
    double time_spent = (double)(mid - begin);
    double time_spent1 = (double)(end - mid);
    printf("%d\t%lf\t%lf\n", p + 1, time_spent, time_spent1);
    fprintf(fileptr1, "%d,%lf,%lf\n", p + 1, time_spent,
time_spent1);
}
printf("\n");
}
```



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Graphs





BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering


**Pseudo Code
& Example**


Experiment No. 2

* Merge Sort:-

• Pseudo code:- (A, p, q, r) :

1. $n_1 \leftarrow q - p + 1$
2. $n_2 \leftarrow r - q$
3. create arrays $L[1 \dots n_1 + 1]$ and $R[1 \dots n_2 + 1]$
4. for $i \leftarrow 1$ to n_1
do $L[i] \leftarrow A[p + i - 1]$
- 5.
6. for $j \leftarrow 1$ to n_2
do $R[j] \leftarrow A[q + j]$
- 7.
8. $L[n_1 + 1] \leftarrow \infty$
9. $R[n_2 + 1] \leftarrow \infty$
10. $i \leftarrow 1$
11. $j \leftarrow 1$
12. for $k \leftarrow p$ to r
do if $L[i] \leq R[j]$
then $A[k] \leftarrow L[i]$
 $i \leftarrow i + 1$
else $A[k] \leftarrow R[j]$
 $j \leftarrow j + 1$ ($j = j + 1$)
- 13.
- 14.
- 15.
- 16.
- 17.





BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

• Quick Sort Example: -

[28 | 9 | 13 | 2]

Pivot = 28.

① Partition Around Pivot.

[9 | 13 | 2 | 28]

[9 | 13 | 2]

[28]

↓

↓

② pivot: 9

No action

Partitioning

Need

[2 | 9 | 13]

[28]

Merge Sorted Sub-arrays

[2 | 9 | 13 | 28]

Conclusion

Hence, by completing this experiment I came to know about divide and conquer approach.