



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Name	Manish Shashikant Jadhav
UID	2023301005
Subject	Design and Analysis of Algorithms.
Experiment No.	1.A
Aim	To implement the various functions e.g. linear, non-linear, quadratic, exponential etc.
Code	<pre>#include <stdio.h> #include <math.h> // Function prototypes double linear(int n); // Returns n double powerOfTwo(int n); // Returns 2^n double cubic(int n); // Returns n^3 double nLogN(int n); // Returns n * log2(n) double logFactorial(int n); // Returns (lg n)! // (Factorial of logarithm) double lnLnN(int n); // Returns ln(ln(n)) double nTimesTwoToN(int n); // Returns n * 2^n double powerOfTwoLog(int n); // Returns 2^lg(n) double lnN(int n); // Returns ln(n) double exponentialTwoTwoNPlusOne(int n); // Returns 2^(2^n+1) double factorial(int n); // Returns n! // Function implementation of n double linear(int n) { return n; } // Function implementation of 2^n double powerOfTwo(int n) { return pow(2, n); }</pre>



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

```
// Function implementation of n^3
double cubic(int n)
{
    return pow(n, 3);
}

// Function implementation of n * log2(n)
double nLogN(int n)
{
    return n * log2(n);
}

// Function implementation of (lg n)! (Factorial of logarithm)
double logFactorial(int n)
{
    return tgamma(log2(n) + 1); // Using tgamma for gamma function
    (factorial )
}

// Function implementation of ln(ln(n))
double lnLnN(int n)
{
    return log(log(n));
}

// Function implementation of n * 2^n
double nTimesTwoToN(int n)
{
    return n * pow(2, n);
}

// Function implementation of 2^lg(n)
double powerOfTwoLog(int n)
{
    return pow(2, log2(n));
}
```



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

```
// Function implementation of ln(n)
double lnN(int n)
{
    return log(n);
}

// Function implementation of 2^(2^n+1)
double exponentialTwoTwoNPlusOne(int n)
{
    return pow(2, pow(2, n) + 1);
}

// Function implementation of n!
double factorial(int n)
{
    if (n == 0 || n == 1)
        return 1;
    else
        return n * factorial(n - 1);
}

int main()
{
    int n;


    // Calculate and display values for n from 0 to 100 with an
    // increment of 1
    for (n = 0; n <= 100; n++)
    {
        printf("n = %d:\n", n);
        printf("1. n: %d\n", (int)linear(n));
        printf("2. 2^n: %f\n", powerOfTwo(n));
        printf("3. n^3: %f\n", cubic(n));
        printf("4. n lg n: %f\n", nLogN(n));
        printf("5. (lg n)! (Factorial of logarithm): %f\n",
logFactorial(n));
    }
}
```




BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering




```
printf("6. ln ln n: %f\n", lnLnN(n));  
printf("7. n*2^n: %f\n", nTimesTwoToN(n));  
printf("8. 2^lg n: %f\n", powerOfTwoLog(n));  
printf("9. ln n: %f\n", lnN(n));  
printf("10. 2^(2^n+1): %f\n", exponentialTwoTwoNPlusOne(n));  
printf("\n");  
}  
  
// Calculate and display values for n from 0 to 20 with an  
// increment of 1 for the factorial function  
printf("Factorial Function (n!):\n");  
for (n = 0; n <= 20; n++)  
{  
    printf("n = %d: %.0f\n", n, factorial(n));  
}  
  
return 0;  
}
```


Graph






BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering






BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering


$(\lg n)!$




$\ln(\ln(n))$





$n * 2^n$






BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering





BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering





BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

**Solved
Problem:**

Date _____
Page _____

Experiment No. 0.

- 1) $n = 5$, then $n = 5$.
- 2) $2n$, $n = 3$, then $2n = 2 \times 3 = 6$.
- 3) n^3 , $n = 4$ then $n^3 = 4^3 = 64$.
- 4) $n \log n$, $n = 6$, then $n \log n = 6 \times \log(6) \approx 6 \times 1.79 \approx 10.74$.
- 5) $(\log n)!$, $n = 10$.
then $(\log 10)! = (\log 10)! = 2! = 2$.
- 6) $\ln(\ln(n))$, $n = 9$
then $\ln(\ln(9)) \approx \ln(2.20) \approx 0.79$.
- 7) $n \times 2^n$, $n = 3$.
then $3 \times 2^3 = 3 \times 8 = 24$.
- 8) $n^{\log n}$, $n = 2$.
then $2^{\log 2} = 2^1 = 2$.
- 9) $\ln(n)$, $n = 7$, then $\ln(7) \approx 1.95$.
- 10) 2^{n+1} , $n = 1$
then $2^{1+1} = 2^2 = 4$.

Conclusion

Hence, by completing this experiment I came to know about to implement the various functions e.g. linear, non-linear, quadratic, exponential etc.



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Experiment No.	1.B
Aim	Experiment on finding the running time of an algorithm(Insertion Sort and Selection Sort).
Code	<pre>#include <stdio.h> #include <stdlib.h> #include <time.h> void insertSort(int *arr, int n) { for (int j = 1; j < n; j++) { int key = arr[j]; int i = j - 1; while (i > -1 && key < arr[i]) { arr[i + 1] = arr[i]; i = i - 1; } arr[i + 1] = key; } } void selectSort(int *a, int n) { int temp; for (int i = 0; i < n - 1; i++) { int p = i; for (int j = i + 1; j < n; j++) { if (a[p] > a[j]) { p = j; } } if (p != i) { temp = a[i]; a[i] = a[p]; a[p] = temp; } } }</pre>



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

```
        temp = a[i];
        a[i] = a[p];
        a[p] = temp;
    }
}
}
void main()
{
    srand(time(NULL));
    FILE *fileptr;
    FILE *fileptr1;
    int n = 100000;
    fileptr = fopen("inp.txt", "w");
    int arr[n];
    for (int j = 0; j < n; j++)
    {
        arr[j] = rand() % 100000 + 1;
        fprintf(fileptr, "%d\n", arr[j]);
    }
    fclose(fileptr);

    fileptr1 = fopen("time.csv", "w");
    printf("Block Size\tInsertion Sort\tSelection sort\n");

    fileptr = fopen("inp.txt", "r");
    for (int p = 99; p < n; p = p + 100)
    {
        int array[p + 1];
        int array1[p + 1];
        for (int j = 0; j < p; j++)
        {
            array[j] = arr[j];
            fscanf(fileptr, "%1d", &array1[j]);
        }
        clock_t begin = clock();
        insertSort(array, p + 1);
        clock_t mid = clock();
```




BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering


```
selectSort(array1, p + 1);  
clock_t end = clock();  
double time_spent = (double)(mid - begin);  
double time_spent1 = (double)(end - mid);  
printf("%d\t%lf\t%lf\n", p + 1, time_spent, time_spent1);  
fprintf(fileptr1, "%d,%lf,%lf\n", p + 1, time_spent,  
time_spent1);  
}  
printf("\n");  
}
```


Graph:

Insertion Sort




Selection Sort





BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering





BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Insertion Sort

Pseudocode and example:

Experiment No. 1.

- * Insertion Sort :-
- Pseudocode :-

```
procedure insertionSort (arr)
    n = length(arr)
    for i from 1 to n-1
        key = arr[i]
        j = i-1
        while j >= 0 and arr[j] > key
            arr[j+1] = arr[j]
            j = j-1
        end while
        arr[j+1] = key
    end for
end procedure.
```

- Ex. 28, 9, 13, 2, 4, 6.

a) Step 1: 28 9 13 2 4 6 (Swap 28 and 9)


b) Step 2: 9 28 13 2 4 6 (Swap 13 and 28)

c) Step 3: 9, 13, 28, 2, 4, 6 (Swap 28 and 2 and insert 2 at correct pos.)

d) Step 4: 2, 9, 13, 28, 4, 6 (Swap 28 and 4 and insert 4 at correct position).

e) Step 5: 2, 4, 9, 13, 28, 6. (Swap 28 and 6 and insert 6 at correct position).

f) Final Sorted Array: 2, 4, 6, 9, 13, 28.




BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Selection Sort

Pseudocode and example:

- * selection sort :-
- PseudoCode:-
 procedure selectionSort (arr)
 n = length (arr)
 for i from 0 to n-2
 minIndex = i
 for j from i+1 to n-1
 if arr[j] < arr[minIndex]
 minIndex = j
 end if
 end for
 swap arr[i] and arr[minIndex]
 end for
 end procedure.
 - Ex. 28, 9, 13, 2, 4, 6.
 a) Step 1: Min. is 2 (at index 3). Swap to at 0.
 ∴ 2, 28, 9, 13, 4, 6
 b) Step 2: Min. is 4. (at index 4) swap to index 1.
 ∴ 2, 4, 28, 9, 13, 6.
 c) Step 3: Min. is 6 (at index 5) swap to index 2.
 ∴ 2, 4, 6, 28, 9, 13
 d) Step 4: Min. is 9 (at index 4) swap to index 3.
 ∴ 2, 4, 6, 9, 28, 13.
 e) Step 5: Min. is 13 (at index 5) swap to index 4
 ∴ Final sorted array = 2, 4, 6, 9, 28, 13.



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Conclusion	Hence, by completing this experiment I came to know about finding the running time of an algorithm(Insertion Sort and Selection Sort).
-------------------	--