



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Name	Manish Shashikant Jadhav
UID	2023301005
Subject	Design and Analysis of Algorithms (DAA)
Experiment No.	7
Aim	To implement Backtracking (N-Queen's problem and sum of subsets).
Code:	<pre>#include <stdio.h> #include <stdlib.h> #include <stdbool.h> #define MAX_SIZE 20 int board[MAX_SIZE]; // Array to store the positions of queens in N-Queens problem int solutionCount = 0; // Counter to keep track of the number of solutions found // Function to print a solution to the N-Queens problem void printNQueensSolution(int n); // Function to check if placing a queen at position (row, col) is safe bool isSafe(int row, int col); // Recursive function to solve the N-Queens problem void solveNQueens(int n, int row); // Function to print a subset of a set void printSubset(int set[], int size); // Recursive function to solve the Sum of Subsets problem void solveSubsetSum(int set[], int n, int targetSum, int index, int subset[], int subsetIndex);</pre>



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

```
int main() {
    int choice;
    while (1) {
        printf("\nChoose an option:\n");
        printf("1. Solve N-Queens problem\n");
        printf("2. Solve Sum of Subsets problem\n");
        printf("3. Exit\n");
        printf("Enter your choice: ");
        scanf("%d", &choice);

        if (choice == 1) {
            int n;
            printf("\nEnter the number of queens (N): ");
            scanf("%d", &n);
            printf("\nN-Queens Solution(s):\n");
            solveNQueens(n, 0);
            printf("\nTotal solutions: %d\n", solutionCount);
            solutionCount = 0;
        } else if (choice == 2) {
            int n, set[MAX_SIZE], targetSum;
            printf("\nEnter the number of elements in the set: ");
            scanf("%d", &n);
            printf("Enter the elements of the set:\n");
            for (int i = 0; i < n; i++) {
                scanf("%d", &set[i]);
            }
            printf("Enter the target sum: ");
            scanf("%d", &targetSum);
            int subset[MAX_SIZE];
            printf("\nSubsets with sum equal to %d:\n", targetSum);
            solveSubsetSum(set, n, targetSum, 0, subset, 0);
        } else if (choice == 3) {
            break;
        } else {
            printf("\nInvalid choice. Please try again.\n");
        }
    }
}
```



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

```
    }  
}  
return 0;  
}  
  
void printNQueensSolution(int n) {  
    printf("[");  
    for (int i = 0; i < n - 1; i++) {  
        printf("%d, ", board[i]);  
    }  
    printf("%d]\n", board[n - 1]);  
}  
  
bool isSafe(int row, int col) {  
    // Check if there is a queen in the same column or in the  
    // diagonal positions  
    for (int i = 0; i < row; i++) {  
        if (board[i] == col || abs(board[i] - col) == abs(i -  
row)) {  
            return false;  
        }  
    }  
    return true;  
}  
  
void solveNQueens(int n, int row) {  
    // Base case: If all queens are placed, print the solution  
    if (row == n) {  
        printNQueensSolution(n);  
        solutionCount++;  
        return;  
    }  
    // Try placing a queen in each column of the current row  
    for (int col = 0; col < n; col++) {  
        if (isSafe(row, col)) {  
            board[row] = col;  
            solveNQueens(n, row + 1);  
        }  
    }  
}
```



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

```
    }  
    }  
}  
  
void printSubset(int set[], int size) {  
    printf("{");  
    for (int i = 0; i < size - 1; i++) {  
        printf("%d, ", set[i]);  
    }  
    printf("%d}\n", set[size - 1]);  
}  
  
void solveSubsetSum(int set[], int n, int targetSum, int  
index, int subset[], int subsetIndex) {  
    // Base case: If all elements of the set are considered,  
    check if subset sum is equal to targetSum  
    if (index == n) {  
        int sum = 0;  
        for (int i = 0; i < subsetIndex; i++) {  
            sum += subset[i];  
        }  
        if (sum == targetSum) {  
            printSubset(subset, subsetIndex);  
        }  
        return;  
    }  
    // Include the current element in the subset and recurse  
    subset[subsetIndex] = set[index];  
    solveSubsetSum(set, n, targetSum, index + 1, subset,  
subsetIndex + 1);  
    // Exclude the current element from the subset and recurse  
    solveSubsetSum(set, n, targetSum, index + 1, subset,  
subsetIndex);  
}
```



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Output

```
PS D:\Manish\SPIT> cd 'd:\Manish\SPIT\4th SEM\DAA\Exp7\output'
PS D:\Manish\SPIT\4th SEM\DAA\Exp7\output> & .\'backtracking.exe'

Choose an option:
1. Solve N-Queens problem
2. Solve Sum of Subsets problem
3. Exit
Enter your choice: 1

Enter the number of queens (N): 4

N-Queens Solution(s):
[1, 3, 0, 2]
[2, 0, 3, 1]

Total solutions: 2

Choose an option:
1. Solve N-Queens problem
2. Solve Sum of Subsets problem
3. Exit
Enter your choice: 2

Enter the number of elements in the set: 4
Enter the elements of the set:
1
2
3
4
Enter the target sum: 5

Subsets with sum equal to 5:
{1, 4}
{2, 3}

Choose an option:
1. Solve N-Queens problem
2. Solve Sum of Subsets problem
3. Exit
Enter your choice: 3
PS D:\Manish\SPIT\4th SEM\DAA\Exp7\output> 
```



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Pseudo Code

Page No. _____
Date: _____

YOUVA

DAA 2023301005
Experiment No. 7.


* Backtracking (N-Queen's and Sum of Subsets).

N=4 Queens

- Every row should have 1 queen.
- Every column should ~~be~~ have 1 queen.
- None of the queens should attack each other.

• Algorithm:-

```
bool nQueen(int board[N][N], int row) {
    if (row == N) return true;
    for (int col = 0; col < N; col++) {
        if (isSafe(board, row, col)) {
            board[row][col] = 1;
            if (nQueen(board, row + 1))
                return true;
            board[row][col] = 0;
        }
    }
    return false;
}
```



BHARATIYA VIDYA BHAVAN'S
SARDAR PATEL INSTITUTE OF TECHNOLOGY
(Empowered Autonomous Institute Affiliated to Mumbai University)
Department Of Computer Engineering

Sum of Subsets:-

Subset_Sum(x, T):

if $T=0$

return true

else if $T < 0$ or $x = \emptyset$

return false

else

$x \leftarrow$ any element of x

with \leftarrow Subset_Sum($x \setminus \{x\}, T-x$)

wout \leftarrow Subset_Sum($x \setminus \{x\}, T$)

return (with \vee wout)

Conclusion

Hence, by completing this experiment I came to know about implementation of Backtracking (N-Queen's problem and sum of subsets).