AETHER Platform — Unified Agent Onboarding Guide

Classification: *Technical Reference Manual*

Target Audience: *IT Administrators, Platform Engineers, Security Architects*

Status: *Release Specification (v3.0.0)*

This guide provides step-by-step instructions and programmatic payloads to onboard AI workers from all **12 supported platform connectors** in the AETHER system.

---

1. Connector Reference Table

AETHER maps every onboarded agent to its runtime connector, determining the authentication flow, API integration scope, and monitoring method.

Connector ID	Display Name	Connector Category	Target API Endpoint / Domain	Auth Method	Default Monitoring Method	required Scopes / Roles
`ms-copilot`	Microsoft Copilot	Microsoft	`https://graph.microsoft.com/v1.0`	OAuth 2.0 / Entra ID	`api-poll`	`User.Read.All`, `AuditLog.Read.All`
`ms-copilot-studio`	Copilot Studio	Microsoft	`https://api.powerplatform.com/v1`	OAuth 2.0 / Entra ID	`api-poll`	`Environment.Read`, `Bot.Read.All`
`azure-ai-foundry`	Azure AI Foundry	Microsoft	`https://management.azure.com/...`	Azure Managed Identity / SPN	`api-poll`	`Reader`, `Contributor`
`ms-entra-id`	Microsoft Entra ID	Microsoft	`https://graph.microsoft.com/v1.0/identity`	OAuth 2.0 Client Credentials	`api-poll`	`Directory.Read.All`, `Application.Read.All`
`openai-assistants`	OpenAI Assistants	OpenAI	`https://api.openai.com/v1`	API Key / Bearer Token	`api-poll`	`assistants.read`, `runs.read`
`azure-openai`	Azure OpenAI	Microsoft	`https://resource.openai.azure.com`	Managed Identity / API Key	`api-poll`	`Cognitive Services OpenAI User`
`langgraph`	LangGraph	Open Source	`https://api.smith.langchain.com/v1`	API Key	`sdk-push`	`runs.read`, `traces.read`
`crewai`	CrewAI	Open Source	`https://api.crewai.com/v1`	API Key	`sdk-push`	`crews.read`, `tasks.read`
`salesforce-agentforce`	Salesforce Agentforce	Salesforce	`https://domain.my.salesforce.com`	OAuth 2.0 / JWT Bearer	`webhook`	`api`, `einsteinanalytics`

Connector ID	Display Name	Connector Category	Target API Endpoint / Domain	Auth Method	Default Monitoring Method	required Scopes / Roles
`databricks`	Databricks Agents	Databricks	`https://workspace.cloud.databricks.com`	Service Principal / PAT	`api-poll`	`workspace.read`, `serving-endpoints.read`
`snowflake-cortex`	Snowflake Cortex	Snowflake	`https://account.snowflakecomputing.com`	Key Pair / OAuth	`api-poll`	`CORTEXUSER`, `DATAREADER`
`custom-agents`	Custom Enterprise Agents	Custom / SDK	`https://aether-api.contoso.com`	AETHER SDK / API Key	`sdk-push`	`agent.register`, `agent.heartbeat`

2. Onboarding Steps for All 12 Connectors

1. Microsoft Copilot (`ms-copilot`)

Used for generic Microsoft Copilots deployed across Microsoft 365, SharePoint, or Teams.

- **Endpoint URL:** `https://graph.microsoft.com/v1.0/users/user-id/chats`
- **Default Monitoring:** `api-poll`
- **JSON API Payload:**

```
{ "name": "M365 Legal Assistant", "platform": "Microsoft Copilot", "department": "Legal", "owner": "Sarah Chen", "endpoint": "https://graph.microsoft.com/v1.0/users/legal-bot-id/chats", "monthlyCost": 150.00, "tasksExecuted": 540, "monitoringMethod": "api-poll", "piiAccess": true, "financialAccess": false }
```

2. Copilot Studio (`ms-copilot-studio`)

Used for customized conversational agents built inside the Microsoft Copilot Studio authoring environment.

- **Endpoint URL:** `https://api.powerplatform.com/v1/environments/env-id/bots/bot-id`
- **Default Monitoring:** `api-poll`
- **JSON API Payload:**

```
{ "name": "HR Benefits Copilot", "platform": "Copilot Studio", "department": "HR", "owner": "Marcus Aurelius", "endpoint": "https://api.powerplatform.com/v1/environments/prod-env-123/bots/hr-bot-456", "monthlyCost": 250.00, "tasksExecuted": 1420, "monitoringMethod": "api-poll", "piiAccess": true, "financialAccess": false }
```

3. Azure AI Foundry (`azure-ai-foundry`)

For agents built, hosted, and managed using Azure's AI Foundry dashboard.

- **Endpoint URL:** `https://management.azure.com/subscriptions/sub-id/resourceGroups/rg/providers/Microsoft.MachineLearningServices/workspaces/ws`
- **Default Monitoring:** `api-poll`
- **JSON API Payload:**

```
{ "name": "Azure Support Classifier", "platform": "Azure AI Foundry", "department": "Customer Success",
"owner": "Sarah Chen", "endpoint": "https://management.azure.com/subscriptions/sub-999/resourceGroups/ai-rg/p
roviders/Microsoft.MachineLearningServices/workspaces/support-ws", "monthlyCost": 480.00, "tasksExecuted":
8900, "monitoringMethod": "api-poll", "piiAccess": false, "financialAccess": false }
```

4. Microsoft Entra ID (`ms-entra-id`)

For identity synchronization agents and autonomous directory access accounts running in Azure.

- **Endpoint URL:** `https://graph.microsoft.com/v1.0/identity/conditionalAccess/policies`
- **Default Monitoring:** `api-poll`
- **JSON API Payload:**

```
{ "name": "Entra ID Credential Rotator", "platform": "Microsoft Entra ID", "department": "Security", "owner":
"Manish Kapoor", "endpoint": "https://graph.microsoft.com/v1.0/identity/credential-rotator-agent",
"monthlyCost": 120.00, "tasksExecuted": 250, "monitoringMethod": "api-poll", "piiAccess": true,
"financialAccess": false }
```

5. OpenAI Assistants (`openai-assistants`)

For custom agents built using the OpenAI Assistants API (v1 or v2).

- **Endpoint URL:** `https://api.openai.com/v1/assistants/assistant-id`
- **Default Monitoring:** `api-poll`
- **JSON API Payload:**

```
{ "name": "Product Recommendation Assistant", "platform": "OpenAI", "department": "Marketing", "owner":
"Elena Rostova", "endpoint": "https://api.openai.com/v1/assistants/asst_xyz123abc", "monthlyCost": 350.00,
"tasksExecuted": 6800, "monitoringMethod": "api-poll", "piiAccess": false, "financialAccess": false }
```

6. Azure OpenAI (`azure-openai`)

For enterprise deployments accessing OpenAI models via secure Azure endpoints.

- **Endpoint URL:** `https://resource-name.openai.azure.com/openai/deployments/deployment-name`
- **Default Monitoring:** `api-poll`
- **JSON API Payload:**

```
{ "name": "Azure Summarization Model", "platform": "Azure OpenAI", "department": "Engineering", "owner":
"Sarah Chen", "endpoint":
"https://aether-openai-eastus.openai.azure.com/openai/deployments/gpt-4o-summarizer", "monthlyCost": 950.00,
"tasksExecuted": 12500, "monitoringMethod": "api-poll", "piiAccess": true, "financialAccess": false }
```

7. LangGraph (`langgraph`)

For stateful, multi-agent workflows running on LangGraph Cloud or locally.

- **Endpoint URL:** `https://api.smith.langchain.com/v1/projects/project-id`
- **Default Monitoring:** `sdk-push`
- **JSON API Payload:**

```
{ "name": "Software Engineer Graph", "platform": "LangGraph", "department": "Engineering", "owner": "Alex Mercer", "endpoint": "https://api.smith.langchain.com/v1/projects/langgraph-eng-project", "monthlyCost": 150.00, "tasksExecuted": 850, "monitoringMethod": "sdk-push", "piiAccess": false, "financialAccess": false }
```

8. CrewAI (`crewai`)

For cooperative multi-agent crews executing sequential or hierarchical tasks.

- **Endpoint URL:** `https://api.crewai.com/v1/crews/crew-id`
- **Default Monitoring:** `sdk-push`
- **JSON API Payload:**

```
{ "name": "Market Analysis Crew", "platform": "CrewAI", "department": "Marketing", "owner": "Lisa Williams", "endpoint": "https://api.crewai.com/v1/crews/crew-market-101", "monthlyCost": 180.00, "tasksExecuted": 400, "monitoringMethod": "sdk-push", "piiAccess": false, "financialAccess": false }
```

9. Salesforce Agentforce (`salesforce-agentforce`)

For Einstein-powered transactional agents running inside Salesforce CRM.

- **Endpoint URL:** `https://subdomain.my.salesforce.com/services/data/v62.0`
- **Default Monitoring:** `webhook`
- **JSON API Payload:**

```
{ "name": "Sales Lead Qualifier", "platform": "Salesforce Agentforce", "department": "Sales", "owner": "Lisa Williams", "endpoint": "https://contoso.my.salesforce.com/services/data/v62.0", "monthlyCost": 300.00, "tasksExecuted": 2500, "monitoringMethod": "webhook", "piiAccess": true, "financialAccess": false }
```

10. Databricks Agents (`databricks`)

For data analytics and machine learning retrieval agents hosted on Databricks serving endpoints.

- **Endpoint URL:** `https://workspace-id.cloud.databricks.com/api/2.0/serving-endpoints/endpoint-name`
- **Default Monitoring:** `api-poll`
- **JSON API Payload:**

```
{ "name": "Warehouse Inventory Analyst", "platform": "Databricks", "department": "Operations", "owner":
"David Miller", "endpoint":
"https://dbc-1234abcd-1234.cloud.databricks.com/api/2.0/serving-endpoints/inventory-endpoint", "monthlyCost":
550.00, "tasksExecuted": 3120, "monitoringMethod": "api-poll", "piiAccess": false, "financialAccess": false }
```


11. Snowflake Cortex (`snowflake-cortex`)

For database agents accessing LLMs and search functions natively inside Snowflake.

- **Endpoint URL:** `https://account-id.snowflakecomputing.com/api/v2`
- **Default Monitoring:** `api-poll`
- **JSON API Payload:**


```
{ "name": "Financial Fraud Detector", "platform": "Snowflake Cortex", "department": "Finance", "owner":
"David Miller", "endpoint": "https://contoso.snowflakecomputing.com/api/v2", "monthlyCost": 450.00,
"tasksExecuted": 5200, "monitoringMethod": "api-poll", "piiAccess": true, "financialAccess": true }
```


12. Custom Enterprise Agents (`custom-agents`)

For custom in-house Python, Node, or Go agents utilizing the AETHER Monitoring SDK.

- **Endpoint URL:** `https://your-internal-domain/api/v1/agents/agent-name`
- **Default Monitoring:** `sdk-push`
- **JSON API Payload:**


```
{ "name": "Enterprise Document Searcher", "platform": "Custom Agents", "department": "Engineering", "owner":
"Alex Mercer", "endpoint": "https://document-search.internal.contoso.com/api/v1/probe", "monthlyCost": 80.00,
"tasksExecuted": 150, "monitoringMethod": "sdk-push", "piiAccess": true, "financialAccess": false }
```


3. General Onboarding Verification Workflow

Once an agent is onboarded using the wizard or REST API:

1. **SQLite Insertion:** The backend writes the agent properties to the `agents` table in `aether.db`.
2. **Onboarding Event Broadcast:** An `AgentOnboarded` event is dispatched to the AETHER Event Bus.
3. **Supervisory Execution:** When you click the **"Run All Agents"** button in the Command Center:

- **Compliance Agent** audits the agent's PII and financial access against regulatory standards.
- **Risk Agent** calculates the risk score and evaluates threat levels.
- **Governance Agent** flags violations (e.g. `GOV-MODEL-001` if running on unapproved foundation models).
- **Cost Agent** reviews token and monthly spend efficiency.
- **Health Agent** performs an HTTP probe on the registry endpoint URL to verify latency and uptime.