CS 563: Software Maintenance And Evolution

Software Defect Prediction

Oregon State University, Spring 2024

Today's plan

- Learn about how to brainstorm and solve a problem using software defect prediction as an example
- In-class exercise: Brainstorm ideas for your own class projects

• What are software defects?

- What are software defects?
 - Bugs or errors in the code, documentation, requirements, etc.
 where the actual behavior or software differs from its expected behavior

- What are software defects?
 - Bugs or errors in the code, documentation, requirements, etc.
 where the actual behavior or software differs from its expected behavior


 What is software defect prediction and why should we care about predicting software defects?

- What are software defects?
 - Bugs or errors in the code, documentation, requirements, etc. where the actual behavior or software differs from its expected behavior
- What is software defect prediction and why should we care about predicting software defects?
 - A real-world software consists of many components
 - Testing all components in every release/update is time-consuming
 - What if there was a technique that tells us about the components that are more likely to have defects in the current release?
 - This would:
 - Increase the productivity of software engineers
 - Increase the quality of the product
 - Reduce the testing costs

 How to know which software modules are more likely to be defective (or buggy)?

 How to know which software modules are more likely to be defective (or buggy)?

Modules of previous versions of the software



Al Seminar on Al4SE: Opportunities and Challenges

- https://engineering.oregonstate.edu/events/ai-seminar-ai-software-engineering-ai4se-opportunities-and-challenges
- https://media.oregonstate.edu/media/t/1 jqu7qqrc/232665543

 How to know which software modules are more likely to be defective (or buggy)?

Modules of previous versions of the software

Module Id	x1 = branch count	x2= LOC	x3 = halstea d	 y = defective ?
1	18	1000	1	 No
2	30	900	10	 Yes
3	20	5000	3	 Yes

Machine Learning
Algorithm



New module x
for new version of
the software



Yes/No

Recap:

- What problem are we solving? (Problem statement)
- Why should one care about solving that problem? (Motivation)
- How are we solving it? (Approach)
 - **High-level idea:** use ML to predict the modules/components of software that are more likely to be buggy
 - Assumptions?

Recap:

- What problem are we solving? (Problem statement)
- Why should one care about solving that problem? (Motivation)
- How are we solving it? (Approach)
 - **High-level idea:** use ML to predict the modules/components of software that are more likely to be buggy
 - Assumptions:
 - Multiple versions/releases of software exist; You have access to the data that tells you
 defects encountered and fixed in the past.
 - What if above doesn't hold?

Recap:

- What problem are we solving? (Problem statement)
- Why should one care about solving that problem? (Motivation)
- How are we solving it? (Approach)
 - High-level idea: use ML to predict the modules/components of software that are more likely to be buggy
 - Assumptions:
 - Multiple versions/releases of software exist; You have access to the data that tells you
 defects encountered and fixed in the past.
 - What if above doesn't hold?
 - Find "similar" software application and predict across software

CS 563: Software Maintenance and Evolution Oregon State University

Software Defect Prediction

Refining Approach:

- How are we solving it? (Approach)
 - **High-level idea:** use ML to predict the modules/components of software that are more likely to be buggy
 - Assumptions:
 - Multiple versions/releases of software exist; You have access to the data that tells you
 defects encountered and fixed in the past.
 - What if above doesn't hold?
 - Find "similar" software application and predict across software
 - What else do we need to think about to concretize the high-level idea?

CS 563: Software Maintenance and Evolution Oregon State University

Software Defect Prediction

Refining Approach:

- How are we solving it? (Approach)
 - High-level idea: use ML to predict the modules/components of software that are more likely to be buggy
 - Assumptions:
 - Multiple versions/releases of software exist; You have access to the data that tells you
 defects encountered and fixed in the past.
 - What if above doesn't hold?
 - Find "similar" software application and predict across software
 - What else do we need to think about to concretize the high-level idea?
 - Input features

Refining Approach:

- How are we solving it? (Approach)
 - **High-level idea:** use ML to predict the modules/components of software that are more likely to be buggy
 - Assumptions:
 - Multiple versions/releases of software exist; You have access to the data that tells you
 defects encountered and fixed in the past.
 - What if above doesn't hold?
 - Find "similar" software application and predict across software
 - What else do we need to think about to concretize the high-level idea?
 - Input features
 - Machine Learning algorithm

These two will:

- demonstrate the novelty of your solution
- Impact the effectiveness of your solution

Refining Approach:

- How are we solving it? (Approach)
 - **High-level idea:** use ML to predict the modules/components of software that are more likely to be buggy
 - What input features can we use?
 - What is the key insight?

Refining Approach:

- How are we solving it? (Approach)
 - **High-level idea:** use ML to predict the modules/components of software that are more likely to be buggy
 - What input features can we use?
 - What is the **key insight**?

The more "complex" is the code, the more likely it is to be buggy or defective.

Refining Approach:

- How are we solving it? (Approach)
 - **High-level idea:** use ML to predict the modules/components of software that are more likely to be buggy
 - What input features can we use?
 - What is the key insight?
 The more "complex" is the code, the more likely it is to be buggy or defective.
 - How do we measure "code complexity"?

Refining Approach:

- How are we solving it? (Approach)
 - High-level idea: use ML to predict the modules/components of software that are more likely to be buggy
 - What input features can we use?
 - What is the key insight?
 The more "complex" is the code, the more likely it is to be buggy or defective.
 - How do we measure "code complexity"?
 - Lines of code (LOC)
 - Commented lines
 - Non-commented lines
 - McCabe cyclomatic complexity (control flow)
 - Halstead complexity measures (operators and operands)

- We will have more possible paths if we have more condition statements in our code.
- McCabe cyclomatic complexity = number of simple conditions + 1.

- We will have more possible paths if we have more condition statements in our code.
- McCabe cyclomatic complexity = number of simple conditions + 1.
- Simple conditions are conditional statements without OR or AND.
- E.g.,:
 - If (a > b) —> this counts as one simple condition
 - While (a > b) —> this counts as one simple condition
 - For (a=b; a > b; b++) —> this counts as one simple condition
 - Do...while (a > b) —> this counts as one simple condition

- For compound conditions, count each simple condition inside it.
- If (a > b) OR (a > 2) —> this counts as two simple conditions

```
if (a > b)
statement
else if (a > 2)
statement
```

- For compound conditions, count each simple condition inside it.
- If (a > b) OR (a > 2) —> this counts as two simple conditions
- If (a > b) AND (a > 2) —> this counts as two simple conditions

```
if (a > b)
if (a > 2)
statement
```

McCabe cyclomatic complexity Quiz (1/3)

McCabe cyclomatic complexity: measures complexity by counting the number of linearly independent paths in the control flow graph of the code.

McCabe cyclomatic complexity = number of simple conditions + 1.

• What is the McCabe cyclomatic complexity for the following code

snippets?

```
int a = 1;
int b = 2;
int c = a + b;
```

```
int a = 1;
int b = 2;
if (a > b)
a = b;
int c = a + b;
```

McCabe cyclomatic complexity Quiz (1/3)

McCabe cyclomatic complexity: measures complexity by counting the number of linearly independent paths in the control flow graph of the code.

McCabe cyclomatic complexity = number of simple conditions + 1.

What is the McCabe cyclomatic complexity for the following code

snippets?

McCabe Complexity = 1

```
int a = 1;
int b = 2;
if (a > b)
a = b;
int c = a + b;
```

McCabe Complexity = 2

McCabe Complexity = 2

McCabe cyclomatic complexity Quiz (2/3)

McCabe cyclomatic complexity: measures complexity by counting the number of linearly independent paths in the control flow graph of the code.

McCabe cyclomatic complexity = number of simple conditions + 1.

What is the McCabe cyclomatic complexity for the following code

snippets?

```
int a = 1;

int b = 2;

if (a > b && a > 1)

a = b;

int c = a + b;
```

```
int a = 1;

int b = 2;

if (a > b || a > 1)

a = b;

int c = a + b;
```

McCabe cyclomatic complexity Quiz (2/3)

McCabe cyclomatic complexity: measures complexity by counting the number of linearly independent paths in the control flow graph of the code.

McCabe cyclomatic complexity = number of simple conditions + 1.

What is the McCabe cyclomatic complexity for the following code

snippets?

```
int a = 1;

int b = 2;

if (a > b && a > 1)

a = b;

int c = a + b;
```

McCabe Complexity = 3

```
int a = 1;

int b = 2;

if (a > b || a > 1)

a = b;

int c = a + b;
```

McCabe Complexity = 3

```
int a = 1;
int b = 2;
if (a > b)
a = b;
if (2 * a > b)
a = b;
int c = a + b;
```

McCabe Complexity = 3

McCabe cyclomatic complexity Quiz (3/3)

McCabe cyclomatic complexity: measures complexity by counting the number of linearly independent paths in the control flow graph of the code.

McCabe cyclomatic complexity = number of simple conditions + 1.

What is the McCabe cyclomatic complexity for the following code

snippets?

```
int a = 1;
int b = 2;
while (a > b)
a--;
int c = a + b;
```

```
int a = 1;
int b = 2;
int c = 3;
try {
    a= 10;
} catch (ExceptionType1 name) {
    b = 10;
} catch (ExceptionType2 name) {
    c = 10;
}
```

McCabe cyclomatic complexity Quiz (3/3)

McCabe cyclomatic complexity: measures complexity by counting the number of linearly independent paths in the control flow graph of the code.

McCabe cyclomatic complexity = number of simple conditions + 1.

• What is the McCabe cyclomatic complexity for the following code

snippets?

```
int a = 1;
int b = 2;
while (a > b)
a--;
int c = a + b;
```

McCabe Complexity = 2

```
int a = 1;
int b = 2;
int c = 3;
try {
    a = 10;
} catch (ExceptionType1 name) {
    b = 10;
} catch (ExceptionType2 name) {
    c = 10;
}
McCabe Complexity = 3
```

McCabe Complexity = 4

Halstead Complexity Measures: measures complexity based on operators and operands used in the code.

- n1 = number of distinct operators (!=, !, %, /, *, +, &&, ||, etc.)
- n2 = number of distinct operands (identifiers that are not reserved words, constants (character, number, or string constants), types (bool, char, double), etc.
- N1 = total number of the operators
- N2 = total number of operands

Halstead Complexity Measures: measures complexity based on operators and operands used in the code.

- n1: = number of distinct operators
- n2 = number of distinct operands
- N1 = total number of the operators
- N2 = total number of operands
- Code vocabulary: n = n1 + n2
- Code length: N = N1 + N2
- Volume: V = N log₂ n
- **Difficulty**: D = n1 / 2 * N2 / n2

• ...

As the number of unique operators and operands in a program increases, the complexity of understanding and maintaining the program also increases. The logarithm in the formula is used to reflect this non-linear relationship. The base of the logarithm (2 in this case) is chosen because it reflects the binary nature of computation in computers (0s and 1s).

Halstead Complexity Measures: measures complexity based on operators and operands used in the code.

- n1: = number of distinct operators
- n2 = number of distinct operands
- N1 = total number of the operators
- N2 = total number of operands
- Code vocabulary: n = n1 + n2
- Code length: N = N1 + N2
- **Volume**: V = N log₂ n
- **Difficulty**: D = n1 / 2 * N2 / n2

The difficulty metric reflects the mental effort required to understand the relationships and actions within a program. A lower difficulty score indicates that the program is easier to understand, while a higher difficulty score suggests that the program is more complex and harder to comprehend.

Lines of Code (LOC)

- Actual executable lines of code higher number means more complex code
- Lines of code vs Statements of code?
- Code comments higher number means easy to comprehend the code and therefore lower complexity?

Lines of Code (LOC)

- Actual executable lines of code higher number means more complex code
- Lines of code vs Statements of code?
- Code comments higher number means easy to comprehend the code and therefore lower complexity?

What about process-centric (instead of code-centric) metrics?

Metric name	Definition		
REVISIONS	Number of revisions of a file		
REFACTORINGS	Number of times a file has been refactored ¹		
BUGFIXES	Number of times a file was involved in bug-fixing ²		
AUTHORS	Number of distinct authors that checked a file into the repository		
LOC_ADDED	Sum over all revisions of the lines of code added to a file		
MAX_	Maximum number of lines of code added		
LOC_ADDED	for all revisions		
AVE_LOC_ADDED	Average lines of code added per revision		
LOC_DELETED	Sum over all revisions of the lines of code deleted from a file		

MAX_	Maximum number of lines of code		
LOC_DELETED	deleted for all revisions		
AVE_	Average lines of code deleted per		
LOC_DELETED	revision		
CODECHURN	Sum of (added lines of code - deleted		
CODECHURN	lines of code) over all revisions		
MAX_	Maximum CODECHURN for all		
CODECHURN	revisions		
AVE_	Average CODECHURN per revision		
CODECHURN			
MAY CHANCECET	Maximum number of files committed		
MAX_CHANGESET	together to the repository		
AVE CHANCECET	Average number of files committed		
AVE_CHANGESET	together to the repository		
AGE	Age of a file in weeks (counting		
AGE	backwards from a specific release)		
	A 1 745		

Recap:

- How are we solving it? (Approach)
 - **High-level idea:** use ML to predict the modules/components of software that are more likely to be buggy
 - Assumption:
 - Multiple versions/releases of software exist; You have access to the data that tells you
 defects encountered and fixed in the past.
 - What if above doesn't hold?
 - Find "similar" software application and predict across software
 - What else do we need to think about to concretize the high-level idea?
 - Input features
 - Machine Learning algorithm

Now that we have some ideas of input features, lets talk about the second aspect of the approach

What machine learning approach to consider?

• Option-1: supervised learning technique

• Option-2: unsupervised learning technique

What machine learning approach to consider?

- Option-1: supervised learning technique
 - Requires a labelled training data
 - Shown to be very effective for classification problems
 - E.g., Naive baise, Support Vector Machine, Neural Networks
 - Pros and Cons?
- Option-2: unsupervised learning technique
 - Does not require any training dataset
 - E.g.?

What machine learning approach to consider?

- Option-1: supervised learning technique
 - Requires a labelled training data
 - Shown to be very effective for classification problems
 - E.g., Naive baise, Support Vector Machine, Neural Networks
 - Pros and Cons?
- Option-2: unsupervised learning technique
 - Does not require any training dataset
 - E.g. K-means, agglomerative clustering, genetic algorithm, etc.
 - Pros and Cons?
- Which option would you choose and why?
- How will you deal with the class-imabalance problem?

Dataset:

- Real-world open-source software?
- Existing evaluations exist?

Evaluation Metrics:

- How do we measure the effectiveness of a classifier?
 - Precision: ratio of correctly classified positive examples and total examples
 - Recall/ True positive rate (TPR) / Sensitivity: ratio of positive examples that are correctly identified
 - False positive rate (FPR): ratio of negative examples that are incorrectly classified
 - Specificity = 1 FPR: ability of the model to correctly identify negative instances

Evaluation Metrics:


How do we measure the effectiveness of a classifier?

• Precision: ratio of correctly classified positive examples and total

examples


 Recall/ True positive rate (TPR) / Sensitivity: ratio of positive examples that are correctly identified

- False positive rate (FPR): ratio of negative examples that are incorrectly classified
- **Specificity** = **1 FPR**: ability of the model to correctly identify negative instances
- Confusion matrix



Evaluation Metrics:

- How do we measure the effectiveness of a classifier?
 - Precision = TP / (TP + FP)
 - Recall/ True positive rate (TPR) / Sensitivity = TP / (TP + FN)
 - False positive rate (FPR)= FP / (FP + TN)
 - Specificity = 1 FPR
 - Confusion matrix
 - Receiver operating characteristic (ROC) curve
 - Area under the curve (AUC)



Dataset:

- Real-world open-source software
- Existing evaluations exist

Evaluation Metrics:

- How do we measure the effectiveness of a classifier?
 - Precision
 - Recall
 - True positive rate
 - False positive rate
 - Confusion matrix
 - AUC ROC curve


Implementation?

Dataset:

- Real-world open-source software
- Existing evaluations exist

Evaluation Metrics:

- How do we measure the effectiveness of a classifier?
 - Precision
 - Recall
 - True positive rate
 - False positive rate
 - Confusion matrix
 - AUC ROC curve
- Implementation?



CS 563: Software Maintenance and Evolution Oregon State University

Software Defect Prediction

What should we do next now that we have some idea of solving the problem?

- Literature Survey!
 - What all features and ML techniques have existing solutions tried?
 - What kind of datasets and metrics are used for evaluation? What are their limitations?
 - High-level idea: use ML to predict the modules/components of software that are more likely to be buggy
 - Assumption:
 - Multiple versions/releases of software exist; You have access to the data that tells you defects encountered and fixed in the past.
 - What if above doesn't hold?
 - Find "similar" software application and predict across software
 - What else do we need to think about to concretize the high-level idea?
 - Input features
 - ML algorithm (supervised or unsupervised)

These two will:

- demonstrate the novelty of your solution
- Impact the effectiveness of your solution

CS 563: Software Maintenance and Evolution Oregon State University

Announcements

- Project idea proposal assignment released
- Homework-1 assignment released
- Paper selection assignment released
 - A list of 10 papers associated with their presentation date.
 - A group of at most 2 students will present each paper (selection is on the FCFS basis). Read the assignment for more details.
 - Everyone will write and submit a review of all the papers individually (due before that paper's presentation date)
 - Form a group (optional) and use the technique to read papers we discussed to go through all papers. Discuss papers with your partner and select the one that interests you.
 - NOTE: Upcoming lectures will cover the concepts described in the research papers, so don't reject a paper because you feel you don't know the specific concepts used in that paper. Ask me, if you have any doubts about whether a specific topic will be covered or not.

In-class exercise: brainstorm project ideas

- Either individually or in a group of 2, think about:
 - The problem that you would like to solve (problem statement)
 - Why should one care about solving that problem (motivation)
 - Some high-level approach to solve the problem
 - MAKE NOTES!