



# Inspection Certificate



Abnahmeprüfzeugnis / Certificate de Réception / 3.1 to EN10204

Page

1 / 1

Part number 813394 - 4000159337

Part description 2336787 2MLXKMS0003A

Yarn Type PA6.6(470DTEX)-G210

Silicone Type 185-235 G/M2

Lot number 010009774382

Remark Fabric tested to TMS-F2004 Rev 07 Type B Applies to Batch No's: 0030758750 0030758780 0030758805  
0030758904 0030758922 0030758969

Char.Descr.	Unit	Char.Class	USL	LSL	$\bar{x}_j$	Display on	Subgr.size	Remark
Width	N	--		175.0	177.33		3	TMS-F2004 Rev 07
Ends	Threads/cm	--	19.0	17.0	17.57		3	DIN EN 1049 P2
Picks	Threads/cm	--	19.0	17.0	17.80		3	DIN EN 1049 P2
Coating Weight	N	--	35	20	22.7		3	DIN EN 12127
Weight	N	--	235	185	204.0		3	DIN EN 12127
Warp Max.load	N/5cm	CC		2500	3320.0		3	DIN EN ISO 13934-
Weft Max.load	N/5cm	CC		2500	3209.3		3	DIN EN ISO 13934-
Warp Elongation	%	CC	50.0	20.0	32.03		3	DIN EN ISO 13934-
Weft Elongation	%	CC	50.0	20.0	35.33		3	DIN EN ISO 13934-
Warp Tear	N	--		175	320.0		3	DIN EN ISO 13937-
Weft Tear	N	--		175	318.0		3	DIN EN ISO 13937-
Warp Flammability	mm/min	CC	80		3.0		3	FMVSS 302
Weft Flammability	mm/min	CC	80		3.0		3	FMVSS 302

Date of release :

10/10/2023

Signed by :

*J. Warburton*

Released by :

*D. Keane*

MILLIKEN INDUSTRIALS LTD.  
QUALITY CONTROL DEPT.  
APPROVED No.7

Please Note: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warranty and without accepting any responsibility or liability. Each customer must test and be responsible for its own specific use, further processing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at [www.milliken.com/terms](http://www.milliken.com/terms) (all additional/different terms are rejected) unless explicitly agreed otherwise in a signed writing.