

Mr C has a long
floating name

ESC101: Foundations of Computing

Purushottam Kar

Announcements

- Special session on using computers
 - August 11, 2018 (coming Saturday), 5PM, NCL CC-02
 - Not a revision class – only for students who are new to computers
 - Thanks to Parth Sharma (tutor) for the suggestion and offer



Adding two unknown numbers

3



Adding two unknown numbers

3

HOW WE USUALLY SPEAK TO A HUMAN



Adding two unknown numbers

3

HOW WE USUALLY SPEAK TO A HUMAN



Adding two unknown numbers

3

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?



Adding two unknown numbers

3

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello



Adding two unknown numbers

3

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a , b are two variables.



Adding two unknown numbers

3

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a , b are two variables.

Please ask me for value of a .



Adding two unknown numbers

3

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a , b are two variables.

Please ask me for value of a .

Please ask me for value of b .



Adding two unknown numbers

3

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Please print their sum.



Adding two unknown numbers

3

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Please print their sum.

Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Please print their sum.

Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Please print their sum.

Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Please print their sum.

Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>  
int main(){
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Please print their sum.

Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello
a, b are two variables.
Please ask me for value of a.
Please ask me for value of b.
Please print their sum.
Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d", &a);
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello
a, b are two variables.
Please ask me for value of a.
Please ask me for value of b.
Please print their sum.
Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d", &a);
scanf("%d", &b);
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello
a, b are two variables.
Please ask me for value of a.
Please ask me for value of b.
Please print their sum.
Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d", &a);
scanf("%d", &b);
printf("%d", a + b);
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello
a, b are two variables.
Please ask me for value of a.
Please ask me for value of b.
Please print their sum.
Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d", &a);
scanf("%d", &b);
printf("%d", a + b);
return 0;
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello
a, b are two variables.
Please ask me for value of a.
Please ask me for value of b.
Please print their sum.
Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d", &a);
scanf("%d", &b);
printf("%d", a + b);
return 0;
}
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello
a, b are two variables.
Please ask me for value of a.
Please ask me for value of b.
Please print their sum.
Goodbye




Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d", &a);
scanf("%d", &b);
printf("%d", a + b);
return 0;
}
```



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello
a, b are two variables.
Please ask me for value of a.
Please ask me for value of b.
Please print their sum.
Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

```
int main(){
```

```
int a, b;
```

```
scanf("%d", &a);
```


```
scanf("%d", &b);
```

```
printf("%d", a + b);
```

```
return 0;
```

```
}
```

a



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Please print their sum.

Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

```
int main(){
```

```
int a, b;
```


```
scanf("%d", &a);
```

```
scanf("%d", &b);
```

```
printf("%d", a + b);
```

```
return 0;
```

```
}
```



a

b

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Please print their sum.

Goodbye



Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

```
int main(){
```

```
int a, b;
```


```
scanf("%d", &a);
```

```
scanf("%d", &b);
```

Please give
me input

```
return 0;
```

```
}
```



a

b

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Please print their sum.

Goodbye



Adding two unknown numbers

3


HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d", &a);
    scanf("%d", &b);
    printf("%d + %d = %d", a, b, a + b);
    return 0;
}
```

a

b

Please give
me input



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello
a, b are two variables.
Please ask me for value of a.
Please ask me for value of b.

Console

Activity Log

Input

Output

Adding two unknown numbers

3


HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d", &a);
    scanf("%d", &b);
    printf("%d", a + b);
    return 0;
}
```

a

b

Please give
me input



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?
Hello
a, b are two variables.
Please ask me for value of a.
Please ask me for value of b.

Console

Activity Log

Input

Output

3 8

Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```


```
int main(){
```

Thanks. Let me
get back to work

Please give
me input

```
return 0;
```

```
}
```



b

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Console

Activity Log

Input

Output

3 8

Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

```
int main(){
```

```
int a, b;
```

```
scanf("%d", &a);
```

```
scanf("%d", &b);
```


```
printf("%d", a + b);
```

```
return 0;
```

```
}
```

a

b



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Console

Activity Log

Input

Output

3 8

Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

```
int main(){
```

```
int a, b;
```

```
scanf("%d", &a);
```

```
scanf("%d", &b);
```

```
printf("%d", a + b);
```


```
return 0;
```

```
}
```

3

a

b



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Console

Activity Log

Input

Output

3 8

Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

```
int main(){
```

```
int a, b;
```

```
scanf("%d", &a);
```

```
scanf("%d", &b);
```

```
printf("%d", a + b);
```

```
return 0;
```


```
}
```

3

a

8

b



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Console

Activity Log

Input

Output

3 8

Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

```
int main(){
```

```
int a, b;
```

```
scanf("%d", &a);
```

```
scanf("%d", &b);
```

```
printf("%d", a + b);
```

```
return 0;
```

```
}
```


3

8

a

b

11



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Console

Activity Log

Input

Output

3 8

Adding two unknown numbers

3

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

```
int main(){
```

```
int a, b;
```

```
scanf("%d", &a);
```

```
scanf("%d", &b);
```

```
printf("%d", a + b);
```

```
return 0;
```

```
}
```

3


8

a

b

11

11



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Please ask me for value of a.

Please ask me for value of b.

Console

Activity Log

Input

Output

3 8

Words of Caution

35



Words of Caution

35

In Prutor, input has to be specified before “Execute”



Words of Caution

35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake



Words of Caution

35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake

```
scanf(“%d”,a);
```



Words of Caution

35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake

```
scanf(“%d”,a);
```



Words of Caution

35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake

```
scanf(“%d”,a);
```



```
scanf(“%d”,&a);
```



Words of Caution

35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake

`scanf(“%d”,a);`



`scanf(“%d",&a);`



Words of Caution

35

In Prutor, input has to be specified before “Execute”

Please be very careful about this common mistake

`scanf(“%d”,a);`



`scanf(“%d”,&a);`



Will explain what this & means, in a few weeks



Words of Caution

35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake


`scanf(“%d”,a);`



`scanf(“%d",&a);`



Will explain what this & means, in a few weeks



Words of Caution

35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake


`scanf(“%d”,a);`



`scanf(“%d",&a);`



Will explain what this & means, in a few weeks



Words of Caution

35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake



`scanf(“%d”,a);`



`scanf(“%d",&a);`



Will explain what this & means, in a few weeks



Words of Caution

35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake



`scanf(“%d”,a);`




`scanf(“%d",&a);`



Will explain what this & means, in a few weeks



Words of Caution



35

In Prutor, input has to be specified before “Execute”
Please be very careful about this common mistake



`scanf(“%d”,a);`




`scanf(“%d",&a);`



Will explain what this & means, in a few weeks



Words of Caution



35

In Prutor, input has to be specified before “Enter”
Please be very careful about this common mistake

Both work!
Experiment!



```
scanf("%d",a);
```




```
scanf("%d",&a);
```



Will explain what this & means, in a few weeks



Words of Caution



35

In Prutor, input has to be specified before “Enter”
Please be very careful about this common mistake

Both work!
Experiment!



```
scanf("%d",a);
```




```
scanf("%d",&a);
```



Will explain what this & means, in a few weeks



Words of Caution



35


In Prutor, input has to be specified before “E”
Please be very careful about this common mistake

Both work!
Experiment!



```
scanf("%d",a);
```




```
scanf("%d",&a);
```



Will explain what this & means, in a few weeks



Words of Caution



35

Yes, in printf they are different but in scanf, both look like *whitespaces* to me

specified before “E

Both work!
Experiment!

Please be very careful about this common mistake



```
scanf("%d",a);
```




```
scanf("%d",&a);
```



Will explain what this & means, in a few weeks



Words of Caution



35

Yes, in printf they are different but in scanf, both look like *whitespaces* to me

specified before “E

Both work!
Experiment!

Please be very careful about this common mistake


```
scanf("%d",a);
```




```
scanf("%d",&a);
```



Will explain what this & means, in a few weeks



Words of Caution



35

Yes, in printf they are different but in scanf, both look like *whitespaces* to me

specified before “E

Both work!
Experiment!

Space, Tab, Newline are called whitespace characters since they are invisible ☺


scanf(“%d”, &a);




will explain what this & means, in a few weeks

Why? Space is not same as newline ☺

Huh! What is a whitespace?



Words of Caution



35

Yes, in printf they are different but in scanf, both look like *whitespaces* to me


specified before “E” but this common

Both work!
Experiment!

Space, Tab, Newline are called whitespace characters since they are invisible 😊

```
3      ... int a, b, c, d;
```


scanf(“%d”, &a);




will explain what this & means, in a few weeks

Why? Space is not same as newline 😊

Huh! What is a whitespace?



Words of Caution



35

Yes, in printf they are different but in scanf, both look like *whitespaces* to me

specified before “E” but this common


Both work!
Experiment!

Space, Tab, Newline are called whitespace characters since they are invisible 😊

```
3  int a, b, c, d;
```

TAB


scanf(“%d”, &a);




will explain what this & means, in a few weeks

Why? Space is not same as newline 😊

Huh! What is a whitespace?



Words of Caution



35

Yes, in printf they are different but in scanf, both look like *whitespaces* to me

specified before “E

Both work!
Experiment!

Space, Tab, Newline are called whitespace characters since they are invisible 😊

```
3  . . . int0a,0b,0c,0d; -
```

TAB SPACE


scanf(“%d”,&a);




will explain what this & means, in a few weeks

Why? Space is not same as newline 😊

Huh! What is a whitespace?



Words of Caution



35

Yes, in printf they are different but in scanf, both look like *whitespaces* to me

specified before “E” but this common


Both work!
Experiment!

Space, Tab, Newline are called whitespace characters since they are invisible 😊

```
3  . . . int 0a, 0b, 0c, 0d; 0
```

TAB SPACE NEWLINE


scanf(“%d”, &a);



will explain what this & means, in a few weeks

Why? Space is not same as newline 😊

Huh! What is a whitespace?



Shorthand for multiple inputs

58



Shorthand for multiple inputs

58

HOW WE USUALLY SPEAK TO A HUMAN



Shorthand for multiple inputs

58

HOW WE USUALLY SPEAK TO A HUMAN



Shorthand for multiple inputs

58

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?



Shorthand for multiple inputs

58

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello



Shorthand for multiple inputs

58

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.



Shorthand for multiple inputs

58

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace



Shorthand for multiple inputs

58

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.



Shorthand for multiple inputs

58

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d%d", &a, &b);
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d%d", &a, &b);
printf("%d", a + b);
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d%d", &a, &b);
printf("%d", a + b);
return 0;
}
```

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Please print their sum.

Goodbye




Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
int a, b;
scanf("%d%d", &a, &b);
printf("%d", a + b);
return 0;
}
```



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Please print their sum.

Goodbye





Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs


58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```

a

b



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs


58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```

a

b



Input please

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Please print their sum.

Goodbye



Shorthand for multiple inputs


58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```

a

b



Input please

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

Shorthand for multiple inputs


58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```

a

b



Input please

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3 8

Shorthand for multiple inputs


58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```

a

b



Input please

Thanks

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3 8

Shorthand for multiple inputs


58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```

a

b



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3 8

Shorthand for multiple inputs

58


HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```

3

a

b



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output


3 8

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```



3

8

a

b

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3 8

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```


3

8

a

b

11



HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Console

Activity Log

Input

Output

3 8

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```


3

8

a

b

11



11

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3 8

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```


3

8

a

b

11



11

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Console

Activity Log

Input

Output

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```


3

8

a

b

11



11

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

38

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

```
int main(){
```

```
int a, b;
```

You entered
only one integer

```
return 0;
```

```
}
```


3

8

a

b

11



11

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I
will give both values separated
by a whitespace

Console

Activity Log

Input

Output

38

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```


3

8

a

b

11



11

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3

8

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
int main(){
    int a, b;
    scanf("%d%d", &a, &b);
    printf("%d", a + b);
    return 0;
}
```


3

8

a

b

11



11

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3

8

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

3

8

```
int main(){
```

```
int a, b;
```

a

b

All look the same to me

11

```
return 0;
```

11

HOW WE USUALLY SPEAK TO A HUMAN

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3

8

Shorthand for multiple inputs



HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

3

8

```
int main(){
```

```
int a, b;
```

a


b

All look the same to me

11

```
return 0;
```

```
}
```



11

HOW WE USUALLY SPEAK TO A PERSON

Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3

8

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

3

8

```
int main(){
```

```
int a, b;
```

a

b

All look the same to me

11

```
return 0;
```

11

HOW WE USUA

Help!!!



Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3

8

Shorthand for multiple inputs

58

HOW WE MUST SPEAK TO MR. COMPILER

```
#include <stdio.h>
```

3

8

```
int main(){
```

```
int a, b;
```

a

b


All look the same to me

```
printf("%d", &a, &b);
```

11

```
return 0;
```

```
}
```



11

Okay okay

HOW WE USUA

Help!!!



Do you speak English?

Hello

a, b are two variables.

Ask me for values of a and b. I will give both values separated by a whitespace

Console

Activity Log

Input

Output

3

8

What is going on with scanf?

97



What is going on with scanf?

97

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!



What is going on with scanf?

97

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE USUALLY SPEAK TO A HUMAN

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!


Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE USUALLY SPEAK TO A HUMAN



Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE MUST SPEAK TO MR. COMPILER

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE MUST SPEAK TO MR. COMPILER

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE MUST SPEAK TO MR. COMPILER

```
scanf("%d%d", &a, &b);
```

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE MUST SPEAK TO MR. COMPILER

```
scanf("%d%d", &a, &b);
```

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE MUST SPEAK TO MR. COMPILER

```
scanf("%d%d", &a, &b);
```

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read




What is going on with scanf?

97

HOW WE MUST SPEAK TO MR. COMPILER

```
scanf("%d%d", &a, &b);
```

A diagram showing the scanf function call. The format string "%d%d" is highlighted in a light blue box. The variable addresses "&a" and "&b" are highlighted in a light purple box and a light orange box respectively. Arrows point from the format string to the variables, indicating the flow of data.

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

97

HOW WE MUST SPEAK TO MR. COMPILER

```
scanf("%d%d", &a, &b);
```

Format string

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read




What is going on with scanf?

97

HOW WE MUST SPEAK TO MR. COMPILER

```
scanf("%d%d", &a, &b);
```

Format string



HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read




What is going on with scanf?

97

HOW WE MUST SPEAK TO MR. COMPILER

```
scanf("%d%d", &a, &b);
```

Format string



Format string tells me **how** you will write things, and then I am told **where** to store what I have read

HOW WE USUALLY SPEAK TO A HUMAN

Please read one integer. Ignore all whitespace (spaces, tabs, newlines) after that till I write another integer. Read that second integer too.

Store value of the first integer in a and value of second integer in b.

Remember Mr. C likes to be told beforehand what all we are going to ask him to do!

Scanf follows this exact same rule while telling Mr. C how to read



What is going on with scanf?

113



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input
scanf will never print anything



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter

He treats all whitespace characters the same when integers are being input

scanf will never print anything

```
scanf("Hello %d",&a);
```



What is going on with scanf?


113

Be a bit careful since Mr C is a bit careless in this matter

He treats all whitespace characters the same when integers are being input

scanf will never print anything

`scanf("Hello %d",&a);`




What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input

scanf will never print anything
`scanf("Hello %d",&a);`



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a



What is going on with scanf?


113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input

scanf will never print anything

scanf("Hello %d",&a);

Use printf to print and scanf to read



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a



What is going on with scanf?

113


Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input

scanf will never print anything

scanf("Hello %d",&a);

Use printf to print and scanf to read

Try out what happens with the following



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input


scanf will never print anything

```
scanf("Hello %d",&a);
```

Use printf to print and scanf to read

Try out what happens with the following

```
scanf("%d %d",&a,&b);
```



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input

scanf will never print anything


```
scanf("Hello %d",&a);
```

Use printf to print and scanf to read

Try out what happens with the following

```
scanf("%d %d",&a,&b);
```

```
scanf("%d,%d",&a,&b);
```



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input

scanf will never print anything

```
scanf("Hello %d",&a);
```


Use printf to print and scanf to read

Try out what happens with the following

```
scanf("%d %d",&a,&b);
```

```
scanf("%d,%d",&a,&b);
```

```
scanf("%d\n%d",&a,&b);
```



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input

scanf will never print anything

```
scanf("Hello %d",&a);
```


Use printf to print and scanf to read

Try out what happens with the following

```
scanf("%d %d",&a,&b);
```

```
scanf("%d,%d",&a,&b);
```

```
scanf("%d\n%d",&a,&b);  scanf("%d\t%d",&a,&b);
```



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input

scanf will never print anything

```
scanf("Hello %d",&a);
```


Use printf to print and scanf to read

Try out what happens with the following

```
scanf("%d %d",&a,&b);
```

```
scanf("%d,%d",&a,&b);    scanf("\'%d%d\'",&a,&b);
```

```
scanf("%d\n%d",&a,&b);    scanf("%d\t%d",&a,&b);
```



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter
He treats all whitespace characters the same when
integers are being input

scanf will never print anything

`scanf("Hello %d",&a);`


Use printf to print and scanf to read

Try out what happens with the following


`scanf("%d %d",&a,&b);` `scanf("%dHello%d",&a,&b);`

`scanf("%d,%d",&a,&b);` `scanf("\"%d%d\"",&a,&b);`

`scanf("%d\n%d",&a,&b);` `scanf("%d\t%d",&a,&b);`



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a



What is going on with scanf?

113

Be a bit careful since Mr C is a bit careless in this matter

He treats characters the same when

integer

My advice to you is to take input one at a time in the beginning 😊 Try out acrobatics in free time

scanf("Hello %d",&a);

Use printf to print and scanf to read

Try out what happens with the following

scanf("%d %d",&a,&b);


scanf("%d,%d",&a,&b);

scanf("%d\n%d",&a,&b);


scanf("%dHello%d",&a,&b);

scanf("\n%d%d\n",&a,&b);

scanf("%d\t%d",&a,&b);



Hmm ... you are going to write the English word Hello followed by space followed by an integer. I will store the value of that integer in a




What's in a Name?




What's in a Name?

- Mr. C really does not care what we name our variables so long as they are legal names



What's in a Name?

- Mr. C really does not care what we name our variables so long as they are legal names




There are
illegal names?



What's in a Name?

- Mr. C really does not care what we name our variables so long as they are legal names



There are
illegal names?

Imagine if your parents
had named you "Hello"



What's in a Name?

- Mr. C really does not care what we name our variables so long as they are legal names



Imagine if your parents
had named you "Hello"



What's in a Name?

- Mr. C really does not care what we name our variables so long as they are legal names



My friends would greet me as Hello Hello?

Imagine if your parents had named you "Hello"



What's in a Name?


- Mr. C really does not care what we name our variables so long as they are legal names



My friends would greet me as Hello Hello?


Wouldn't be nice, right?
Mr C thinks so too.

Imagine if your parents had named you "Hello"



What's in a Name?


- Mr. C really does not care what we name our variables so long as they are legal names



My friends would greet me as Hello Hello?


Wouldn't be nice, right?
Mr C thinks so too.

Imagine if your parents had named you "Hello"



What's in a Name?

- Mr. C really does not care what we name our variables so long as they are legal names




She's right. Some variable names are illegal

Wouldn't be nice, right?
Mr C thinks so too.


My friends would greet me as Hello Hello?

Imagine if your parents had named you "Hello"



What's in a Name?

- Mr. C really does not care what we name our variables so long as they are legal names
- Certain names are called “reserved keywords”




She's right. Some variable names are illegal

Wouldn't be nice, right?
Mr C thinks so too.


My friends would greet me as Hello Hello?

Imagine if your parents had named you “Hello”



What's in a Name?

- Mr. C really does not care what we name our variables so long as they are legal names
- Certain names are called “reserved keywords”



Cannot use reserved keywords as variable names




She's right. Some variable names are illegal

My friends would greet me as Hello Hello?

Wouldn't be nice, right?
Mr C thinks so too.

Imagine if your parents had named you “Hello”



Reserved Keywords

140



Reserved Keywords

140

auto, break, case, char, const, continue, default, do, double, else, enum, extern, float, for, goto, if, int, long, register, return, short, signed, sizeof, static, struct, switch, typedef, union, unsigned, void, volatile, while



Reserved Keywords

140

auto, break, case, char, const, continue, default, do, double, else, enum, extern, float, for, goto, if, int, long, register, return, short, signed, sizeof, static, struct, switch, typedef, union, unsigned, void, volatile, while

Prutor shows keywords in a different color 😊



Reserved Keywords

140

auto, break, case, char, const, continue, default, do, double, else, enum, extern, float, for, goto, if, **int**, long, register, **return**, short, signed, sizeof, static, struct, switch, typedef, union, unsigned, void, volatile, while

Prutor shows keywords in a different color ☺

Have already seen int and return in use



Reserved Keywords

140

auto, break, case, char, const, continue, default, do, double, else, enum, extern, float, for, goto, if, int, long, register, return, short, signed, sizeof, static, struct, switch, typedef, union, unsigned, void, volatile, while

Prutor shows keywords in a different color ☺

Have already seen int and return in use

Will soon see use for long, float



Reserved Keywords

140


auto, break, case, char, const, continue, default, do, double, else, enum, extern, float, for, goto, if, int, long, register, return, short, signed, sizeof, static, struct, switch, typedef, union, unsigned, void, volatile, while

Prutor shows keywords in a different color ☺

Have already seen int and return in use

Will soon see use for long, float

By the end of course, you will become very comfortable with most of these keywords ☺



How to give Names in C

146



How to give Names in C

146

Mr C calls names we give to our variables as *identifiers*



How to give Names in C

146

Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive




How to give Names in C

146

Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive




How to give Names in C

146

Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive

For me, the names temp, Temp, TEMP, TeMp are all different variable names



How to give Names in C


146

Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive



For me, the names temp, Temp, TEMP, TeMp are all different variable names



How to give Names in C


146

Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive

```
#include <stdio.h>
```

For me, the names temp, Temp, TEMP, TeMp are all different variable names



How to give Names in C


146

Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive

```
#include <stdio.h>  
int main(){
```

For me, the names temp, Temp, TEMP, TeMp are all different variable names



How to give Names in C

146


Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive

```
#include <stdio.h>

int main(){
    int temp, TEMP, Temp, TeMp;
```

For me, the names temp, Temp, TEMP, TeMp are all different variable names



How to give Names in C

146


Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive

```
#include <stdio.h>

int main(){
    int temp, TEMP, Temp, TeMp;
    return 0;
}
```

For me, the names temp, Temp, TEMP, TeMp are all different variable names



How to give Names in C

146


Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive

```
#include <stdio.h>

int main(){
    int temp, TEMP, Temp, TeMp;
    return 0;
}
```

For me, the names temp, Temp, TEMP, TeMp are all different variable names



How to give Names in C

146


Mr C calls names we give to our variables as *identifiers*
Names are case-sensitive

```
#include <stdio.h>

int main(){
    int temp, TEMP, Temp, TeMp;
    return 0;
}
```



For me, the names temp, Temp, TEMP, TeMp are all different variable names




How to give Names in C

146

Mr C calls names we give to our variables as *identifiers*
Names are case-sensitive


```
#include <stdio.h>

int main(){
int temp, TEMP, Temp, TeMp;
return 0;
}
```



So this program is fine?

For me, the names temp, Temp, TEMP, TeMp are all different variable names




How to give Names in C

146

Mr C calls names we give to our variables as *identifiers*
Names are case-sensitive

```
#include <stdio.h>


int main(){
int temp, TEMP, Temp, TeMp;
return 0;
}
```



So this program is fine?

For me, the names temp, Temp, TEMP, TeMp are all different variable names

Yes, but not advisable.
May make mistakes,
confuse others



How to give Names in C

146


Mr C calls names we give to our variables as *identifiers*

Names are case-sensitive

Names can contain A-Z, a-z, 0-9, underscore _

```
#include <stdio.h>


int main(){
int temp, TEMP, Temp, TeMp;
return 0;
}
```



So this program is fine?

For me, the names temp, Temp, TEMP, TeMp are all different variable names

Yes, but not advisable.
May make mistakes,
confuse others



How to give Names in C

146

Mr C calls names we give to our variables as *identifiers*


Names are case-sensitive

Names can contain A-Z, a-z, 0-9, underscore _

Names cannot start with a digit

```
#include <stdio.h>


int main(){
int temp, TEMP, Temp, TeMp;
return 0;
}
```



So this program is fine?

For me, the names temp, Temp, TEMP, TeMp are all different variable names

Yes, but not advisable.
May make mistakes,
confuse others



Writing pretty code is an art

162



Writing pretty code is an art

162

```
1iitk,me@iitk,#iitk,iitk.1,  
    iitk-1, iit k,
```



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



iitk1,iitk_1,me_iitk,
iitk_one, iitK



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



iitk1,iitk_1,me_iitk,
iitk_one, iitK



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



iitk1,iitk_1,me_iitk,
iitk_one, iitK



Make names meaningful i.e. hzoxys valid name but ☹



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



iitk1,iitk_1,me_iitk,
iitk_one, iitK



Make names meaningful i.e. hzoxys valid name but ☹

Programmers are artists and differ on what is more pretty



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



iitk1,iitk_1,me_iitk,
iitk_one, iitK



Make names meaningful i.e. hzoxys valid name but ☹

Programmers are artists and differ on what is more pretty
numFirst, numSecond



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



iitk1,iitk_1,me_iitk,
iitk_one, iitK



Make names meaningful i.e. hzoxys valid name but ☹

Programmers are artists and differ on what is more pretty

numFirst, numSecond num_first, num_second



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



iitk1,iitk_1,me_iitk,
iitk_one, iitK



Make names meaningful i.e. hzoxys valid name but ☹

Programmers are artists and differ on what is more pretty

numFirst, numSecond num_first, num_second

Make names not too long e.g. tmp vs temporary



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



iitk1,iitk_1,me_iitk,
iitk_one, iitK



Make names meaningful i.e. hzoxys valid name but ☹

Programmers are artists and differ on what is more pretty

numFirst, numSecond num_first, num_second

Make names not too long e.g. tmp vs temporary

You will gradually get used to many artistic styles



Writing pretty code is an art

162

1iitk,me@iitk,#iitk,iitk.1,
iitk-1, iit k,



iitk1,iitk_1,me_iitk,
iitk_one, iitK



Make names meaningful i.e. hzoxys valid name but ☹

Programmers are artists and differ on what is more pretty

numFirst, numSecond num_first, num_second

Make names not too long e.g. tmp vs temporary

You will gradually get used to many artistic styles

tmp, iter, var, fun, ref



Beyond Integers



Beyond Integers

- Lots of fun possible with integers alone




Beyond Integers

- Lots of fun possible with integers alone
 - However, the box storing integers is actually not very big




Beyond Integers

- Lots of fun possible with integers alone
 - However, the box storing integers is actually not very big



Beyond Integers

- Lots of fun possible with integers alone
 - However, the box storing integers is actually not very big
 - Can only store integers between -2,147,483,648 and 2,147,483,647



Beyond Integers

- Lots of fun possible with integers alone
 - However, the box storing integers is actually not very big
 - Can only store integers between -2,147,483,648 and 2,147,483,647
 - Some years ago the range was much smaller -32,768 and 32,767



Beyond Integers

- Lots of fun possible with integers alone
 - However, the box storing integers is actually not very big
 - Can only store integers between -2,147,483,648 and 2,147,483,647
 - Some years ago the range was much smaller -32,768 and 32,767
 - Computers have become really powerful in last 5-10 years



Beyond Integers

- Lots of fun possible with integers alone
 - However, the box storing integers is actually not very big
 - Can only store integers between -2,147,483,648 and 2,147,483,647
 - Some years ago the range was much smaller -32,768 and 32,767
 - Computers have become really powerful in last 5-10 years
- Also, what about real numbers (fractions etc)



Beyond Integers

- Lots of fun possible with integers alone
 - However, the box storing integers is actually not very big
 - Can only store integers between -2,147,483,648 and 2,147,483,647
 - Some years ago the range was much smaller -32,768 and 32,767
 - Computers have become really powerful in last 5-10 years
- Also, what about real numbers (fractions etc)
 - How to ask Mr C to work with a real number?



Beyond Integers

- Lots of fun possible with integers alone
 - However, the box storing integers is actually not very big
 - Can only store integers between -2,147,483,648 and 2,147,483,647
 - Some years ago the range was much smaller -32,768 and 32,767
 - Computers have become really powerful in last 5-10 years
- Also, what about real numbers (fractions etc)
 - How to ask Mr C to work with a real number?
 - How to ask Mr C to print a real number?



Long integers

184



Long integers

Really long – can store integers between

184



Long integers

184

Really long – can store integers between

-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807



Long integers

184

Really long – can store integers between

-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807



Long integers

184

Really long – can store integers between

-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
```



Long integers

184

Really long – can store integers between

-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
int main(){
```



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
int main(){
long a; // long int a; works too!
```



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
int main(){
long a; // long int a; works too!
scanf("%ld", &a);
```



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>

int main(){
    long a; // long int a; works too!
    scanf("%ld", &a);
    printf("My first long int %ld", a);
}
```



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>

int main(){
    long a; // long int a; works too!
    scanf("%ld", &a);
    printf("My first long int %ld", a);
    return 0;
```



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>

int main(){
    long a; // long int a; works too!
    scanf("%ld", &a);
    printf("My first long int %ld", a);
    return 0;
}
```



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
int main(){
    long a; // long int a; works too!
    scanf("%ld", &a);
    printf("My first long int %ld", a);
    return 0;
}
```

Comment



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
int main(){
    long a; // long int a; works too!
    scanf("%ld", &a);
    printf("My first long int %ld", a);
    return 0;
}
```

Comment

%ld



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
int main(){
    long a; // long int a; works too!
    scanf("%ld", &a);
    printf("My first long int %ld", a);
    return 0;
}
```

Comment

%ld

Integer arithmetic applies to
long int as well +, -, /, *, %, ()



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
int main(){
    long a; // long int a; works too!
    scanf("%ld", &a);
    printf("My first long int %ld", a);
    return 0;
}
```

Comment

%ld

Integer arithmetic applies to
long int as well +, -, /, *, %, ()
Try them out on Prutor



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
int main(){
    long a; // long int a; works too!
    scanf("%ld", &a);
    printf("My first long int %ld", a);
    return 0;
}
```

Comment

%ld

Integer arithmetic applies to long int as well +, -, /, *, %, ()

Try them out on Prutor

How does long int interact with int – int + long, int * long?



Long integers

184

Really long – can store integers between
-9,223,372,036,854,775,808 and 9,223,372,036,854,775,807

```
#include <stdio.h>
int main(){
    long a; // long int a; works too!
    scanf("%ld", &a);
    printf("My first long int %ld", a);
    return 0;
}
```

Comment

%ld

Integer arithmetic applies to long int as well +, -, /, *, %, ()

Try them out on Prutor

How does long int interact with int – int + long, int * long?

Next class 😊



How about Real numbers?

201



How about Real numbers?

201

int allows us to store, do math formulae with integers



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>  
int main(){
```



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
int main(){
float a;
scanf("%f", &a);
```



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
int main(){
float a;
scanf("%f", &a);
printf("My first real %f", a);
```



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
int main(){
float a;
scanf("%f", &a);
printf("My first real %f", a);
return 0;
```



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
int main(){
float a;
scanf("%f", &a);
printf("My first real %f", a);
return 0;
}
```



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```

```
scanf("%f", &a);
```

%f

```
printf("My first real %f", a);
```

```
return 0;
```

```
}
```



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```

```
scanf("%f", &a);
```

%f

```
printf("My first real %f", a);
```

```
return 0;
```

```
}
```

Very large range $3.4e+38$



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```

```
scanf("%f", &a);
```

%f

```
printf("My first real %f", a);
```

```
return 0;
```

```
}
```

Very large range $3.4e+38$

Arithmetic operations apply to float as well +, -, /, *, ()



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```

```
scanf("%f", &a);
```

%f

```
printf("My first real %f", a);
```

```
return 0;
```

```
}
```

Very large range $3.4e+38$

Arithmetic operations apply to float as well +, -, /, *, ()



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```

```
scanf("%f", &a);
```

%f

```
printf("My first real %f", a);
```


```
return 0;
```

```
}
```

Very large range $3.4e+38$

Arithmetic operations apply to float as well +, -, /, *, ()

What happened to %?



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```


```
scanf("%f", &a);
```

%f

```
printf("My first real %f", a);
```

```
return 0;
```


```
}
```



Very large range $3.4e+38$

Arithmetic operations apply to float as well +, -, /, *, ()

What happened to %?



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```

```
scanf("%f", &a);
```

%f

```
printf("My first real number is %f", a);
```

```
return 0;
```


```
}
```

😊 Did you ever do remainders with real numbers in school?

Very large range $3.4e+38$

Arithmetic operations apply to float as well +, -, /, *, ()

What happened to %?



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```

```
scanf("%f", &a);
```

%f

```
printf("My first real number is %f", a);  
return 0;
```

```
}
```

😊 Did you ever do remainders with real numbers in school?

Very large range $3.4e+38$

Arithmetic operations apply to float as well +, -, /, *, ()



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```

```
scanf("%f", &a);
```

%f

```
printf("My first real number is %f", a);
```

```
return 0;
```


```
}
```

😊 Did you ever do remainders with real numbers in school?

Very large range $3.4e+38$

Arithmetic operations apply to float as well +, -, /, *, ()

I remember. Remainders make sense for integers, not for real numbers



How about Real numbers?

201

int allows us to store, do math formulae with integers

float allows us to store, do math formulae with reals

```
#include <stdio.h>
```

```
int main(){
```

```
float a;
```


```
scanf("%f", &a);
```

%f

```
printf("My first real number is %f", a);
```

```
return 0;
```

```
}
```



☺ Did you ever do remainders with real numbers in school?

Very large range $3.4e+38$

Arithmetic operations apply to float as well +, -, /, *, ()

Try them out on Prutor

I remember. Remainders make sense for integers, not for real numbers

