

# Fancy Arrays

ESC101: Fundamentals of Computing

Purushottam Kar

# Recap – 6 golden rules of functions 2



# Recap – 6 golden rules of functions 2

**RULE 1:** When we give a variable as input, the value stored inside that variable gets passed as an argument



# Recap – 6 golden rules of functions 2

**RULE 1:** When we give a variable as input, the value stored inside that variable gets passed as an argument

**RULE 2:** When we give an expression as input, the value generated by that expression gets passed as argument



# Recap – 6 golden rules of functions 2

**RULE 1:** When we give a variable as input, the value stored inside that variable gets passed as an argument

**RULE 2:** When we give an expression as input, the value generated by that expression gets passed as argument

**RULE 3:** In case of a mismatch b/w type of arg promised and type of arg passed, typecasting will be attempted



# Recap – 6 golden rules of functions <sup>2</sup>

**RULE 1:** When we give a variable as input, the value stored inside that variable gets passed as an argument

**RULE 2:** When we give an expression as input, the value generated by that expression gets passed as argument

**RULE 3:** In case of a mismatch b/w type of arg promised and type of arg passed, typecasting will be attempted

**RULE 4:** All values passed to a function get stored in a fresh variable inside that function



# Recap – 6 golden rules of functions 2

**RULE 1:** When we give a variable as input, the value stored inside that variable gets passed as an argument

**RULE 2:** When we give an expression as input, the value generated by that expression gets passed as argument

**RULE 3:** In case of a mismatch b/w type of arg promised and type of arg passed, typecasting will be attempted

**RULE 4:** All values passed to a function get stored in a fresh variable inside that function

**RULE 5:** Value returned by a function can be used freely in any way values of that data-type could have been used



# Recap – 6 golden rules of functions 2

**RULE 1:** When we give a variable as input, the value stored inside that variable gets passed as an argument

**RULE 2:** When we give an expression as input, the value generated by that expression gets passed as argument

**RULE 3:** In case of a mismatch b/w type of arg promised and type of arg passed, typecasting will be attempted

**RULE 4:** All values passed to a function get stored in a fresh variable inside that function

**RULE 5:** Value returned by a function can be used freely in any way values of that data-type could have been used

**RULE 6:** All clones share the memory address space

# Passing Arrays to Functions

3



ESC101: Fundamentals  
of Computing

# Passing Arrays to Functions

No new rules need to be learnt. Let us see how 😊



# Passing Arrays to Functions

No new rules need to be learnt. Let us see how ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array



# Passing Arrays to Functions

No new rules need to be learnt. Let us see how 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

Thus, when we pass an array into a function, we are just sending a pointer, **not the entire array**



# Passing Arrays to Functions

No new rules need to be learnt. Let us see how 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

Thus, when we pass an array into a function, we are just sending a pointer, **not the entire array**

**CAREFUL:** this has two important consequences



# Passing Arrays to Functions

No new rules need to be learnt. Let us see how 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

Thus, when we pass an array into a function, we are just sending a pointer, **not the entire array**

**CAREFUL:** this has two important consequences

The array will not get copied onto a new array inside the function since the only thing that will get copied is the address to the first element of the array



# Passing Arrays to Functions


No new rules need to be learnt. Let us see how 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

Thus, when we pass an array into a function, we are just sending a pointer, **not the entire array**

**CAREFUL:** this has two important consequences

The array will not get copied onto a new array inside the function since the only thing that will get copied is the address to the first element of the array  
If you make changes to the array inside the function, main() will see them



# Passing Arrays to Functions

No new rules need to be learnt. Let us see how 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

Thus, when we pass an array into a function, we are just sending a pointer, **not the entire array**

**CAREFUL:** this has two important consequences

The array will not get copied onto a new array inside the function since the only thing that will get copied is the address to the first element of the array  
If you make changes to the array inside the function, main() will see them

Notice that when we pass an array to scanf (strings), scanf is able to change the values inside that array



# Passing arrays to functions

4



ESC101: Fundamentals  
of Computing

# Passing arrays to functions

4

Two styles – both are exactly the same. Some people prefer one style and some prefer the other style



# Passing arrays to functions

4

Two styles – both are exactly the same. Some people prefer one style and some prefer the other style

**Note:** since passing an array is just like passing a pointer, if a clone uses the sizeof operator on an array passed to it, it will just get the value 8



# Passing arrays to functions

4

Two styles – both are exactly the same. Some people prefer one style and some prefer the other style

**Note:** since passing an array is just like passing a pointer, if a clone uses the sizeof operator on an array passed to it, it will just get the value 8

**Careful:** this means that info about length of array must be passed separately to a clone



# Passing arrays to functions

Two styles – both are exactly the same. Some people prefer one style and some prefer the other style

**Note:** since passing an array is just like passing a pointer, if a clone uses the sizeof operator on an array passed to it, it will just get the value 8

**Careful:** this means that info about length of array must be passed separately to a clone

```
void print2ndElement(int *b){  
    printf("%d %d\n", b[1], sizeof(b));  
}  
  
int main(void){  
    int a[5] = {1,2,3,4,5};  
    printf("%d\n", sizeof(a));  
    print2ndElement(a);  
    print2ndElement(a+1);  
    return 0;  
}
```



# Passing arrays to functions

4

Two styles – both are exactly the same. Some people prefer one style and some prefer the other style

**Note:** since passing an array is just like passing a pointer, if a clone uses the sizeof operator on an array passed to it, it will just get the value 8

**Careful:** this means that info about length of array must be passed separately to a clone

```
void print2ndElement(int b[5]){
    printf("%d %d\n", b[1], sizeof(b));
}

int main(void){
    int a[5] = {1,2,3,4,5};
    printf("%d\n", sizeof(a));
    print2ndElement(a);
    print2ndElement(a+1);
    return 0;
}
```



# Passing arrays to functions

4


Two styles – both are exactly the same. Some people prefer one style and some prefer the other style

**Note:** since passing an array is just like passing a pointer, if a clone uses the sizeof operator on an array passed to it, it will just get the value 8

**Careful:** this means that info about length of array must be passed separately to a clone

```
void print2ndElement(int b[5]){
    printf("%d %d\n", b[1], sizeof(b));
}

int main(void){
    int a[5] = {1,2,3,4,5};
    printf("%d\n", sizeof(a));
    print2ndElement(a);
    print2ndElement(a+1);
    return 0;
}
```



# Passing arrays to functions


Two styles – both are exactly the same. Some people prefer one style and some prefer the other style

**Note:** since passing an array is just like passing a pointer, if a clone uses the sizeof operator on an array passed to it, it will just get the value 8

**Careful:** this means that info about length of array must be passed separately to a clone

```
void print2ndElement(int b[5]){
    printf("%d %d\n", b[1], sizeof(b));
}

int main(void){
    int a[5] = {1,2,3,4,5};
    printf("%d\n", sizeof(a));
    print2ndElement(a);
    print2ndElement(a+1);
    return 0;
}
```



# Passing arrays to functions


Two styles – both are exactly the same. Some people prefer one style and some prefer the other style

**Note:** since passing an array is just like passing `a[0]` gets passed, clone uses the `sizeof` operator. If on an array passed to it, it will just get the value 8

**Careful:** this means that info about length of array must be passed separately to a clone

```
void print2ndElement(int b[5]){
    printf("%d %d\n", b[1], sizeof(b));
}

int main(void){
    int a[5] = {1,2,3,4,5};
    printf("%d\n", sizeof(a));
    print2ndElement(a);
    print2ndElement(a+1);
    return 0;
}
```



# Passing arrays to functions


Two styles – both are exactly the same. Some people prefer one style and some prefer the other style

**Note:** since passing an array is just like passing  $\&a[0]$  gets passed, clone uses the `sizeof` operator. If on an array passed to it, it will just get the value 8

**Careful:** this means  $\&a[1]$  gets passed about length of array must be passed separately to a clone

```
void print2ndElement(int b[5]){
    printf("%d %d\n", b[1], sizeof(b));
}

int main(void){
    int a[5] = {1,2,3,4,5};
    printf("%d\n", sizeof(a));
    print2ndElement(a);
    print2ndElement(a+1);
    return 0;
}
```



# Passing arrays to functions

Two styles – both are exactly the same. Some people prefer one style and some prefer the other style


Recall that  $b[1]$  is the same as  $*(b+1)$

**Note:** since passing an array is just like passing  $\&a[0]$  gets passed, clone uses the `sizeof` operator. If on an array passed to it, it will just get the value 8

**Careful:** this means  $\&a[1]$  gets passed about length of array must be passed separately to a clone

```
void print2ndElement(int b[5]){
    printf("%d %d\n", b[1], sizeof(b));
}

int a[5] = {1,2,3,4,5};
printf("%d\n", sizeof(a));
print2ndElement(a);
print2ndElement(a+1);
return 0;
}
```



# Passing arrays to functions

5



# Passing arrays to functions

5

No matter what the manner in which you declare function



# Passing arrays to functions

No matter what the manner in which you declare function

```
void print2ndElement(int b[])
```



# Passing arrays to functions

No matter what the manner in which you declare function

```
void print2ndElement(int b[])
void print2ndElement(int b[5])
```



# Passing arrays to functions

No matter what the manner in which you declare function

```
void print2ndElement(int b[])
```

```
void print2ndElement(int b[5])
```

```
void print2ndElement(int *b)
```



# Passing arrays to functions

No matter what the manner in which you declare function

```
void print2ndElement(int b[])
void print2ndElement(int b[5])
void print2ndElement(int *b)
```

In all cases, just pointer to first element of array gets passed



# Passing arrays to functions

No matter what the manner in which you declare function

```
void print2ndElement(int b[])
void print2ndElement(int b[5])
void print2ndElement(int *b)
```

In all cases, just pointer to first element of array gets passed

In second case you are telling Mr C that you will pass an array of 5 integers but he will throw that information away!



# Passing arrays to functions

No matter what the manner in which you declare function

```
void print2ndElement(int b[])
void print2ndElement(int b[5])
void print2ndElement(int *b)
```

In all cases, just pointer to first element of array gets passed

In second case you are telling Mr C that you will pass an array of 5 integers but he will throw that information away!

You can pass an int array of any length here. Just a pointer will get passed.



# Passing arrays to functions

No matter what the manner in which you declare function

```
void print2ndElement(int b[])
void print2ndElement(int b[5])
void print2ndElement(int *b)
```

In all cases, just pointer to first element of array gets passed

In second case you are telling Mr C that you will pass an array of 5 integers but he will throw that information away!

You can pass an int array of any length here. Just a pointer will get passed.

This is why you must always pass the actual length of array as a separate argument



# Passing arrays to functions

No matter what the manner in which you declare function

```
void print2ndElement(int b[])
void print2ndElement(int b[5])
void print2ndElement(int *b)
```

In all cases, just pointer to first element of array gets passed

In second case you are telling Mr C that you will pass an array of 5 integers but he will throw that information away!

You can pass an int array of any length here. Just a pointer will get passed.

This is why you must always pass the actual length of array as a separate argument

```
void print2ndElement(int b[], int arrLength)
```

# Declaring arrays inside functions

6



# Declaring arrays inside functions

6

We can declare and use new variables inside functions –  
char, float, long, int, even arrays of int, char etc



# Declaring arrays inside functions

6

We can declare and use new variables inside functions – char, float, long, int, even arrays of int, char etc

However, all these (including arrays) get destroyed when the clone dies –are called *local variables* of the function



# Declaring arrays inside functions

6

We can declare and use new variables inside functions – char, float, long, int, even arrays of int, char etc

However, all these (including arrays) get destroyed when the clone dies –are called *local variables* of the function

If you declare a double variable inside a function, it will be destroyed when the function returns



# Declaring arrays inside functions

6

We can declare and use new variables inside functions – char, float, long, int, even arrays of int, char etc

However, all these (including arrays) get destroyed when the clone dies –are called *local variables* of the function

If you declare a double variable inside a function, it will be destroyed when the function returns

If you declare a static float array inside a function, it will be destroyed when the function returns



# Declaring arrays inside functions

6

We can declare and use new variables inside functions – char, float, long, int, even arrays of int, char etc

However, all these (including arrays) get destroyed when the clone dies –are called *local variables* of the function

If you declare a double variable inside a function, it will be destroyed when the function returns

If you declare a static float array inside a function, it will be destroyed when the function returns

... except dynamically declared arrays (i.e. those declared using malloc/calloc/realloc) – these are not destroyed ☺



# Declaring arrays inside functions

6

We can declare and use new variables inside functions – char, float, long, int, even arrays of int, char etc

However, all these (including arrays) get destroyed when the clone dies –are called *local variables* of the function

If you declare a double variable inside a function, it will be destroyed when the function returns

If you declare a static float array inside a function, it will be destroyed when the function returns

... except dynamically declared arrays (i.e. those declared using malloc/calloc/realloc) – these are not destroyed ☺

Advantage: can exploit this to return arrays from a function



# Declaring arrays inside functions

6

We can declare and use new variables inside functions – char, float, long, int, even arrays of int, char etc

However, all these (including arrays) get destroyed when the clone dies –are called *local variables* of the function


If you declare a double variable inside a function, it will be destroyed when the function returns

If you declare a static float array inside a function, it will be destroyed when the function returns

... except dynamically declared arrays (i.e. those declared using malloc/calloc/realloc) – these are not destroyed ☺

Advantage: can exploit this to return arrays from a function

Disadvantage: can cause memory leaks if you are not careful – remember to free arrays before a function exits if the array no longer needed



# Returning Arrays from Functions

7



# Returning Arrays from Functions

7

To return an array, simply return the address of the first element of the array – as simple as that ☺



# Returning Arrays from Functions

7

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array



# Returning Arrays from Functions

7

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays that have been malloced/calloced/realloced. Do not return statically declared arrays – they are destroyed!



# Returning Arrays from Functions

7

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays that have been malloced/calloced/realloced. Do not return statically declared arrays – they are destroyed!

If the main function tries to read a destroyed array – SEGFAULT!



# Returning Arrays from Functions

7

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays that have been malloced/calloced/realloced. Do not return statically declared arrays – they are destroyed!

If the main function tries to read a destroyed array – SEGFAULT!

Gives us another trick of returning multiple values from a function – simply return an array



# Returning Arrays from Functions

7

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays that have been malloced/calloced/realloced. Do not return statically declared arrays – they are destroyed!

If the main function tries to read a destroyed array – SEGFAULT!

Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want ☺



# Returning Arrays from Functions

7

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays that have been malloced/calloced/realloced. Do not return statically declared arrays – they are destroyed!

If the main function tries to read a destroyed array – SEGFAULT!

Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want ☺

Disadvantage: all those values have to be of that same type



# Returning Arrays from Functions

7

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays that have been malloced/calloced/realloced. Do not return statically declared arrays – they are destroyed!

If the main function tries to read a destroyed array – SEGFAULT!

Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want ☺

Disadvantage: all those values have to be of that same type


Disadvantage: can only return one array ☹



# Returning Arrays from Functions

7

To return an array, simply return the address of the first element of the array – as simple as that ☺



**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays that have been malloced/calloced/realloced. Do not return statically declared arrays – they are destroyed!

If the main function tries to read a destroyed array – SEGFAULT!

Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want ☺

Disadvantage: all those values have to be of that same type

Disadvantage: can only return one array ☹



# Returning Arr

What if I want to return multiple arrays?

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays that have been malloced/calloced/realloced. Do not return statically declared arrays – they are destroyed!


If the main function tries to read a destroyed array – SEGFAULT!

Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want ☺

Disadvantage: all those values have to be of that same type

Disadvantage: can only return one array ☹



# Returning Arr

What if I want to return multiple arrays?



To return an array, simply return the address of the first element of the array – as simple as that 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays that have been malloced/calloced/realloced. Do not return statically declared arrays – they are destroyed!

If the main function tries to read a destroyed array – SEGFAULT!



Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want 😊

Disadvantage: all those values have to be of that same type

Disadvantage: can only return one array 😞



# Returning Arr



What if I want to return multiple arrays?

To return an array, simply return the address of the first element of the array – as simple as that 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays which you have dynamically allocated/calloced/realloced. Do not return statically declared arrays – they are destroyed!

If the main function tries to read a destroyed array – SEGFAULT!



Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want 😊

Disadvantage: all those values have to be of that same type

Disadvantage: can only return one array 😞



# Returning Arr

What if I want to return multiple arrays?

To return an array, simply return the address of the first element of the array – as simple as that 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays which you dynamically allocated/calloced/realloced. Do not return statically declared arrays – they are destroyed!




If the main function tries to read a destroyed array – SEGFAULT!

Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want 😊

Disadvantage: all those values have to be of that same type

Disadvantage: can only return one array 😞



# Returning Arr

What if I want to return multiple arrays?

To return an array, simply return the address of the first element of the array – as simple as that 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays which you dynamically allocated/calloced/realloced. Do not return statically declared arrays – they are destroyed!



If the main function tries to read a destroyed array – IT!

Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want 😊

Disadvantage: all those values have to be of that same type

Disadvantage: can only return one array 😞



# Returning Arr

What if I want to return multiple arrays?

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays which you dynamically allocated/calloced/realloced. Do not return statically declared arrays – they are destroyed!




If the main function tries to read a destroyed array – IT'S TERRIBLE!

Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want ☺

Disadvantage: all those values have to be of that same type

Disadvantage: can only return one array ☹



# Returning Arr

What if I want to return multiple arrays?

To return an array, simply return the address of the first element of the array – as simple as that ☺

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays which you dynamically allocated/malloced/calloced/reallocated – destroyed arrays – they are destroyed.




If the main function tries to read a destroyed array – **INCORRECT!**

Gives us another trick of returning multiple values from a function – simply return an array

Advantage: can return as many values as you want ☺

Disadvantage: all those values have to be of that same type

Disadvantage: can only return one array ☹



# Returning Arr

What if I want to return multiple arrays?

To return an array, simply return the address of the first element of the array – as simple as that 😊

**Rule 5** (of pointers): name of an array is nothing but a pointer to the first element of that array

**WARNING:** return only those arrays which you dynamically allocated/malloced/calloced/reallocated – destroyed arrays – they are destroyed.


If the main function tries to read a destroyed array – it will crash.

Gives us another trick of returning multiple variables from a function.

Using the same tricks we learnt till now to return multiple variables

**Trick 1:** malloc an array of pointers and return that array

**Trick 2:** ask the calling function to tell you the address where a pointer variable is stored so that you can modify the address (this will require passing a pointer to a pointer to the function)



Correct!

# Passing 2D arrays as inputs

8



ESC101: Fundamentals  
of Computing

# Passing 2D arrays as inputs

More care required for 2D arrays



# Passing 2D arrays as inputs

More care required for 2D arrays

Recall 2D arrays are stored as 1D arrays



# Passing 2D arrays as inputs

More care required for 2D arrays

Recall 2D arrays are stored as 1D arrays

```
char str[3][5];
```



# Passing 2D arrays as inputs



# More care required for 2D arrays

Recall 2D arrays are stored as 1D arrays

```
char str[3][5];
```

# Passing 2D arrays as inputs



# More care required for 2D arrays

Recall 2D arrays are stored as 1D arrays

```
char str[3][5];
```

# Passing 2D arrays as inputs

More care required for 2D arrays

Recall 2D arrays are stored as 1D arrays

```
char str[3][5];
```

000000	■■■■■
000001	■■■■■
000002	■■■■■
000003	■■■■■
str[0][0]	■■■■■
000004	■■■■■
str[0][1]	■■■■■
000005	■■■■■
str[0][2]	■■■■■
000006	■■■■■
str[0][3]	■■■■■
000007	■■■■■
str[0][4]	■■■■■
000008	■■■■■
str[1][0]	■■■■■
000009	■■■■■
str[1][1]	■■■■■
000010	■■■■■
str[1][2]	■■■■■
000011	■■■■■
str[1][3]	■■■■■
000012	■■■■■
str[1][4]	■■■■■
000013	■■■■■
str[2][0]	■■■■■
000014	■■■■■
str[2][1]	■■■■■
000015	■■■■■
str[2][2]	■■■■■
000016	■■■■■
str[2][3]	■■■■■
000017	■■■■■
str[2][4]	■■■■■
000018	■■■■■
000019	■■■■■
000020	■■■■■
000021	■■■■■
000022	■■■■■
000023	■■■■■
...	■■■■■


# Passing 2D arrays as inputs

More care required for 2D arrays

Recall 2D arrays are stored as 1D arrays

```
char str[3][5];
```

This means, in order to access str[1][0],  
we need to skip 5 elements



# Passing 2D arrays as inputs



More care required for 2D arrays

Recall 2D arrays are stored as 1D arrays

```
char str[3][5];
```

This means, in order to access `str[1][0]`, we need to skip 5 elements

To do so we need to know how many elements are there in each row

# Passing 2D arrays as inputs



# More care required for 2D arrays

Recall 2D arrays are stored as 1D arrays

```
char str[3][5];
```

This means, in order to access str[1][0], we need to skip 5 elements

To do so we need to know how many elements are there in each row

If passing a 2D array to a clone, must tell  
that clone this information

# Passing 2D arrays to functions

9



ESC101: Fundamentals  
of Computing

# Passing 2D arrays to functions

9

**Case 1:** both the number of rows and the number of columns are fixed



# Passing 2D arrays to functions

9

**Case 1:** both the number of rows and the number of columns are fixed

```
void access2D(char str[3][5], int i, int j){  
    printf("%c", str[i][j]);  
}  
  
int main(){  
    char str[3][5] = {"Hi", "Wow", "Bye"};  
    access2D(str, 1, 0);  
    return 0;  
}
```




# Passing 2D arrays to functions

9

**Case 1:** both the number of rows and the number of columns are fixed

```
void access2D(char str[3][5], int i, int j){  
    printf("%c", str[i][j]);  
}  
  
int main(){  
    char str[3][5] = {"Hi", "Wow", "Bye"};  
    access2D(str, 1, 0);  
    return 0;  
}
```




# Passing 2D arrays to functions

9

**Case 1:** both the number of rows and the number of columns are fixed

```
void access2D(char str[3][5], int i, int j){  
    printf("%c", str[i][j]);  
}  
  
int main(){  
    char str[3][5] = {"Hi", "Wow", "Bye"};  
    access2D(str, 1, 0);  
    return 0;  
}
```




# Passing 2D arrays to functions

9

**Case 1:** both the number of rows and the number of columns are fixed

Notice that our usual way of accessing array elements works here just fine!

```
void access2D(char str[3][5], int i, int j){  
    printf("%c", str[i][j]);  
}  
  
int main(){  
    char str[3][5] = {"Hi", "Wow", "Bye"};  
    access2D(str, 1, 0);  
    return 0;  
}
```



# Passing 2D arrays to functions

10



# Passing 2D arrays to functions

10

**Case 2:** number of rows  
unknown but number of  
columns are fixed



# Passing 2D arrays to functions

10

**Case 2:** number of rows unknown but number of columns are fixed

```
void access2D(char str[][5], int i, int j){  
    printf("%c", str[i][j]);  
}  
int main(){  
    char str[3][5] = {"Hi", "Wow", "Bye"};  
    access2D(str, 2, 1);  
    return 0;  
}
```




# Passing 2D arrays to functions

10

**Case 2:** number of rows unknown but number of columns are fixed

```
void access2D(char str[][5], int i, int j){  
    printf("%c", str[i][j]);  
}  
int main(){  
    char str[3][5] = {"Hi", "Wow", "Bye"};  
    access2D(str, 2, 1);  
    return 0;  
}
```




# Passing 2D arrays to functions

10

**Case 2:** number of rows unknown but number of columns are fixed

```
void access2D(char str[][5], int i, int j){  
    printf("%c", str[i][j]);  
}  
int main(){  
    char str[3][5] = {"Hi", "Wow", "Bye"};  
    access2D(str, 2, 1);  
    return 0;  
}
```




# Passing 2D arrays to functions

10

**Case 2:** number of rows unknown but number of columns are fixed

Notice that our usual way of accessing array elements still works here just fine!

```
void access2D(char str[][5], int i, int j){  
    printf("%c", str[i][j]);  
}  
  
int main(){  
    char str[3][5] = {"Hi", "Wow", "Bye"};  
    access2D(str, 2, 1);  
    return 0;  
}
```



# Passing 2D arrays to functions


10

**Case 2:** number of rows unknown but number of columns are fixed

Notice that our usual way of accessing array elements still works here just fine!

Note that specifying number of rows is not needed at all!

```
void access2D(char str[][5], int i, int j){  
    printf("%c", str[i][j]);  
}  
  
int main(){  
    char str[3][5] = {"Hi", "Wow", "Bye"};  
    access2D(str, 2, 1);  
    return 0;  
}
```



# Passing 2D arrays to functions

11



# Passing 2D arrays to functions

11

**Case 3:** both num. of rows  
and number of columns are  
unknown 😔



# Passing 2D arrays to functions

11

**Case 3:** both num. of rows  
and number of columns are  
unknown 😞

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements



# Passing 2D arrays to functions

11

**Case 3:** both num. of rows  
and number of columns are  
unknown ☹

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements

**Trick 1:** treat 2D array as a 1D  
array and do the indexing  
yourself ☺



# Passing 2D arrays to functions

11

**Case 3:** both num. of rows  
and number of columns are  
unknown ☹

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements

**Trick 1:** treat 2D array as a 1D  
array and do the indexing  
yourself ☺

Works since internally Mr C  
stores all 2D arrays as nothing  
but 1D arrays



# Passing 2D arrays to functions

11


**Case 3:** both num. of rows and number of columns are unknown ☹

Here, Mr C doesn't know how to access 2<sup>nd</sup> row elements

**Trick 1:** treat 2D array as a 1D array and do the indexing yourself ☺

Works since internally Mr C stores all 2D arrays as nothing but 1D arrays

```
void access2D(char* str, int i, int j, int c){  
    // c gives num of columns i.e. num of  
    // elements in each row  
    printf("%c", *(str + c * i + j));  
}  
  
int main(){  
    char str[3][5] = {"Hi","Wow","Bye"};  
    char *ptr = &str[0][0];  
    int numCols = 5;  
    access2D(str, 1, 2, numCols);  
    return 0;  
}
```



# Passing 2D arrays to functions

11



**Case 3:** both num. of rows and number of columns are unknown 😞

Here, Mr C doesn't know how to access 2<sup>nd</sup> row elements

**Trick 1:** treat 2D array as a 1D array and do the indexing yourself ☺

Works since internally Mr C stores all 2D arrays as nothing but 1D arrays

```
void access2D(char* str, int i, int j, int c){  
    // c gives num of columns i.e. num of  
    // elements in each row  
    printf("%c", *(str + c * i + j));  
}  
  
int main(){  
    char str[3][5] = {"Hi","Wow","Bye"};  
    char *ptr = &str[0][0];  
    int numCols = 5;  
    access2D(str, 1, 2, numCols);  
    return 0;  
}
```



# Passing 2D arrays to functions

11


**Case 3:** both num. of rows and number of columns are unknown 😞

Here, Mr C doesn't know how to access 2<sup>nd</sup> row elements

**Trick 1:** treat 2D array as a 1D array and do the indexing yourself ☺

Works since internally Mr C stores all 2D arrays as nothing but 1D arrays

```
void access2D(char* str, int i, int j, int c){  
    // c gives num of columns i.e. num of  
    // elements in each row  
    printf("%c", *(str + c * i + j));  
}  
  
int main(){  
    char str[3][5] = {"Hi","Wow","Bye"};  
    char *ptr = &str[0][0];  
    int numCols = 5;  
    access2D(str, 1, 2, numCols);  
    return 0;  
}
```



# Passing 2D arrays to functions

11

**Cas** Both num. of rows and number of columns are unknown 😞

Here, Mr C doesn't know how to access 2<sup>nd</sup> row elements

**Trick 1:** treat 2D array as a 1D array and do the indexing yourself ☺

Works since internally Mr C stores all 2D arrays as nothing but 1D arrays



```
void access2D(char* str, int i, int j, int c){  
    // c gives num of columns i.e. num of  
    // elements in each row  
    printf("%c", *(str + c * i + j));  
}  
  
int main(){  
    char str[3][5] = {"Hi","Wow","Bye"};  
    char *ptr = &str[0][0];  
    int numCols = 5;  
    access2D(str, 1, 2, numCols);  
    return 0;  
}
```



# Passing 2D arrays

11

Caso  
and number of columns are  
unknown 😞

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements


**Trick 1:** treat 2D array as a 1D  
array and do the indexing  
yourself ☺

Works since internally Mr C  
stores all 2D arrays as nothing  
but 1D arrays

If accessing row index 0 column index 2, simply skip 2 elements of first row. If accessing row index 1 column index 2, first skip 5 elements of first row and then skip 2 elements of 2<sup>nd</sup> row

```
c){  
    // c gives num of columns i.e. num of  
    // elements in each row  
    printf("%c", *(str + c * i + j));  
}
```

```
int main(){  
    char str[3][5] = {"Hi","Wow","Bye"};  
    char *ptr = &str[0][0];  
    int numCols = 5;  
    access2D(str, 1, 2, numCols);  
    return 0;
```



# Passing 2D arrays to functions

12

**Case 3:** both num. of rows  
and number of columns are  
unknown 😞

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements



# Passing 2D arrays to functions

12

**Case 3:** both num. of rows  
and number of columns are  
unknown 😞

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements

**Trick 2:** create array of arrays



# Passing 2D arrays to functions

**Case 3:** both num. of rows  
and number of columns are  
unknown 😞

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements

**Trick 2:** create array of arrays

Advantage: hassle free indexing



# Passing 2D arrays to functions

12

**Case 3:** both num. of rows  
and number of columns are  
unknown ☹

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements

**Trick 2:** create array of arrays

Advantage: hassle free indexing

Disadvantage: write code for malloc ☺



# Passing 2D arrays to functions

12

**Case 3:** both num. of rows  
and number of columns are  
unknown ☹

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements

**Trick 2:** create array of arrays

Advantage: hassle free indexing

Disadvantage: write code for malloc ☺

This works since going to the second  
row does not require knowing how  
many elements are there in first row



# Passing 2D arrays to functions

12

**Case 3:** both num. of rows  
and number of columns are  
unknown ☹

Here, Mr C doesn't know how  
to access 2<sup>nd</sup> row elements

**Trick 2:** create array of arrays

Advantage: hassle free indexing

Disadvantage: write code for malloc ☺

This works since going to the second  
row does not require knowing how  
many elements are there in first row

In case of arrays of arrays, every row  
has a separate pointer pointing to its  
first element – see last week's lecture



# Passing 2D arrays to functions

12

**Case 3:** both num. of rows and number of columns are unknown ☹

Here, Mr C doesn't know how to access 2<sup>nd</sup> row elements

**Trick 2:** create array of arrays

Advantage: hassle free indexing

Disadvantage: write code for malloc ☺

This works since going to the second row does not require knowing how many elements are there in first row

In case of arrays of arrays, every row has a separate pointer pointing to its first element – see last week's lecture

```
void access2D(char** str, int i, int j){  
    printf("%c", str[i][j]);  
}  
  
int main(){  
    char **str = (char**)malloc(3*sizeof(char*));  
    int i;  
    for(i = 0; i < 3; i++){  
        str[i] = (char*)malloc(5*sizeof(char));  
        gets(str[i]);  
    }  
    access2D(str, 1, 1);  
    return 0;  
}
```



# Passing 2D arrays to functions

Now, we'll see how to access 2<sup>nd</sup> row elements

## Trick 2: create array of arrays

Advantage: hassle free indexing

Disadvantage: write code for malloc ☺

This works since going to the second row does not require knowing how many elements are there in first row

In case of arrays of arrays, every row has a separate pointer pointing to its first element – see last week's lecture

```
void access2D(char** str, int i, int j){  
    printf("%c", str[i][j]);  
}  
int main(){  
    char **str = (char**)malloc(3*sizeof(char*));  
    int i;  
    for(i = 0; i < 3; i++){  
        str[i] = (char*)malloc(5*sizeof(char));  
        gets(str[i]);  
    }  
    access2D(str, 1, 1);  
    return 0;  
}
```



# Passing 2D arrays to functions

Hi  
Wow  
Bye

Now how  
to access 2<sup>nd</sup> row elements

## Trick 2: create array of arrays

Advantage: hassle free indexing

Disadvantage: write code for malloc ☺

This works since going to the second row does not require knowing how many elements are there in first row

In case of arrays of arrays, every row has a separate pointer pointing to its first element – see last week's lecture

```
void access2D(char** str, int i, int j){  
    printf("%c", str[i][j]);  
}  
  
int main(){  
    char **str = (char**)malloc(3*sizeof(char*));  
    int i;  
    for(i = 0; i < 3; i++){  
        str[i] = (char*)malloc(5*sizeof(char));  
        gets(str[i]);  
    }  
    access2D(str, 1, 1);  
    return 0;  
}
```



# Passing 2D arrays to functions

12

Console Activity Log Input Output

Hi  
Wow  
Bye

ws are

Now how to access 2<sup>nd</sup> row elements

## Trick 2: create array of arrays


Advantage: hassle free indexing

Disadvantage: write code for malloc ☺

This works since going to the second row does not require knowing how many elements are there in first row

In case of arrays of arrays, every row has a separate pointer pointing to its first element – see last week's lecture

```
void access2D(char** str, int i, int j){  
    printf("%c", str[i][j]);  
}  
int main(){  
    char **str = (char**)malloc(3*sizeof(char*));  
    int i;  
    for(i = 0; i < 3; i++){  
        str[i] = (char*)malloc(5*sizeof(char));  
        gets(str[i]);  
    }  
    access2D(str, 1, 1);  
    return 0;  
}
```



# Passing 2D arrays to functions

Hi  
Wow  
Bye

Now how to access 2<sup>nd</sup> row elements

## Trick 2: create array of arrays

Advantage: hassle free indexing

Disadvantage: write code for malloc ☺

This works since going to the second row does not require knowing how many elements are there in first row

In case of arrays of arrays, every row has a separate pointer pointing to its first element – see last week's lecture

```
void access2D(char** str, int i, int j){
    printf("%c", str[i][j]);
}

int main(){
    char **str = (char**)malloc(3*sizeof(char*));
    int i;
    for(i = 0; i < 3; i++){
        str[i] = (char*)malloc(5*sizeof(char));
        gets(str[i]);
    }
    access2D(str, 1, 1);
    return 0;
}
```

