



WIKIPEDIA
The Free Encyclopedia

[Main page](#)
[Contents](#)
[Featured content](#)
[Current events](#)
[Random article](#)
[Donate to Wikipedia](#)
[Wikipedia store](#)

Interaction

[Help](#)
[About Wikipedia](#)
[Community portal](#)
[Recent changes](#)
[Contact page](#)

Tools

[What links here](#)
[Related changes](#)
[Upload file](#)
[Special pages](#)
[Permanent link](#)
[Page information](#)
[Wikidata item](#)
[Cite this page](#)

Print/export

[Create a book](#)
[Download as PDF](#)
[Printable version](#)

Languages


[Deutsch](#)
[日本語](#)
[Русский](#)

 [Edit links](#)

[Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)



BCJR algorithm

From Wikipedia, the free encyclopedia

The **BCJR algorithm** is an algorithm for [maximum a posteriori](#) decoding of [error correcting codes](#) defined on trellises (principally [convolutional codes](#)). The algorithm is named after its inventors: Bahl, Cocke, [Jelinek](#) and Raviv.^[1] This algorithm is critical to modern iteratively-decoded error-correcting codes including [turbo codes](#) and [low-density parity-check codes](#).

Contents [hide]

- 1 Steps involved
- 2 Variations
 - 2.1 SBTG BCJR
 - 2.2 Log-Map BCJR
 - 2.3 Max-Log-Map BCJR
- 3 Implementations
- 4 See also
- 5 References
- 6 External links

Steps involved [\[edit\]](#)

Based on the [trellis](#):

- Compute Forward probabilities α
- Compute Backward probabilities β
- Compute smoothed probabilities based on other information (i.e. noise variance for [AWGN](#), bit crossover probability for [Binary symmetric channel](#))

Variations [\[edit\]](#)

SBGT BCJR [\[edit\]](#)

Berrou, Glavieux and Thitimajshima Simplification.^[2]

Log-Map BCJR [\[edit\]](#)

^[3]

Max-Log-Map BCJR [\[edit\]](#)


Implementations [\[edit\]](#)

- [Susa](#) framework implements BCJR algorithm for [Forward error correction](#) codes and channel equalization in C++.

See also [\[edit\]](#)

- [Forward-backward algorithm](#)
- [Maximum a posteriori \(MAP\) estimation](#)
- [Hidden Markov model](#)

References [\[edit\]](#)

- ↑ L.Bahl, J.Cocke, F.Jelinek, and J.Raviv, "Optimal Decoding of Linear Codes for minimizing symbol error rate", IEEE Transactions on Information Theory, vol. IT-20(2), pp.284-287, March 1974.
- ↑ Sichun Wang and François Patenaude, "A Systematic Approach to Modified BCJR MAP Algorithms for Convolutional Codes," *EURASIP Journal on Applied Signal Processing*, vol. 2006, Article ID 95360, 15 pages, 2006. doi:[10.1155/ASP/2006/95360](#) 
- ↑ P. Robertson, P. Hoeher and E. Villebrun, "Optimal and Sub-Optimal Maximum A Posteriori Algorithms Suitable

External links [[edit](#)]

- [The on-line textbook: Information Theory, Inference, and Learning Algorithms](#) [[↗](#)], by [David J.C. MacKay](#), discusses the BCJR algorithm in chapter 25.
- [The implementation of BCJR algorithm in Susa signal processing framework](#) [[↗](#)]

Categories: [Error detection and correction](#)

This page was last modified on 25 June 2015, at 08:17.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

