

Main page Contents Featured content Current events Random article Donate to Wkipedia Wkipedia store

Interaction

Help About Wikipedia Community portal Recent changes Contact page

Tools

What links here Related changes Upload file Special pages Permanent link Page information Wkidata item Cite this page

Print/export

Create a book Download as PDF Printable version

Languages

Add links

Article Talk Read Edit More

Search

Q

Stone method

From Wikipedia, the free encyclopedia (Redirected from Stone's method)



This article includes a list of references, related reading or external links, but its sources remain unclear because it lacks inline citations. Please improve this article by introducing more precise citations. (September 2013)

In numerical analysis, **Stone's method**, also known as the **strongly implicit procedure** or **SIP**, is an algorithm for solving a sparse linear system of equations. The method uses an incomplete LU decomposition, which approximates the exact LU decomposition, to get an iterative solution of the problem. The method is named after Herbert L. Stone, who proposed it in 1968.

The LU decomposition is an excellent general purpose linear equation solver. The biggest disadvantage is that it fails to take advantage of coefficient matrix to be a sparse matrix. The LU decomposition of a sparse matrix is usually not sparse, thus, for large system of equations, LU decomposition may require a prohibitive amount of memory and number of arithmetical operations.

In the preconditioned iterative methods, if the preconditioner matrix \mathbf{M} is a good approximation of coefficient matrix \mathbf{A} then the convergence is faster. This brings us to idea of using approximate factorization $\mathbf{L}\mathbf{U}$ of \mathbf{A} as the iteration matrix \mathbf{M} .

A version of incomplete lower-upper decomposition method was proposed by H. L. Stone in 1968. This method is designed for equation system arising from discretisation of partial differential equations and was firstly used for a pentadiagonal system of equation obtained while solving an elliptic partial differential equation in a two dimensional space by a finite difference method. The LU approximate decomposition was looked in the same pentadiagonal form as the original matrix (three diagonal for L and three diagonals for U) as the best match of the seven possible equations for the five unknowns for the each row of the matrix.

Algorithm [edit]

```
For the linear system Ax = b
calculate Incomplete LU factorization of matrix A
      \mathbf{A}\mathbf{x} = (\mathbf{M} - \mathbf{N})\mathbf{x} = (\mathbf{L}\mathbf{U} - \mathbf{N})\mathbf{x} = \mathbf{b}
      \mathbf{M} \mathbf{x}^{(k+1)} = \mathbf{N} \mathbf{x}^{(k)} + \mathbf{b}, with ||\mathbf{M}|| >> ||\mathbf{N}||
      \mathbf{M} \mathbf{x}^{(k+1)} = \mathbf{L} \mathbf{J} \mathbf{J} \mathbf{x}^{(k+1)} = \mathbf{c}^{(k)}
      LUx^{(k)} = L(Ux^{(k+1)}) = Ly^{(k)} = c^{(k)}
set a guess
      k = 0, x^{(k)} r^{(k)} = b - Ax^{(k)}
while ( \|\mathbf{r}^{(k)}\|_2 \geq \epsilon ) do
      evaluate new right hand side
            c^{(k)} = \mathbf{N}\mathbf{x}^{(k)} + \mathbf{b}
      solve Ly^{(k)} = c^{(k)} by forward substitution
            y^{(k)} = L^{-1}c^{(k)}
      solve Ux^{(k+1)} = y^{(k)} by back substitution
            x^{(k+1)} = U^{-1}v^{(k)}
end while
```

References [edit]

- Stone, H. L. (1968). "Iterative Solution of Implicit Approximations of Multidimensional Partial Differential Equations". *SIAM Journal of Numerical Analysis* **5** (3): 530–538. doi:10.1137/0705044 & the original article
- Ferziger, J.H. and Peric, M. (2001). *Computational Methods for Fluid Dynamics*. Springer-Verlag, Berlin. ISBN 3-540-42074-6.
- Acosta, J.M. (2001). Numerical Algorithms for Three Dimensional Computational Fluid Dynamic Problems.

PhD Thesis. Polytechnic University of Catalunia.

• This article incorporates text from the article Stone's_method & on CFD-Wiki & that is under the GFDL license.

v•t•e	Numerical linear algebra	[hide]
Key concepts	Floating point · Numerical stability	
Problems	$\textbf{\textit{Matrix}} \textbf{\textit{multiplication}} (\textbf{\textit{algorithms}}) \cdot \textbf{\textit{Matrix}} \textbf{\textit{decompositions}} \cdot \textbf{\textit{Linear}} \textbf{\textit{equations}} \cdot \textbf{\textit{Sparse}} \textbf{\textit{problems}}$	
Hardware	CPU cache · TLB · Cache-oblivious algorithm · SIMD · Multiprocessing	
Software	BLAS · Specialized libraries · General purpose software	

Categories: Numerical linear algebra

This page was last modified on 12 February 2015, at 22:25.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

Privacy policy About Wikipedia Disclaimers Contact Wikipedia Developers Mobile view

