

Main page Contents Featured content Current events Random article Donate to Wkipedia Wkipedia store

Interaction

Help About Wikipedia Community portal Recent changes Contact page

Tools

What links here Related changes Upload file Special pages Permanent link Page information Wkidata item Cite this page

Print/export

Create a book Download as PDF Printable version

Languages

العربية

Bosanski

Deutsch
 Français
 Italiano
 Norsk bokmål
 Русский
 Српски / srpski

Українська

Article Talk Read Edit More Search Q

Line drawing algorithm

From Wikipedia, the free encyclopedia



This article may be expanded with text translated from the corresponding article in German. (December 2009) Click [show] for important translation instructions.

A **line drawing algorithm** is a graphical algorithm for approximating a line segment on discrete graphical media. On discrete media, such as pixel-based displays and printers, line drawing requires such an approximation (in nontrivial cases). Basic algorithms rasterize lines in one color. A better representation with multiple color gradations requires an advanced process, anti-aliasing.

On continuous media, by contrast, no algorithm is necessary to draw a line. For example, oscilloscopes use natural phenomena to draw lines and curves.

The Cartesian slope-intercept equation for a straight line is Y=mx+b With m representing the slope of the line and b as the y intercept. Given that the two endpoints of the line segment are specified at positions (x1,y1) and (x2,y2), we can determine

Two rasterized lines. The colored pixels are shown as circles. Above: monochrome screening; below: Gupta-Sproull anti-aliasing; the ideal line is considered here as a surface.

[show]

values for the slope m and y intercept b with the following calculations, m=(y2-y1)/(x2-x1) so, b=y1-m.x1.

A naive line-drawing algorithm [edit]

The simplest method of screening is the direct drawing of the equation defining the line.

```
dx = x2 - x1

dy = y2 - y1

for x from x1 to x2 {

y = y1 + dX * (x - x1) / dY
```

```
plot(x, y)
```

It is assumed here that the points have already been ordered so that $x_2>x_1$. This algorithm works just fine when dx>=dy (i.e., slope is less than or equal to 1), but if dx< dy (i.e., slope greater than 1), the line becomes quite sparse with lots of gaps, and in the limiting case of dx=0, only a single point is plotted.

The naïve line drawing algorithm is inefficient and thus, slow on a digital computer. Its inefficiency stems from the number of operations and the use of floating-point calculations. Line drawing algorithms such as Bresenham's or Wu's are preferred instead.

List of line drawing algorithms [edit]

The following is a partial list of line drawing algorithms:


- Digital Differential Analyzer (graphics algorithm) Similar to the naive line-drawing algorithm, with minor variations.
- Bresenham's line algorithm optimized to use only additions (i.e. no divisions or multiplications); it also avoids floating-point computations.
- Xiaolin Wu's line algorithm can perform spatial anti-aliasing, appears "ropey" from brightness varying

along the length of the line

• Gupta-Sproull algorithm

References [edit]

Fundamentals of Computer Graphics, 2nd Edition, A.K. Peters by Peter Shirley



Categories: Computer graphics algorithms

This page was last modified on 1 September 2015, at 08:34.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

Privacy policy About Wikipedia Disclaimers Contact Wikipedia Developers Mobile view



