



Interaction

- [Help](#)
- [About Wikipedia](#)
- [Community portal](#)
- [Recent changes](#)
- [Contact page](#)


Print/export

- Create a book
- Download as PDF
- Printable version

 Edit links

Article [Talk](#)

Read Edit View history

Search 

From Wikipedia, the free encyclopedia



Round-robin (RR) is one of the algorithms employed by [process](#) and [network schedulers](#) in [computing](#).^[1] As the term is generally used, [time slices](#) are assigned to each process in equal portions and in circular order, handling all processes without [priority](#) (also known as [cyclic executive](#)). Round-robin scheduling is simple, easy to implement, and [starvation-free](#). Round-robin scheduling can also be applied to other scheduling problems, such as data packet scheduling in computer networks. It is an [Operating System](#) concept.

Contents [[hide](#)]

- ## Process scheduling [\[edit\]](#)


In order to schedule processes fairly, a round-robin scheduler generally employs **time-sharing**, giving each job a time slot or *quantum*^[2] (its allowance of CPU time), and interrupting the job if it is not completed by then. The job is resumed next time a time slot is assigned to that process. If the process terminates or changes its state to waiting during its attributed time quantum, the scheduler selects the first process in the ready queue to execute. In the absence of time-sharing, or if the quanta were large relative to the sizes of the jobs, a process that produced large jobs would be favoured over other processes.

For example, if the time slot is 100 milliseconds, and *job1* takes a total time of 250 ms to complete, the round-robin scheduler will suspend the job after 100 ms and give other jobs their time on the CPU. Once the other jobs have had their equal share (100 ms each), *job1* will get another allocation of CPU time and the cycle will repeat. This process continues until the job finishes and needs no more time on the CPU.

- Consider the following table with the arrival time and execute time of the process with the quantum time of 100ms to understand the Round Robin Scheduling:

Process Name	Arrival Time	Execute Time
P0	0	250
P1	50	170
P2	130	75
P3	190	100
P4	210	130

P5	350	50
----	-----	----



Another approach is to divide all processes into an equal number of timing quanta such that the quantum size is proportional to the size of the process. Hence, all processes end at the same time.

Network packet scheduling [\[edit\]](#)

Main article: [Network scheduler](#)

In [best-effort packet switching](#) and other [statistical multiplexing](#), round-robin scheduling can be used as an alternative to [first-come first-served](#) queuing.

A multiplexer, switch, or router that provides round-robin scheduling has a separate queue for every data flow, where a data flow may be identified by its source and destination address. The algorithm lets every active data flow that has data packets in the queue to take turns in transferring packets on a shared channel in a periodically repeated order. The scheduling is **work-conserving**, meaning that if one flow is out of packets, the next data flow will take its place. Hence, the scheduling tries to prevent link resources from going unused.

Round-robin scheduling results in [max-min fairness](#) if the data packets are equally sized, since the data flow that has waited the longest time is given scheduling priority. It may not be desirable if the size of the data packets varies widely from one job to another. A user that produces large packets would be favored over other users. In that case [fair queuing](#) would be preferable.

If guaranteed or differentiated quality of service is offered, and not only best-effort communication, [deficit round-robin](#) (DRR) scheduling, [weighted round-robin](#) (WRR) scheduling, or [weighted fair queuing](#) (WFQ) may be considered.

In [multiple-access](#) networks, where several terminals are connected to a shared physical medium, round-robin scheduling may be provided by [token passing channel access](#) schemes such as [token ring](#), or by [polling](#) or resource reservation from a central control station.


In a centralized wireless packet radio network, where many stations share one frequency channel, a scheduling algorithm in a central base station may reserve time slots for the mobile stations in a round-robin fashion and provide fairness. However, if [link adaptation](#) is used, it will take a much longer time to transmit a certain amount of data to "expensive" users than to others since the channel conditions differ. It would be more efficient to wait

with the transmission until the channel conditions are improved, or at least to give scheduling priority to less expensive users. Round-robin scheduling does not utilize this. Higher throughput and [system spectrum efficiency](#) may be achieved by channel-dependent scheduling, for example a [proportionally fair](#) algorithm, or [maximum throughput scheduling](#). Note that the latter is characterized by undesirable [scheduling starvation](#). This type of scheduling is one of the very basic algorithms for Operating Systems in computers which can be implemented through circular queue Data Structure.

See also [\[edit\]](#)

- [Weighted round robin](#)
- [Deficit round robin](#)
- [Multilevel queue](#)

References [\[edit\]](#)

- ↑ Arpaci-Dusseau, Remzi H.; Arpaci-Dusseau, Andrea C. (2014), *Operating Systems: Three Easy Pieces [Chapter: Scheduling Introduction]*  (PDF), Arpaci-Dusseau Books
- ↑ Silberschatz, Abraham; Galvin, Peter B.; Gagne, Greg (2010). "Process Scheduling". *Operating System Concepts* (8th ed.). *John Wiley & Sons* (Asia). p. 194. ISBN 978-0-470-23399-3. "5.3.4 Round Robin Scheduling"

Categories: [Processor scheduling algorithms](#) | [Network scheduling algorithms](#)

This page was last modified on 1 July 2015, at 15:09.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

