



WIKIPEDIA
The Free Encyclopedia

Main page
Contents
Featured content
Current events
Random article
Donate to Wikipedia
Wikipedia store

Interaction

Help
About Wikipedia
Community portal
Recent changes
Contact page

Tools

What links here
Related changes
Upload file
Special pages
Permanent link
Page information
Wikidata item
Cite this page

Print/export

Create a book
Download as PDF
Printable version

Languages

Русский

Edit links

Article **Talk**

Read **Edit** View history

Sweep and prune

From Wikipedia, the free encyclopedia

In **physical simulations**, **sweep and prune** is a **broad phase** algorithm used during **collision detection** to limit the number of pairs of solids that need to be checked for **collision**, i.e. intersection. This is achieved by sorting the starts (lower bound) and ends (upper bound) of the **bounding volume** of each solid along a number of arbitrary axes. As the solids move, their starts and ends may overlap. When the bounding volumes of two solids overlap in all axes they are flagged to be tested by more precise and time consuming algorithms.

Sweep and prune exploits **temporal coherence** as it is likely that solids do not move significantly between two simulation steps. Because of that, at each step, the sorted lists of bounding volume starts and ends can be updated with relatively few computational operations. Sorting algorithms which are fast at sorting almost-sorted lists, such as **insertion sort**, are particularly good for this purpose.

According with the type of bounding volume used, it is necessary to update the bounding volume dimensions every time a solid is reoriented. To circumvent this, temporal coherence can be used to compute the changes in bounding volume geometry with fewer operations. Another approach is to use **bounding spheres** or other orientation independent bounding volumes.

Sweep and prune is also known as *sort and sweep*^[1] being called that way at David Baraff Ph. D thesis in 1992.^[2] Later works like the 1995 paper about I-COLLIDE by Cohen *et al.* ^[3] refer to the algorithm as *sweep and prune*.

See also [edit]

- Collision detection
- Bounding volume
- Physics engine
- Game physics

References [edit]

- ↑ Ericson, Christer (2005), *Real-time collision detection* , Morgan Kaufmann series in interactive 3D technology, Amsterdam: Elsevier, pp. 329–338, ISBN 978-1-55860-732-3
- ↑ Baraff, D. (1992), *Dynamic Simulation of Non-Penetrating Rigid Bodies, (Ph. D thesis)* , Computer Science Department, Cornell University, pp. 52–56
- ↑ Cohen, Jonathan D.; Lin, Ming C.; Manocha; Ponamgi, Madhav K. (April 9–12, 1995), *I-COLLIDE: an Interactive and Exact Collision Detection System for Large Scale Environments* (PDF), Proceedings of the 1995 Symposium on Interactive 3D Graphics (Monterey, CA), pp. 189–196

External links [edit]

- Bullet user manual
- Collision Detection in Interactive 3d Environments



*This computing article is a **stub**. You can help Wikipedia by expanding it.*

Categories: Computational physics Computer physics engines Computing stubs

This page was last modified on 25 September 2014, at 02:10.

Text is available under the **Creative Commons Attribution-ShareAlike License**; additional terms may apply. By using this site, you agree to the **Terms of Use** and **Privacy Policy**. Wikipedia® is a registered trademark of the **Wikimedia Foundation, Inc.**, a non-profit organization.

Privacy policy **About Wikipedia** **Disclaimers** **Contact Wikipedia** **Developers** **Mobile view**

