



WIKIPEDIA  
The Free Encyclopedia

Main page  
Contents  
Featured content  
Current events  
Random article  
Donate to Wikipedia  
Wikipedia store

Interaction  
Help  
About Wikipedia  
Community portal  
Recent changes  
Contact page

Tools  
What links here  
Related changes  
Upload file  
Special pages  
Permanent link  
Page information  
Wikidata item  
Cite this page

Print/export  
Create a book  
Download as PDF  
Printable version

Languages  
Português  
中文  
 Edit links

[Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)

# De Boor's algorithm

From Wikipedia, the free encyclopedia  
(Redirected from [De Boor algorithm](#))

In the [mathematical](#) subfield of [numerical analysis](#) the **de Boor's algorithm** is a fast and [numerically stable algorithm](#) for evaluating [spline curves](#) in [B-spline](#) form. It is a generalization of the [de Casteljau's algorithm](#) for [Bézier curves](#). The algorithm was devised by [Carl R. de Boor](#). Simplified, potentially faster variants of the de Boor algorithm have been created but they suffer from comparatively lower stability.<sup>[1][2]</sup>

## Contents

[\[hide\]](#)

- 1 Introduction
- 2 Outline of the algorithm
- 3 The algorithm
- 4 See also
- 5 External links
  - 5.1 Computer code
- 6 References

## Introduction [\[edit\]](#)

The general setting is as follows. We would like to construct a curve whose shape is described by a sequence of  $p$  points  $\mathbf{d}_0, \mathbf{d}_1, \ldots, \mathbf{d}_{p-1}$ , which plays the role of a *control polygon*. The curve can be described as a function  $\mathbf{s}(x)$  of one parameter  $x$ . To pass through the sequence of points, the curve must satisfy  $\mathbf{s}(u_0) = \mathbf{d}_0, \ldots, \mathbf{s}(u_{p-1}) = \mathbf{d}_{p-1}$ . But this is not quite the case: in general we are satisfied that the curve "approximates" the control polygon. We assume that  $u_0, \ldots, u_{p-1}$  are given to us along with  $\mathbf{d}_0, \mathbf{d}_1, \ldots, \mathbf{d}_{p-1}$ .

One approach to solve this problem is by [splines](#). A spline is a curve that is a piecewise  $n^{\text{th}}$  degree polynomial. This means that, on any interval  $[u_i, u_{i+1})$ , the curve must be equal to a polynomial of degree at most  $n$ . It may be equal to different polynomials on different intervals. The polynomials must be *synchronized*: when the polynomials from intervals  $[u_{i-1}, u_i)$  and  $[u_i, u_{i+1})$  meet at the point  $u_i$ , they must have the same value at this point and their derivatives must be equal (to ensure that the curve is smooth).

De Boor's algorithm is an algorithm which, given  $u_0, \ldots, u_{p-1}$  and  $\mathbf{d}_0, \mathbf{d}_1, \ldots, \mathbf{d}_{p-1}$ , finds the value of spline curve  $\mathbf{s}(x)$  at a point  $x$ . It uses  $O(n^2) + O(n + p)$  operations where  $n$  is the degree and  $p$  the number of control points of  $s$ .

## Outline of the algorithm [\[edit\]](#)

Suppose we want to evaluate the spline curve for a parameter value  $x \in [u_\ell, u_{\ell+1}]$ . We can express the curve as

$$\mathbf{s}(x) = \sum_{i=0}^{p-1} \mathbf{d}_i N_i^n(x),$$

where<sup>[3]</sup>

$$N_i^n(x) = \frac{x - u_i}{u_{i+n} - u_i} N_i^{n-1}(x) + \frac{u_{i+n+1} - x}{u_{i+n+1} - u_{i+1}} N_{i+1}^{n-1}(x),$$

and

$$N_i^0(x) = \begin{cases} 1, & \text{if } x \in [u_i, u_{i+1}) \\ 0, & \text{otherwise} \end{cases}$$

Due to the spline locality property,

$$\mathbf{s}(x) = \sum_{i=\ell-n}^{\ell} \mathbf{d}_i N_i^n(x)$$

So the value  $\mathbf{s}(x)$  is determined by the control points  $\mathbf{d}_{\ell-n}, \mathbf{d}_{\ell-n+1}, \dots, \mathbf{d}_{\ell}$ ; the other control points  $\mathbf{d}_i$  have no influence. De Boor's algorithm, described in the next section, is a procedure which efficiently calculates the expression for  $\mathbf{s}(x)$ .

## The algorithm [\[edit\]](#)

Suppose  $x \in [u_{\ell}, u_{\ell+1})$  and  $\mathbf{d}_i^{[0]} = \mathbf{d}_i$  for  $i = \ell - n, \dots, \ell$ . Now calculate

$$\mathbf{d}_i^{[k]} = (1 - \alpha_{k,i})\mathbf{d}_{i-1}^{[k-1]} + \alpha_{k,i}\mathbf{d}_i^{[k-1]}; \quad k = 1, \dots, n; \quad i = \ell - n + k, \dots, \ell$$

with

$$\alpha_{k,i} = \frac{x - u_i}{u_{i+n+1-k} - u_i}.$$

Then  $\mathbf{s}(x) = \mathbf{d}_{\ell}^{[n]}$ .

## See also [\[edit\]](#)

- De Casteljau's algorithm
- Bézier curve
- NURBS

## External links [\[edit\]](#)

- De Boor's Algorithm↗
- The DeBoor-Cox Calculation↗

## Computer code [\[edit\]](#)

TinySpline: Open source C-library for splines which implements De Boor's algorithm↗

## References [\[edit\]](#)

- ↑ Lee, E. T. Y. (December 1982). "A Simplified B-Spline Computation Routine". *Computing* (Springer-Verlag) **29** (4): 365–371. doi:10.1007/BF02246763 ↗.
- ↑ Lee, E. T. Y. (1986). "Comments on some B-spline algorithms". *Computing* (Springer-Verlag) **36** (3): 229–238. doi:10.1007/BF02240069 ↗.
- ↑ http://www.cs.mtu.edu/~shene/COURSES/cs3621/NOTES/spline/B-spline/bspline-basis.html ↗

Categories: Numerical analysis | Splines | Interpolation

This page was last modified on 28 July 2015, at 12:40.

Text is available under the  [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the  [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#)  [About Wikipedia](#)  [Disclaimers](#)  [Contact Wikipedia](#)  [Developers](#)  [Mobile view](#)

