



WIKIPEDIA
The Free Encyclopedia

[Main page](#)
[Contents](#)
[Featured content](#)
[Current events](#)
[Random article](#)
[Donate to Wikipedia](#)
[Wikipedia store](#)

Interaction
[Help](#)
[About Wikipedia](#)
[Community portal](#)
[Recent changes](#)
[Contact page](#)

Tools
[What links here](#)
[Related changes](#)
[Upload file](#)
[Special pages](#)
[Permanent link](#)
[Page information](#)
[Wikidata item](#)
[Cite this page](#)

Print/export
[Create a book](#)
[Download as PDF](#)
[Printable version](#)


Languages
[Ελληνικά](#)
[فارسی](#)
[Português](#)
[Српски / srpski](#)
[Tiếng Việt](#)
[中文](#)

 [Edit links](#)

[Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)



Maximum subarray problem

From Wikipedia, the free encyclopedia
(Redirected from [Kadane's algorithm](#))

In [computer science](#), the **maximum subarray problem** is the task of finding the contiguous subarray within a one-dimensional [array](#) of numbers (containing at least one positive number) which has the largest sum. For example, for the sequence of values −2, 1, −3, 4, −1, 2, 1, −5, 4; the contiguous subarray with the largest sum is 4, −1, 2, 1, with sum 6.

The problem was first posed by [Ulf Grenander](#) of [Brown University](#) in 1977, as a simplified model for [maximum likelihood](#) estimation of patterns in digitized images. A [linear time algorithm](#) was found soon afterwards by [Jay Kadane](#) of [Carnegie-Mellon University](#) ([Bentley 1984](#)).

Contents [hide]

- [1 Kadane's algorithm](#)
- [2 Generalizations](#)
- [3 See also](#)
- [4 References](#)
- [5 External links](#)

Kadane's algorithm [\[edit\]](#)

Kadane's algorithm consists of a scan through the array values, computing at each position the maximum (positive sum) subarray ending at that position. This subarray is either empty (in which case [its sum is zero](#)) or consists of one more element than the maximum subarray ending at the previous position. Thus, the problem can be solved with the following code, expressed here in [Python](#):

```
def max_subarray(A):  
    max_ending_here = max_so_far = 0  
    for x in A:  
        max_ending_here = max(0, max_ending_here + x)  
        max_so_far = max(max_so_far, max_ending_here)  
    return max_so_far
```

A variation of the problem that does not allow zero-length subarrays to be returned, in the case that the entire array consists of negative numbers, can be solved with the following code:

```
def max_subarray(A):  
    max_ending_here = max_so_far = A[0]  
    for x in A[1:]:  
        max_ending_here = max(x, max_ending_here + x)  
        max_so_far = max(max_so_far, max_ending_here)  
    return max_so_far
```

The algorithm can also be easily modified to keep track of the starting and ending indices of the maximum subarray.

Because of the way this algorithm uses optimal substructures (the maximum subarray ending at each position is calculated in a simple way from a related but smaller and overlapping subproblem: the maximum subarray ending at the previous position) this algorithm can be viewed as a simple example of [dynamic programming](#).

The runtime complexity of Kadane's algorithm is $O(n)$.

Generalizations [\[edit\]](#)

Similar problems may be posed for higher-dimensional arrays, but their solution is more complicated; see, e.g., [Takaoka \(2002\)](#). [Brodal & Jørgensen \(2007\)](#) showed how to find the *k* largest subarray sums in a one-dimensional array, in the optimal time bound $O(n + k)$.

See also [edit]

- [Subset sum problem](#)

References [edit]

- Bentley, Jon (1984), "Programming pearls: algorithm design techniques", *Communications of the ACM* **27** (9): 865–873, doi:[10.1145/358234.381162](#) .
- Brodal, Gerth Stølting; Jørgensen, Allan Grønlund (2007), "A linear time algorithm for the k maximal sums problem", *Mathematical Foundations of Computer Science 2007*, Lecture Notes in Computer Science **4708**, Springer-Verlag, pp. 442–453, doi:[10.1007/978-3-540-74456-6_40](#) .
- Takaoka, T. (2002), "Efficient algorithms for the maximum subarray problem by distance matrix multiplication" (PDF), *Electronic Notes in Theoretical Computer Science* **61**.

External links [edit]

- www.algorithmist.com
- alexeigor.wikidot.com
- [Algorithm Design Techniques](#)

Categories: [Optimization algorithms and methods](#) | [Dynamic programming](#)

This page was last modified on 23 August 2015, at 02:16.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)



a
WIKIMEDIA
project



Powered By
MediaWiki