

Main page Contents Featured content Current events Random article Donate to Wkipedia Wkipedia store

Interaction

Help About Wikipedia Community portal Recent changes Contact page

Tools

What links here Related changes Upload file Special pages Permanent link Page information Wkidata item Cite this page

Print/export

Create a book Download as PDF Printable version

Languages

العربية

Français

Article Talk Read Edit View history Search Q

Distance transform

From Wikipedia, the free encyclopedia (Redirected from Euclidean distance map)



This article includes a list of references, but its sources remain unclear because it has insufficient inline citations. Please help to improve this article by introducing more precise citations. (August 2014)

A distance transform, also known as distance map or distance field, is a derived representation of a digital image. The choice of the term depends on the point of view on the object in question: whether the initial image is transformed into another representation, or it is simply endowed with an additional map or field.

Distance fields can also be signed, in the case where it is important to distinguish whether the point is inside or outside of the shape.^[1]

The map labels each pixel of the image with the distance to the nearest *obstacle pixel*. A most common type of obstacle pixel is a *boundary pixel* in a binary image. See the image for an example of a chessboard distance transform on a binary image.

Usually the transform/map is qualified with the chosen metric. For example, one may speak of **Manhattan distance transform**, if the underlying metric is **Manhattan distance**. Common metrics are:

- Euclidean distance
- Taxicab geometry, also known as City block distance or Manhattan distance.
- Chessboard distance

Applications are digital image processing (e.g., blurring effects, skeletonizing), motion planning in robotics, and even pathfinding.

Uniformly-sampled signed distance fields have been used for GPU-accelerated font smoothing, for example by Valve Corporation researchers.^[2]

Signed distance fields can also be used for (3D) solid modelling. Rendering on typical GPU hardware requires conversion to polygon meshes, e.g. by the marching cubes algorithm.^[3]

The distance transform can also be used for font rendering using vectors instead of sampling from texture, as in the opensource project GLyphy.

See also [edit]

- Signed distance function
- Parallel curve
- Level sets methods for distance computation.[4]

References [edit]

- 1. A http://www.merl.com/publications/docs/TR2000-15.pdf
- 2. ^ Green, Chris (2007). "Improved alpha-tested magnification for vector textures and special effects". ACM SIGGRAPH 2007 courses on SIGGRAPH '07. doi:10.1145/1281500.1281665 ₺.
- 3. ^ https://www.youtube.com/watch?v=2MzSmdC49Ns ₺
- 4. A. R. Kimmel, N. Kiryati, and A. M. Bruckstein. Distance maps and weighted distance transforms . Journal of Mathematical Imaging and Vision, Special Issue on Topology and Geometry in Computer Vision, 6:223-233,1996.

External links [edit]

Fast distance transform in C++ ₺ by Felzenszwalb and Huttenlocher

- Distance Transform tutorials in CVonline
- Survey of fast exact Euclidean distance transform algorithms

 ☑
- Distance Transforms & by Henry Kwong and Dynamic Step Distance Transforms & by Richard Scott, The Wolfram Demonstrations Project.
- Morphological DistanceTransform function in Mathematica

Categories: Image processing | Digital geometry

This page was last modified on 28 August 2015, at 19:02.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

Privacy policy About Wikipedia Disclaimers Contact Wikipedia Developers Mobile view

