



WIKIPEDIA
The Free Encyclopedia

[Main page](#)
[Contents](#)
[Featured content](#)
[Current events](#)
[Random article](#)
[Donate to Wikipedia](#)
[Wikipedia store](#)

Interaction
[Help](#)
[About Wikipedia](#)
[Community portal](#)
[Recent changes](#)
[Contact page](#)

Tools
[What links here](#)
[Related changes](#)
[Upload file](#)
[Special pages](#)
[Permanent link](#)
[Page information](#)
[Wikidata item](#)
[Cite this page](#)

Print/export
[Create a book](#)
[Download as PDF](#)
[Printable version](#)

Languages
[Add links](#)

[Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)

Lamport's distributed mutual exclusion algorithm

From Wikipedia, the free encyclopedia

(Redirected from [Lamport's Distributed Mutual Exclusion Algorithm](#))



It has been suggested that this article be [merged](#) into [Lamport's bakery algorithm](#). ([Discuss](#)) *Proposed since October 2013.*

Lamport's Distributed Mutual Exclusion Algorithm is a contention-based algorithm for [mutual exclusion](#) on a [distributed system](#).

Contents [\[hide\]](#)

- 1 Algorithm
 - 1.1 Nodal properties
 - 1.2 Algorithm
- 2 Message complexity
- 3 Drawbacks
- 4 See also
- 5 References

Algorithm [\[edit\]](#)

Nodal properties [\[edit\]](#)

- Every process maintains a queue of pending requests for entering critical section in order. The queues are ordered by virtual time stamps derived from [Lamport timestamps](#).^[1]

Algorithm [\[edit\]](#)

Requesting process

- Enters its request in its own queue (ordered by time stamps)
- Sends a request to every node.
- Wait for replies from all other nodes.
- If own request is at the head of its queue and all replies have been received, enter critical section.
- Upon exiting the critical section, remove its request from the queue and send a release message to every process.

Other processes

- After receiving a request, enter the request in its own request queue (ordered by time stamps) and reply with a time stamp.
- After receiving release message, remove the corresponding request from its own request queue.
- If own request is at the head of its queue and all replies have been received, enter critical section.

Message complexity [\[edit\]](#)

This algorithm creates $3(N - 1)$ messages per request, or $(N - 1)$ messages and 2 broadcasts. $3(N - 1)$ messages per request includes:

- $(N - 1)$ total number of requests
- $(N - 1)$ total number of replies
- $(N - 1)$ total number of releases

Drawbacks [\[edit\]](#)

There exist multiple points of failure.

See also [\[edit\]](#)

- [Ricart-Agrawala algorithm](#) (an improvement over Lamport's algorithm)

- [Lamport's Bakery Algorithm](#)
- [Raymond's Algorithm](#)
- [Maekawa's Algorithm](#)
- [Suzuki-Kasami's Algorithm](#)
- [Naimi-Trehel's Algorithm](#)

References [\[edit\]](#)

- [^] Kshemkalyani, A., & Singhal, M. Chapter 9: Distributed Mutual Exclusion Algorithms. Distributed Computing: Principles, Algorithms, and Systems (Page 10 of 93). Cambridge University Press.



*This [computer science](#) article is a *stub*. You can help Wikipedia by [expanding it](#).*

Categories: [Computer science stubs](#) | [Concurrency control algorithms](#)

This page was last modified on 24 August 2015, at 14:00.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

