

Main page
Contents
Featured content
Current events
Random article
Donate to Wkipedia
Wkipedia store

Interaction

Help About Wikipedia Community portal Recent changes Contact page

Tools

What links here Related changes Upload file Special pages Permanent link Page information Wkidata item Cite this page

Print/export

Create a book
Download as PDF
Printable version

Languages Français Русский

▶ Edit links

Article Talk Read Edit View history Search Q

Fürer's algorithm

From Wikipedia, the free encyclopedia

Fürer's algorithm is an integer multiplication algorithm for very large numbers possessing a very low asymptotic complexity. It was created in 2007 by Swiss mathematician Martin Fürer of Pennsylvania State University^[1] as an asymptotically faster (when analysed on a multitape Turing machine) algorithm than its predecessor, the Schönhage–Strassen algorithm published in 1971.^[2]

The predecessor to the Fürer algorithm, the Schönhage–Strassen algorithm, used fast Fourier transforms to compute integer products in time $O(n\log n\log\log n)$ (in big O notation) and its authors, Arnold Schönhage and Volker Strassen, also conjectured a lower bound for the problem of $\Omega(n\log n)$. Here, n denotes the total number of bits in the two input numbers. Fürer's algorithm reduces the gap between these two bounds: it can be used to multiply binary integers of length n in time $n\log n \, 2^{O(\log^* n)}$ (or by a circuit with that many logic gates), where $\log^* n$ represents the iterated logarithm operation. However, the difference between the $\log \log n$ and $2^{\log^* n}$ factors in the time bounds of the Schönhage–Strassen algorithm and the Fürer algorithm for realistic values of n is very small. [1]

In 2008, Anindya De, Chandan Saha, Piyush Kurur and Ramprasad Saptharishi^[3] gave a similar algorithm that relies on modular arithmetic instead of complex arithmetic to achieve the same running time.

In 2014, David Harvey, Joris van der Hoeven, and Grégoire Lecerf^[4] showed that an optimized version of Fürer's algorithm achieves a running time of $O(n \log n 2^{4 \log^* n})$, making the implied constant in the $O(\log^* n)$ exponent explicit. They also gave a modification to Fürer's algorithm that achieves $O(n \log n 2^{3 \log^* n})$

In 2015 Svyatoslav Covanov and Emmanuel Thomé provided another modifications that achieves same running time. [5] Yet, as all the other implementation, it's still not practical. [citation needed]

See also [edit]

• Number-theoretic transform

References [edit]

- 1. ^a b Fürer, M. (2007). "Faster Integer Multiplication "I" in Proceedings of the thirty-ninth annual ACM symposium on Theory of computing, June 11–13, 2007, San Diego, California, USA
- 2. ^ A. Schönhage and V. Strassen, "Schnelle Multiplikation großer Zahlen", Computing 7 (1971), pp. 281–292.
- Anindya De, Piyush P Kurur, Chandan Saha, Ramprasad Saptharishi. Fast Integer Multiplication Using Modular Arithmetic. Symposium on Theory of Computation (STOC) 2008. arXiv:0801.1416
- A David Harvey, Joris van der Hoeven, and Grégoire Lecerf, "Even faster integer multiplication", 2014, arXiv:1407.3360
- Svyatoslav Covanov and Emmanuel Thomé, "Fast arithmetic for faster integer multiplication", 2015 arXiv:1502.02800

V• T• E	Number-theoretic algorithms [hide]
Primality tests	AKS TEST · APR TEST · Baillie—PSW · ECPP TEST · Elliptic curve · Pocklington · Fermat · Lucas · Lucas—Let-Mer · Périn's · Quadratic Frobenius test · Solovay—Strassen · Miller—Rabin
Prime-generating	Sieve of Atkin · Sieve of Eratosthenes · Sieve of Sundaram · Wheel factorization
Integer factorization	Continued fraction (CFRAC) · Dixon's · Lenstra elliptic curve (ECM) · Euler's · Pollard's rho · $p-1\cdot p+1\cdot$ Quadratic sieve (QS) · General number field sieve (GNFS) · Special number field sieve (SNFS) · Rational sieve · Fermat's · Shanks' square forms · Trial division · Shor's
Multiplication	Ancient Egyptian · Long · Karatsuba · Toom–Cook · Schönhage–Strassen · Fürer's
Discrete logarithm	Baby-step Gant-step · Pollard rho · Pollard kangaroo · Pohlig-Hellman · Index calculus · Function field sieve
Greatest common divisor	Binary · Euclidean · Extended Euclidean · Lehmer's
Modular square root	Cipolla · Pocklington's · Tonelli–Shanks

Other algorithms

 $\textbf{Chakravala} \cdot \textbf{Cornacchia} \cdot \textbf{Integer relation} \cdot \textbf{Integer square root} \cdot \textbf{Modular exponentiation} \cdot \textbf{Schoofs}$

Italics indicate that algorithm is for numbers of special forms • SMALLCAPS indicate a deterministic algorithm



This algorithms or data structures-related article is a stub. You can help Wikipedia by expanding it.

Categories: Computer arithmetic algorithms | Algorithms and data structures stubs | Computer science stubs

This page was last modified on 4 August 2015, at 12:53.

Text is available under the Oreative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

Privacy policy About Wikipedia Disclaimers Contact Wikipedia Developers Mobile view



