

Main page
Contents
Featured content
Current events
Random article
Donate to Wkipedia
Wkipedia store

Interaction

Help About Wikipedia Community portal Recent changes Contact page

Tools

What links here Related changes Upload file Special pages Permanent link Page information Wkidata item Cite this page

Print/export

Create a book
Download as PDF
Printable version

Languages

العربية

Français

0

Article Talk Read Edit View history Search Q

## Binary splitting

From Wikipedia, the free encyclopedia

In mathematics, **binary splitting** is a technique for speeding up numerical evaluation of many types of series with rational terms. In particular, it can be used to evaluate hypergeometric series at rational points. Given a series

$$S(a,b) = \sum_{n=a}^{b} \frac{p_n}{q_n}$$

where  $p_n$  and  $q_n$  are integers, the goal of binary splitting is to compute integers P(a, b) and Q(a, b) such that

$$S(a,b) = \frac{P(a,b)}{Q(a,b)}.$$

The splitting consists of setting m = [(a + b)/2] and recursively computing P(a, b) and Q(a, b) from P(a, m), P(m, b), Q(a, m), and Q(m, b). When a and b are sufficiently close, P(a, b) and Q(a, b) can be computed directly from  $p_a...p_b$  and  $q_a...q_b$ .

Binary splitting requires more memory than direct term-by-term summation, but is asymptotically faster since the sizes of all occurring subproducts are reduced. Additionally, whereas the most naive evaluation scheme for a rational series uses a full-precision division for each term in the series, binary splitting requires only one final division at the target precision; this is not only faster, but conveniently eliminates rounding errors. To take full advantage of the scheme, fast multiplication algorithms such as Toom–Cook and Schönhage–Strassen must be used; with ordinary  $O(n^2)$  multiplication, binary splitting may render no speedup at all or be slower.

Since all subdivisions of the series can be computed independently of each other, binary splitting lends well to parallelization and checkpointing.

In a less specific sense, *binary splitting* may also refer to any divide and conquer algorithm that always divides the problem in two halves.

## References rediti

- David V. Chudnovsky & Gregory V. Chudnovsky. Computer algebra in the service of mathematical physics and number theory. In Computers and Mathematics (Stanford, CA, 1986), pp. 09–232, Dekker, New York, 1990.
- Bruno Haible, Thomas Papanikolaou. Fast multiprecision evaluation of series of rational numbers . Paper distributed with the CLN library source code.
- Lozier, D.W. and Olver, F.W.J. Numerical Evaluation of Special Functions. Mathematics of Computation 1943–1993: A Half-Century of Computational Mathematics, W.Gautschi, eds., Proc. Sympos. Applied Mathematics, AMS, v.48, pp. 79–125 (1994).
- Bach, E. The complexity of number-theoretic constants. Info. Proc. Letters, N 62, pp. 145–152 (1997).
- Borwein, J.M., Bradley, D.M. and Crandall, R.E. Computational strategies for the Riemann zeta function. J. of Comput. Appl. Math., v.121, N 1-2, pp. 247–296 (2000).
- Karatsuba, E.A. Fast evaluation of transcendental functions. (English. Russian original) Probl. Inf. Transm. 27, No.4, 339-360 (1991); translation from Probl. Peredachi Inf. 27, No.4, 76–99 (1991).

Categories: Computer arithmetic algorithms

This page was last modified on 15 March 2013, at 07:22.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.



