




WIKIPEDIA  
The Free Encyclopedia

Main page  
Contents  
Featured content  
Current events  
Random article  
Donate to Wikipedia  
Wikipedia store

Interaction  
Help  
About Wikipedia  
Community portal  
Recent changes  
Contact page

Tools  
What links here  
Related changes  
Upload file  
Special pages  
Permanent link  
Page information  
Wikidata item  
Cite this page


Print/export  
Create a book  
Download as PDF  
Printable version

Languages  
Српски / srpski  Edit links

[Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)



# Spaghetti sort

From Wikipedia, the free encyclopedia



**This article has multiple issues.** Please help [improve it](#) or [\[hide\]](#) discuss these issues on the [talk page](#).

- This article **may be confusing or unclear to readers**. (July 2013)
- This article's **factual accuracy is disputed**. (July 2013)

**Spaghetti sort** is a [linear-time](#), [analog algorithm](#) for sorting a sequence of items, by [Alexander Dewdney](#) in his column, *Scientific American*.<sup>[1][2][3]</sup> This algorithm sorts a sequence of items requiring  $O(n)$  stack space<sup>[*citation needed*]</sup> in a stable manner. It requires a parallel processor.<sup>[*citation needed*]</sup>

**Contents** [\[hide\]](#)

- 1 Algorithm
- 2 Analysis
- 3 References
- 4 External links

## Algorithm [\[edit\]](#)

For simplicity, assume we are sorting a list of [natural numbers](#). The sorting method is illustrated using uncooked rods of [spaghetti](#):

1. For each number  $x$  in the list, obtain a rod of length  $x$ . (One practical way of choosing the unit is to let the largest number  $m$  in the list correspond to one full rod of spaghetti. In this case, the full rod equals  $m$  spaghetti units. To get a rod of length  $x$ , break a rod in two so that one piece is of length  $x$  units; discard the other piece.)
2. Once you have all your spaghetti rods, take them loosely in your fist and lower them to the table, so that they all stand upright, resting on the table surface. Now, for each rod, lower your other hand from above until it meets with a rod—this one is clearly the longest. Remove this rod and insert it into the front of the (initially empty) output list (or equivalently, place it in the last unused slot of the output array). Repeat until all rods have been removed.




## Analysis [\[edit\]](#)

Preparing the  $n$  rods of spaghetti takes linear time. Lowering the rods on the table takes constant time,  $O(1)$ . This is possible because the hand, the spaghetti rods and the table work as a fully [parallel computing](#) device. There are then  $n$  rods to remove so, assuming each contact-and-removal operation takes constant time, the worst-case time complexity of the algorithm is  $O(n)$ .

## References [\[edit\]](#)

- ↑ Dewdney, A. K. (June 1984), "On the spaghetti computer and other analog gadgets for problem solving", *Scientific American* **250** (6): 19–26
- ↑ Stauffer, Dietrich (May 15, 1999), *Annual Reviews of Computational Physics VI*, [World Scientific](#), p. 260, ISBN 981-02-3563-1
- ↑ Adamatzky, Andrew (July 1, 2006), *From Utopian to Genuine Unconventional Computers*, [Luniver Press](#), p. 96, ISBN 0-9551170-9-7

## External links [\[edit\]](#)

- [A. K. Dewdney's homepage](#) 
- [Implementations of a model of physical sorting](#), Boole Centre for Research in Informatics 
- [Classical/Quantum Computing](#), IFF-Institute 

v · t · e

**Sorting algorithms**

[\[show\]](#)

This page was last modified on 17 April 2015, at 15:53.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

