

Main page Contents Featured content Current events Random article Donate to Wkipedia Wkipedia store

Interaction

Help About Wikipedia Community portal Recent changes Contact page

Tools

What links here Related changes Upload file Special pages Permanent link Page information Wkidata item Cite this page

Print/export

Create a book Download as PDF Printable version

Languages

Add links

Article Talk Read Edit More ▼ Search Q

Metropolis light transport

From Wikipedia, the free encyclopedia



This article includes a list of references, but its sources remain unclear because it has insufficient inline citations. Please help to improve this article by introducing more precise citations. (February 2014)

The **Metropolis light transport (MLT)** is an application of a variant of the Monte Carlo method called the Metropolis-Hastings algorithm to the rendering equation for generating images from detailed physical descriptions of three-dimensional scenes.^{[1][2]}

The procedure constructs paths from the eye to a light source using bidirectional path tracing, then constructs slight modifications to the path. Some careful statistical calculation (the Metropolis algorithm) is used to compute the appropriate distribution of brightness over the image. This procedure has the advantage, relative to bidirectional path tracing, that once a path has been found from light to eye, the algorithm can then explore nearby paths; thus difficult-to-find light paths can be explored more thoroughly with the same number of simulated photons. In short, the algorithm generates a path and stores the path's 'nodes' in a list. It can then modify the path by adding extra nodes and creating a new light path. While creating this new path, the algorithm decides how many new 'nodes' to add and whether or not these new nodes will actually create a new path.

Metropolis Light Transport is an unbiased method that, in some cases (but not always), converges to a solution of the rendering equation faster than other unbiased algorithms such as path tracing or bidirectional path tracing. [citation needed]

See also [edit]

• Nicholas Metropolis - The physicist after whom the algorithm is named

Renderers using MLT:

- Arion Render A commercial unbiased renderer based on path tracing and providing an MLT sampler
- Indigo Renderer A commercial unbiased 3D renderer that uses MLT
- Iray (external link [3]) An unbiased renderer that has an option for MLT [3][4]
- Kerkythea A free unbiased 3D renderer that uses MLT
- LuxRender An open source unbiased renderer that uses MLT
- Mitsuba Renderer A research-oriented renderer which implements several MLT variants

References [edit]

- 1. ^ Veach, E.; Guibas, L. J. (1997). "Metropolis light transport". Proceedings of the 24th annual conference on Computer graphics and interactive techniques SIGGRAPH '97. p. 65. doi:10.1145/258734.258775 & ISBN 0897918967.
- 2. ^ Eric Veach; Leonidas J. Guibas. "Metropolis Light Transport" [] (PDF). Stanford University.
- 3. ^ "NVIDIA Advanced Rendering: NVIDIA Iray" & Nvidia-arc.com. Retrieved 2014-02-03.
- 4. ^ "The Architectural and Caustic samplers iray dev blog" ☑. Blog.irayrender.com. 2013-05-30. Retrieved 2014-02-03.

External links [edit]

- Metropolis project at Stanford ☑
- LuxRender an open source render engine that supports MLT ₪
- A Practical Introduction to Metropolis Light Transport
- Unbiased physically based rendering on the GPU
 GPU



This computing article is a stub. You can help Wikipedia by expanding it.

Categories: Monte Carlo methods | Global illumination algorithms | Computing stubs

This page was last modified on 28 August 2015, at 16:12.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

Privacy policy About Wikipedia Disclaimers Contact Wikipedia Developers Mobile view



