



WIKIPEDIA
The Free Encyclopedia

[Main page](#)
[Contents](#)
[Featured content](#)
[Current events](#)
[Random article](#)
[Donate to Wikipedia](#)
[Wikipedia store](#)

Interaction
[Help](#)
[About Wikipedia](#)
[Community portal](#)
[Recent changes](#)
[Contact page](#)

Tools
[What links here](#)
[Related changes](#)
[Upload file](#)
[Special pages](#)
[Permanent link](#)
[Page information](#)
[Wikidata item](#)
[Cite this page](#)

Print/export
[Create a book](#)
[Download as PDF](#)
[Printable version](#)

Languages
[Русский](#)
[Edit links](#)

[Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)

Search

Pollard's rho algorithm for logarithms

From Wikipedia, the free encyclopedia

Pollard's rho algorithm for logarithms is an algorithm introduced by [John Pollard](#) in 1978 for solving the [discrete logarithm](#) problem analogous to [Pollard's rho algorithm](#) for solving the [Integer factorization](#) problem.

The goal is to compute γ such that $\alpha^\gamma = \beta$, where β belongs to a [cyclic group](#) G generated by α . The algorithm computes integers a , b , A , and B such that $\alpha^a \beta^b = \alpha^A \beta^B$. Assuming, for simplicity, that the underlying group is cyclic of order n , we can calculate γ as a solution of the equation

$$(B - b)\gamma = (a - A) \pmod{n}.$$

To find the needed a , b , A , and B the algorithm uses [Floyd's cycle-finding algorithm](#) to find a cycle in the sequence $x_i = \alpha^{a_i} \beta^{b_i}$, where the function $f : x_i \mapsto x_{i+1}$ is assumed to be random-looking and thus is likely to enter into a loop after approximately $\sqrt{\frac{\pi n}{2}}$ steps. One way to define such a function is to use the

following rules: Divide G into three disjoint subsets of approximately equal size: S_0 , S_1 , and S_2 . If x_i is in S_0 then double both a and b ; if $x_i \in S_1$ then increment a , if $x_i \in S_2$ then increment b .

Contents [\[hide\]](#)

- [1 Algorithm](#)
- [2 Example](#)
- [3 Complexity](#)
- [4 References](#)

Algorithm [\[edit\]](#)

Let G be a cyclic group of order p , and given $\alpha, \beta \in G$, and a partition $G = S_0 \cup S_1 \cup S_2$, let $f : G \rightarrow G$ be a map

$$f(x) = \begin{cases} \beta x & x \in S_0 \\ x^2 & x \in S_1 \\ \alpha x & x \in S_2 \end{cases}$$

and define maps $g : G \times \mathbb{Z} \rightarrow \mathbb{Z}$ and $h : G \times \mathbb{Z} \rightarrow \mathbb{Z}$ by

$$g(x, n) = \begin{cases} n & x \in S_0 \\ 2n \pmod{p} & x \in S_1 \\ n + 1 \pmod{p} & x \in S_2 \end{cases}$$
$$h(x, n) = \begin{cases} n + 1 \pmod{p} & x \in S_0 \\ 2n \pmod{p} & x \in S_1 \\ n & x \in S_2 \end{cases}$$

Inputs a a generator of G , b an element of G

Output An integer x such that $a^x = b$, or failure

- Initialise $a_0 \leftarrow 0$
 $b_0 \leftarrow 0$
 $x_0 \leftarrow 1 \in G$
 $i \leftarrow 1$
- $x_i \leftarrow f(x_{i-1})$, $a_i \leftarrow g(x_{i-1}, a_{i-1})$, $b_i \leftarrow h(x_{i-1}, b_{i-1})$
- $x_{2i} \leftarrow f(f(x_{2i-2}))$, $a_{2i} \leftarrow g(f(x_{2i-2}), g(x_{2i-2}, a_{2i-2}))$, $b_{2i} \leftarrow h(f(x_{2i-2}), h(x_{2i-2}, b_{2i-2}))$
- If $x_i = x_{2i}$ then
 - $r \leftarrow b_i - b_{2i}$
 - If $r = 0$ return failure
 - $x \leftarrow r^{-1} (a_{2i} - a_i) \pmod{p}$
 - return x
- If $x_i \neq x_{2i}$ then $i \leftarrow i+1$, and go to step 2.

Example [\[edit\]](#)

Consider, for example, the group generated by 2 modulo $N = 1019$ (the order of the group is $n = 1018$. 2 generates the group of units modulo 1019). The algorithm is implemented by the following C++ program:

```
#include <stdio.h>

const int n = 1018, N = n + 1; /* N = 1019 -- prime */
const int alpha = 2;          /* generator */
const int beta = 5;           /* 2^{10} = 1024 = 5 (N) */

void new_xab( int& x, int& a, int& b ) {
    switch( x%3 ) {
        case 0: x = x*x % N; a = a*2 % n; b = b*2 % n; break;
        case 1: x = x*alpha % N; a = (a+1) % n; break;
        case 2: x = x*beta % N; b = (b+1) % n; break;
    }
}

int main(void) {
    int x=1, a=0, b=0;
    int X=x, A=a, B=b;
    for(int i = 1; i < n; ++i ) {
        new_xab( x, a, b );
        new_xab( X, A, B ); new_xab( X, A, B );
        printf( "%3d %4d %3d %3d %4d %3d %3d\n", i, x, a, b, X, A, B );
        if( x == X ) break;
    }
    return 0;
}
```

The results are as follows (edited):

i	x	a	b	X	A	B
1	2	1	0	10	1	1
2	10	1	1	100	2	2
3	20	2	1	1000	3	3
4	100	2	2	425	8	6
5	200	3	2	436	16	14
6	1000	3	3	284	17	15
7	981	4	3	986	17	17
8	425	8	6	194	17	19
.....						
48	224	680	376	86	299	412
49	101	680	377	860	300	413
50	505	680	378	101	300	415
51	1010	681	378	1010	301	416

That is $2^{681}5^{378} = 1010 = 2^{301}5^{416} \pmod{1019}$ and so $(416 - 378)\gamma = 681 - 301 \pmod{1018}$, for which $\gamma_1 = 10$ is a solution as expected. As $n = 1018$ is not prime, there is another solution $\gamma_2 = 519$, for which $2^{519} = 1014 = -5 \pmod{1019}$ holds.

Complexity [\[edit\]](#)

The running time is approximately $\mathcal{O}(\sqrt{n})$. If used together with the [Pohlig-Hellman algorithm](#), the running time of the combined algorithm is $\mathcal{O}(\sqrt{p})$, where p is the largest prime factor of n .

References [\[edit\]](#)

- Pollard, J. M. (1978). "Monte Carlo methods for index computation (mod p)". *Mathematics of Computation* **32** (143): 918–924. doi:10.2307/2006496 [↗](#).
- Menezes, Alfred J.; van Oorschot, Paul C.; Vanstone, Scott A. (2001). "Chapter 3" [↗](#) (PDF). *Handbook of Applied Cryptography*.

v · t · e	Number-theoretic algorithms [hide]
Primality tests	<i>AKS test</i> · <i>APR test</i> · <i>Baillie–PSW</i> · <i>ECPP test</i> · <i>Elliptic curve</i> · <i>Pocklington</i> · <i>Fermat</i> · <i>Lucas</i> · <i>LUCAS–LEHMER</i> · <i>LUCAS–LEHMER–RIESEL</i> · <i>PROTH'S THEOREM</i> · <i>PÉPIN'S</i> · <i>Quadratic Frobenius test</i> · <i>Solovay–Strassen</i> · <i>Miller–Rabin</i>
Prime-generating	<i>Sieve of Atkin</i> · <i>Sieve of Eratosthenes</i> · <i>Sieve of Sundaram</i> · <i>Wheel factorization</i>
Integer factorization	<i>Continued fraction (CFRAC)</i> · <i>Dixon's</i> · <i>Lenstra elliptic curve (ECM)</i> · <i>Euler's</i> · <i>Pollard's rho</i> · <i>$p - 1$</i> · <i>$p + 1$</i> · <i>Quadratic sieve (QS)</i> · <i>General number field sieve (GNFS)</i> · <i>Special number field sieve (SNFS)</i> · <i>Rational sieve</i> · <i>Fermat's</i> · <i>Shanks' square forms</i> · <i>Trial division</i> · <i>Shor's</i>
Multiplication	<i>Ancient Egyptian</i> · <i>Long</i> · <i>Karatsuba</i> · <i>Toom–Cook</i> · <i>Schönhage–Strassen</i> · <i>Fürer's</i>
Discrete logarithm	<i>Baby-step giant-step</i> · Pollard rho · <i>Pollard kangaroo</i> · <i>Pohlig–Hellman</i> · <i>Index calculus</i> · <i>Function field sieve</i>
Greatest common divisor	<i>Binary</i> · <i>Euclidean</i> · <i>Extended Euclidean</i> · <i>Lehmer's</i>
Modular square root	<i>Cipolla</i> · <i>Pocklington's</i> · <i>Tonelli–Shanks</i>
Other algorithms	<i>Chakravala</i> · <i>Cornacchia</i> · <i>Integer relation</i> · <i>Integer square root</i> · <i>Modular exponentiation</i> · <i>Schoof's</i>
<i>Italics indicate that algorithm is for numbers of special forms</i> · Smallcaps indicate a deterministic algorithm	

Categories: Logarithms | Number theoretic algorithms

This page was last modified on 15 June 2015, at 08:52.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

