



WIKIPEDIA
The Free Encyclopedia

Main page
Contents
Featured content
Current events
Random article
Donate to Wikipedia
Wikipedia store

Interaction

Help
About Wikipedia
Community portal
Recent changes
Contact page

Tools

What links here
Related changes
Upload file
Special pages
Permanent link
Page information
Wikidata item
Cite this page

Print/export

Create a book
Download as PDF
Printable version

Languages

العربية
Čeština
Deutsch
Eesti
Ελληνικά
Español
فارسی
Français
한국어
Italiano
Қазақша
Polski
Português
Русский
Slovenščina
Svenska
ไทย
Українська

Edit links

Create account Log in

Article **Talk**

Read **Edit** More ▾

Search

Directed graph


From Wikipedia, the free encyclopedia

In **mathematics**, and more specifically in **graph theory**, a **directed graph** (or **digraph**) is a **graph**, or set of nodes connected by edges, where the edges have a direction associated with them. In formal terms, a digraph is a pair $G = (V, A)$ (sometimes $G = (V, E)$) of:^[1]


- a set V , whose **elements** are called *vertices* or *nodes*,
- a set A of **ordered pairs** of vertices, called *arcs*, *directed edges*, or *arrows* (and sometimes simply *edges* with the corresponding set named E instead of A).

It differs from an ordinary or **undirected graph**, in that the latter is defined in terms of **unordered pairs** of vertices, which are usually called edges.

A digraph is called "simple" if it has no loops, and no multiple arcs (arcs with same starting and ending nodes). A **directed multigraph**, in which the arcs constitute a **multiset**, rather than a set, of ordered pairs of vertices may have loops (that is, "self-loops" with same starting and ending node) and multiple arcs. Some, but not all, texts allow a digraph, without the qualification simple, to have self loops, multiple arcs, or both.



A directed graph.



Directed graph with corresponding incidence matrix.

Contents [hide]

- Basic terminology
- Indegree and outdegree
- Degree sequence
- Digraph connectivity
- Classes of digraphs
- See also
- Notes
- References

Basic terminology ^[edit]

An arc $e = (x, y)$ is considered to be directed *from* x *to* y ; y is called the *head* and x is called the *tail* of the arc; y is said to be a *direct successor* of x , and x is said to be a *direct predecessor* of y . If a **path** made up of one or more successive arcs leads from x to y , then y is said to be a *successor* of x , and x is said to be a *predecessor* of y . The arc (y, x) is called the arc (x, y) *inverted*.

An **orientation** of a **simple undirected graph** is obtained by assigning a direction to each edge. Any directed graph constructed this way is called an "oriented graph". A directed graph is an oriented simple graph if and only if it has neither self-loops nor 2-cycles.^[2]

A **weighted digraph** is a digraph with weights assigned to its arcs, similar to a **weighted graph**. In the context of graph theory a digraph with weighted edges is called a *network*.

The **adjacency matrix** of a digraph (with loops and multiple arcs) is the integer-valued **matrix** with rows and columns corresponding to the nodes, where a nondiagonal entry a_{ij} is the number of arcs from node i to node j , and the diagonal entry a_{ii} is the number of loops at node i . The adjacency matrix of a digraph is unique up to identical permutation of rows and columns.

Another matrix representation for a digraph is its **incidence matrix**.

See **direction** for more definitions.

Indegree and outdegree ^[edit]


For a node, the number of head endpoints adjacent to a node is called the *indegree* of the node and the number of tail endpoints adjacent to a node is its *outdegree* (called "**branching factor**" in trees).

Let $G = (V, E)$ and $v \in V$, then the indegree is denoted $\deg^-(v)$ and the outdegree as $\deg^+(v)$. A vertex with $\deg^-(v) = 0$ is called a *source*, as it is the origin of each of its incident edges. Similarly, a vertex with $\deg^+(v) = 0$ is called a *sink*.

The *degree sum formula* states that, for a directed graph,

$$\sum_{v \in V} \deg^+(v) = \sum_{v \in V} \deg^-(v) = |E|.$$

If, for every node $v \in V$, we have $\deg^+(v) = \deg^-(v)$, the graph is called a *balanced digraph*.^[3]



Degree sequence ^[edit]

The degree sequence of a directed graph is the list of its indegree and outdegree pairs; for the above example we have degree sequence $((2,0),(2,2),(0,2),(1,1))$. The degree sequence is a directed graph invariant so isomorphic directed graphs have the same degree sequence. However, the degree sequence does not, in general, uniquely identify a graph; in some cases, non-isomorphic graphs have the same degree sequence.

The **digraph realization problem** is the problem of finding a digraph with the degree sequence being a given sequence of positive integer pairs. (Trailing pairs of zeros may be ignored since they are trivially realized by adding an appropriate number of isolated vertices to the digraph.) A sequence which is the degree sequence of some digraph, i.e. for which the digraph realization problem has a solution, is called a *digraphic* or *digraphical* sequence. This problem can either be solved by the **Kleitman–Wang algorithm** or by the **Fulkerson–Chen–Anstee theorem**.

Digraph connectivity ^[edit]


Main article: [Connectivity \(graph theory\)](#)

A digraph G is called *weakly connected* (or just *connected*^[4]) if the undirected *underlying graph* obtained by replacing all directed edges of G with undirected edges is a **connected graph**. A digraph is *strongly connected* or *strong* if it contains a directed path from u to v and a directed path from v to u for every pair of vertices u, v . The *strong components* are the maximal strongly connected subgraphs.

Classes of digraphs ^[edit]


A directed graph G is called **symmetric** if, for every arc that belongs to G , the corresponding reversed arc also belongs to G . A symmetric, loopless directed graph is equivalent to an undirected graph with the edges replaced by pairs of inverse arcs; thus the number of edges is equal to the number of arcs halved.

An **acyclic** directed graph, *acyclic digraph*, or **directed acyclic graph** is a directed graph with no **directed cycles**. Special cases of acyclic directed graphs include **multitrees** (graphs in which no two directed paths from a single starting node meet back at the same ending node), **oriented trees** or *polytrees* (digraphs formed by orienting the edges of undirected acyclic graphs), and **rooted trees** (oriented trees in which all edges of the underlying undirected tree are directed away from the roots).




A **tournament** is an oriented graph obtained by choosing a direction for each edge in an undirected **complete graph**.

In the theory of **Lie groups**, a **quiver** Q is a directed graph serving as the domain of, and thus characterizing the shape of, a *representation* V defined as a **functor**, specifically an object of the **functor category** $\mathbf{FinVct}_K^{F(Q)}$ where $F(Q)$ is the **free category** on Q consisting of paths in Q and \mathbf{FinVct}_K is the category of finite-dimensional **vector spaces** over a **field** K . Representations of a quiver label its vertices with vector spaces and its edges (and hence paths) compatibly with **linear transformations** between them, and transform via **natural transformations**.



See also ^[edit]

- Coates graph
- Flow chart
- Rooted graph
- Flow graph (mathematics)



- [Mason graph](#)
- [Oriented graph](#)
- [Preorder](#)
- [Quiver](#)
- [Signal-flow graph](#)
- [Transpose graph](#)
- [Vertical constraint graph](#)

Notes [\[edit\]](#)

- [^] [Bang-Jensen & Gutin \(2000\)](#). [Diestel \(2005\)](#), Section 1.10. [Bondy & Murty \(1976\)](#), Section 10.
- [^] [Diestel \(2005\)](#), Section 1.10.
- [^] [Satyanarayana, Bhavanari; Prasad, Kuncham Syam](#), *Discrete Mathematics and Graph Theory*, PHI Learning Pvt. Ltd., p. 460, [ISBN 978-81-203-3842-5](#); [Brualdi, Richard A. \(2006\)](#), *Combinatorial matrix classes*, Encyclopedia of mathematics and its applications **108**, Cambridge University Press, p. 51, [ISBN 978-0-521-86565-4](#).
- [^] [Bang-Jensen & Gutin \(2000\)](#) p. 19 in the 2007 edition; p. 20 in the 2nd edition (2009).

References [\[edit\]](#)

- [Bang-Jensen, Jørgen; Gutin, Gregory \(2000\)](#), *[Digraphs: Theory, Algorithms and Applications](#)*^{[↗](#)}, [Springer](#), [ISBN 1-85233-268-9](#)
(the corrected 1st edition of 2007 is now freely available on the authors' site; the 2nd edition appeared in 2009 [ISBN 1-84800-997-6](#)).
- [Bondy, John Adrian; Murty, U. S. R. \(1976\)](#), *[Graph Theory with Applications](#)*^{[↗](#)}, North-Holland, [ISBN 0-444-19451-7](#).
- [Diestel, Reinhard \(2005\)](#), *[Graph Theory](#)*^{[↗](#)} (3rd ed.), [Springer](#), [ISBN 3-540-26182-6](#) (the electronic 3rd edition is freely available on author's site).
- [Harary, Frank; Norman, Robert Z.; Cartwright, Dorwin \(1965\)](#), *Structural Models: An Introduction to the Theory of Directed Graphs*, New York: Wiley.
- [Number of directed graphs \(or digraphs\) with n nodes.](#)*^{[↗](#)}

Categories: [Directed graphs](#)

This page was last modified on 18 July 2015, at 22:55.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

