

Main page
Contents
Featured content
Current events
Random article
Donate to Wkipedia
Wkipedia store

Interaction

Help About Wikipedia Community portal Recent changes Contact page

Tools

What links here Related changes Upload file Special pages Permanent link Page information Wkidata item Cite this page

Print/export

Create a book Download as PDF Printable version

 Article Talk Read Edit View history Search Q

Chaitin's algorithm

From Wikipedia, the free encyclopedia

Chaitin's algorithm is a bottom-up, graph coloring register allocation algorithm that uses cost/degree as its spill metric. It is named after its designer, Gregory Chaitin. Chaitin's algorithm was the first register allocation algorithm that made use of coloring of the interference graph for both register allocations and spilling.

Chaitin's algorithm was presented on the 1982 SIGPLAN Symposium on Compiler Construction, and published in the symposium proceedings. It was extension of an earlier 1981 paper on the use of graph coloring for register allocation. Chaitin's algorithm formed the basis of a large section of research into register allocators.

References [edit]

- Gregory Chaitin Register allocation and spilling via graph coloring

Categories: Graph algorithms

This page was last modified on 14 October 2011, at 05:55.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

Privacy policy About Wikipedia Disclaimers Contact Wikipedia Developers Mobile view

