

[questions](#)[tags](#)[users](#)[badges](#)[unanswered](#)[ask a question](#)[about](#) [f](#)

CodeChef Discussion

Search Here...

☒ questions
 ☐ tags
 ☐ use

MDIST - Editorial

PROBLEM LINK:

[Practice](#) [Contest](#)

DIFFICULTY:

EASY

PREREQUISITES:

[Segment Tree](#)

PROBLEM:

Given a set of n points, we have to process the following two queries

- Update i , x , y : Update the i th point to (x,y)
- Query l , r : Print the maximum Manhattan distance between two points which lie between l to r .

EXPLANATION:

Lets consider a different problem in which we have only one query and no updates. In this problem we have to find two points $P1(x1, y1)$ and $P2(x2, y2)$ such that their Manhattan distance is maximized. Note that the Manhattan distance between any two points can be written as follows

$$\begin{aligned}
 \text{dist}(P1, P2) &= |x1 - x2| + |y1 - y2| \\
 &= \max(\begin{aligned} &x1 - x2 + y1 - y2, \\ &-x1 + x2 + y1 - y2, \\ &x1 - x2 + -y1 + y2, \\ &-x1 + x2 + -y1 + y2 \end{aligned}) \\
 &= \max(\begin{aligned} &(x1 + y1) - (x2 + y2), \\ &(-x1 + y1) - (-x2 + y2), \\ &(x1 - y1) - (x2 - y2), \\ &(-x1 - y1) - (-x2 - y2) \end{aligned}) \\
 &= \max(\begin{aligned} &f1(P1) - f1(P2), \\ &f2(P1) - f2(P2), \\ &f3(P1) - f3(P2), \\ &f4(P1) - f4(P2) \end{aligned})
 \end{aligned}$$

where $f1(P) = x+y$, $f2(P) = -x+y$, $f3(P) = x-y$, $f4(P) = -x-y$

Note the last expression, not only it is free from any absolute signs but also it follows a pattern which is key to solving this problem. Formally we have to find

$$\begin{aligned}
 \max_{(P1,P2)} \{ \text{dist}(P1, P2) \} &= \max_{(P1,P2)} \{ \max(f1(P1) - f1(P2), f2(P1) - f2(P2), f3(P1) - f3(P2), f4(P1) - f4(P2)) \} \\
 &= \max_P \{ f1(P) \} - \min_P \{ f1(P) \}, \max_P \{ f2(P) \} - \min_P \{ f2(P) \}, \\
 &\quad \max_P \{ f3(P) \} - \min_P \{ f3(P) \}, \max_P \{ f4(P) \} - \min_P \{ f4(P) \}
 \end{aligned}$$

That is we have to find the point with maximum and minimum $f1$ value, subtract second from first and do this for $f2$, $f3$ and $f4$ as well and take the maximum among the four.

Now coming back to our original problem, here we have range query and point update, for this we will maintain 4 segment trees each corresponding to $f1, f2, f3$ and $f4$ containing the minimum and maximum values of $f1, f2, f3$ and $f4$. By this method querying and updating can be done in $\mathcal{O}(\log(n))$ time.

RELATED PROBLEM:

[MOSTDIST](#)
[DISTANCE](#)

AUTHOR'S AND TESTER'S SOLUTIONS:

Author's solution can be found [here](#)

Tester's solution will be updated soon

Editorialist's solution will be updated soon

Follow this question

By Email:

Once you sign in you will be able to subscribe for any updates here

By RSS:

[Answers](#)
[Answers and Comments](#)

Tags:

[editorial](#) **×2,795**
[easy](#) **×1,099**
[segment-tree](#) **×343**
[ltime24](#) **×104**

Asked: 27 May, 15:56

Seen: 305 times

Last updated: 4 hours ago

Related questions

[NWAYS - Editorial](#)
[SUBARR - Editorial](#)
[IIT14 - Editorial](#)
[KGP13F - Editorial](#)
[MOVES - Editorial](#)
[LOWSUM - Editorial](#)
[CLEANUP - Editorial](#)
[CHXORR - Editorial](#)
[GAMEAM - Editorial](#)
[SPREAD - Editorial](#)
[segment-tree](#) [ltime24](#) [easy](#) [editorial](#)

edited 4 hours ago



admin

10.8k • 346 • 472 • 486

asked 27 May, 15:56



saurabh060792

175 • 1 • 3 • 8

accept rate: 0%