

Main page
Contents
Featured content
Current events
Random article
Donate to Wkipedia
Wkipedia store

Interaction

Help About Wikipedia Community portal Recent changes Contact page

Tools

What links here Related changes Upload file Special pages Permanent link Page information Wkidata item Cite this page

Print/export

Create a book Download as PDF Printable version

Languages Deutsch

> Español فارسی Français

Русский Српски / srpski Türkçe

Article Talk Read Edit View history Search Q

Tree sort

From Wikipedia, the free encyclopedia



This article **does not cite any references or sources**. Please help improve this article by adding citations to reliable sources. Unsourced material may be challenged and removed. (*September 2014*)

A **tree sort** is a sort algorithm that builds a binary search tree from the keys to be sorted, and then traverses the tree (in-order) so that the keys come out in sorted order. Its typical use is sorting elements adaptively: after each insertion, the set of elements seen so far is available in sorted order.

Contents [hide]


- 1 Efficiency
- 2 Example
- 3 See also
- 4 External links

Efficiency [edit]

Adding one item to a binary search tree is on average an $O(\log n)$ process (in big O notation), so adding n items is an $O(n\log n)$ process, making tree sort a 'fast sort'. But adding an item to an unbalanced binary tree needs O(n) time in the worst-case, when the tree resembles a linked list (degenerate tree), causing a worst case of $O(n^2)$ for this sorting algorithm. This worst case occurs when the algorithm operates on an already sorted set, or one that is nearly sorted. Expected $O(\log n)$ time can however be achieved in this case by shuffling the array.

The worst-case behaviour can be improved upon by using a self-balancing binary search tree. Using such a tree, the algorithm has an $O(n \log n)$ worst-case performance, thus being degree-optimal for a comparison sort. When using a splay tree as the binary search tree, the resulting algorithm (called splaysort) has the additional property that it is an adaptive sort, meaning that its running time is faster than $O(n \log n)$ for inputs that are nearly sorted.

Tree sort



Class Sorting algorithm Data structure Array Worst case $O(n^2)$ (unbalanced) performance $O(n \log n)$ (balanced) $O(n \log n)^{[citation \, needed]}$ **Best case** performance Average case $O(n \log n)$ performance Worst case space $\Theta(n)$ complexity

Example [edit]

The following tree sort algorithm in pseudocode accepts an array of comparable items and outputs the items in ascending order:

```
STRUCTURE BinaryTree

BinaryTree:LeftSubTree

Object:Node

BinaryTree:RightSubTree

PROCEDURE Insert(BinaryTree:searchTree, Object:item)

If searchTree.Node IS NULL THEN

SET searchTree.Node TO item

ELSE

IF item IS LESS THAN searchTree.Node THEN

Insert(searchTree.LeftSubTree, item)

ELSE

Insert(searchTree.RightSubTree, item)
```

```
PROCEDURE InOrder(BinaryTree:searchTree)

IF searchTree.Node IS NULL THEN

EXIT PROCEDURE

ELSE

InOrder(searchTree.LeftSubTree)

EMIT searchTree.Node

InOrder(searchTree.RightSubTree)

PROCEDURE TreeSort(Array:items)

BinaryTree:searchTree

FOR EACH individualItem IN items

Insert(searchTree, individualItem)

InOrder(searchTree)
```

In a simple functional programming form, the algorithm (in Haskell) would look something like this:

In the above implementation, both the insertion algorithm and the retrieval algorithm have $O(n^2)$ worst-case scenarios.

See also [edit]

• Heapsort: builds a binary heap out of its input instead of a binary search tree, and can be used to sort inplace (but not adaptively).

External links [edit]

- Tree Sort of a Linked List ☑
- Tree Sort in C++ ☑



v· t· e	Sorting algorithms	[hide]
Theory	Computational complexity theory · Big O notation · Total order · Lists · Inplacement · Stability · Comparison sort · Adaptive sort · Sorting network · Integer sorting	
Exchange sorts	Bubble sort \cdot Cocktail sort \cdot Odd–even sort \cdot Comb sort \cdot Gnome sort \cdot Quicksort \cdot Stooge sort Bogosort	
Selection sorts	Selection sort · Heapsort · Smoothsort · Cartesian tree sort · Tournament sort · Cycle sort	
Insertion sorts	Insertion sort · Shellsort · Splaysort · Tree sort · Library sort · Patience sorting	
Merge sorts	Merge sort · Cascade merge sort · Oscillating merge sort · Polyphase merge sort · Strand sort	
Distribution sorts	American flag sort · Bead sort · Bucket sort · Burstsort · Counting sort · Pigeonhole sort · Proxm Radix sort · Flashsort	ap sort ·
Concurrent sorts	Bitonic sorter · Batcher odd-even mergesort · Pairwise sorting network	
Hybrid sorts	Block sort · Timsort · Introsort · Spreadsort · JSort	
Other	Topological sorting · Pancake sorting · Spaghetti sort	

Categories: Sorting algorithms

This page was last modified on 15 April 2015, at 18:30.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

Privacy policy About Wikipedia Disclaimers Contact Wikipedia Developers Mobile view



