



WIKIPEDIA
The Free Encyclopedia

Main page

Contents

Featured content

Current events

Random article

Donate to Wikipedia

Wikipedia store

Interaction

Help

About Wikipedia

Community portal

Recent changes

Contact page

Tools

What links here

Related changes

Upload file

Special pages

Permanent link

Page information

Wikidata item

Cite this page

Print/export

Create a book

Download as PDF

Printable version

Languages

Deutsch

Français

Edit links

Article **Talk**

Read

Edit

View history

Search



Ricart–Agrawala algorithm

From Wikipedia, the free encyclopedia

(Redirected from [Ricart-Agrawala Algorithm](#))



This article **does not cite any references or sources**. Please help [improve this article](#) by [adding citations to reliable sources](#). Unsourced material may be challenged and [removed](#). *(December 2009)*

The **Ricart-Agrawala Algorithm** is an algorithm for [mutual exclusion](#) on a [distributed system](#). This algorithm is an extension and optimization of [Lamport's Distributed Mutual Exclusion Algorithm](#), by removing the need for *release* messages. It was developed by [Glenn Ricart](#) and [Ashok Agrawala](#).

Contents [hide]

1 Algorithm

1.1 Terminology

1.2 Algorithm

1.3 Performance

1.4 Common Optimizations

1.5 Problems

2 See also

3 References

Algorithm [edit]

Terminology [edit]

- A *site* is any computing device which is running the Ricart-Agrawala Algorithm
- The *requesting site* is the site which is requesting entry into the critical section.
- The *receiving site* is every other site which is receiving the request from the requesting site.

Algorithm [edit]

Requesting Site

- Sends a message to all sites. This message includes the site's name, and the current timestamp of the system according to its [logical clock](#) (*which is assumed to be synchronized with the other sites*)

Receiving Site

- Upon reception of a request message, immediately send a timestamped *reply* message if and only if:
 - the receiving process is not currently interested in the critical section OR
 - the receiving process has a lower priority (*usually this means having a later timestamp*)
- Otherwise, the receiving process will defer the reply message. This means that a reply will be sent only after the receiving process has finished using the critical section itself.

Critical Section:

- Requesting site enters its critical section only after receiving all reply messages.
- Upon exiting the critical section, the site sends all deferred reply messages.

Performance [edit]

- Number of network messages; $2 \cdot (N - 1)$
- Synchronization Delays: One message propagation delay

Common Optimizations [edit]

Once site P_i has received a *reply* message from site P_j , site P_i may enter the critical section multiple times without receiving permission from P_j on subsequent attempts up to the moment when P_i has sent a *reply* message to P_j . This is called Roucairol-Carvalho optimization or Roucairol-Carvalho algorithm.

Problems [\[edit\]](#)

One of the problems in this algorithm is failure of a node. In such a situation a process may starve forever. This problem can be solved by detecting failure of nodes after some timeout.

See also [\[edit\]](#)

- [Lamport's Bakery Algorithm](#)
- [Lamport's Distributed Mutual Exclusion Algorithm](#)
- [Maekawa's Algorithm](#)
- [Suzuki-Kasami algorithm](#)
- [Raymond's Algorithm](#)
- [Naimi-Trehel's Algorithm](#)

References [\[edit\]](#)

- Maekawa, M.,Oldehoeft, A.,Oldehoeft, R.(1987). Operating Systems: Advanced Concept.Benjamin/Cummings Publishing Company, Inc.

Categories: [Distributed algorithms](#)

This page was last modified on 24 February 2015, at 07:28.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

