



WIKIPEDIA
The Free Encyclopedia

[Main page](#)

[Contents](#)

[Featured content](#)

[Current events](#)

[Random article](#)

[Donate to Wikipedia](#)

[Wikipedia store](#)

Interaction

[Help](#)

[About Wikipedia](#)

[Community portal](#)

[Recent changes](#)

[Contact page](#)

Tools

[What links here](#)

[Related changes](#)

[Upload file](#)

[Special pages](#)

[Permanent link](#)

[Page information](#)

[Wikidata item](#)

[Cite this page](#)

Print/export

[Create a book](#)

[Download as PDF](#)

[Printable version](#)

Languages

[فارسی](#)

[Edit links](#)

[Create account](#) [Log in](#)

Article

[Talk](#)

[Read](#)

[Edit](#)

[View history](#)

Buzen's algorithm

From Wikipedia, the free encyclopedia

In [queueing theory](#), a discipline within the mathematical [theory of probability](#), **Buzen's algorithm** (or **convolution algorithm**) is an algorithm for calculating the [normalization constant](#) $G(N)$ in the [Gordon–Newell theorem](#). This method was first proposed by [Jeffrey P. Buzen](#) in 1973.^[1] Computing $G(N)$ is required to compute the stationary [probability distribution](#) of a closed queueing network.^[2]

Performing a naïve computation of the normalising constant requires enumeration of all states. For a system with N jobs and M states there are $\binom{N+M-1}{M-1}$ states. Buzen's algorithm "computes $G(1)$, $G(2)$, ..., $G(N)$ using a total of NM multiplications and NM additions." This is a significant improvement and allows for computations to be performed with much larger networks.^[1]

Contents [hide]

[1 Problem setup](#)

[2 Algorithm description](#)

[3 Marginal distributions, expected number of customers](#)

[4 Implementation](#)

[5 References](#)

Problem setup [\[edit\]](#)

Consider a closed queueing network with M service facilities and N circulating customers. Write $n_i(t)$ for the number of customers present at the i th facility at time t , such that $\sum_{i=1}^M n_i = N$. We assume that the service time for a customer at the i th facility is given by an [exponentially distributed](#) random variable with parameter μ_i and that after completing service at the i th facility a customer will proceed to the j th facility with probability p_{ij} .^[2]

It follows from the [Gordon–Newell theorem](#) that the equilibrium distribution of this model is

$$\mathbb{P}(n_1, n_2, \dots, n_M) = \frac{1}{G(N)} \prod_{i=1}^M (X_i)^{n_i}$$

where the X_i are found by solving

$$\mu_j X_j = \sum_{i=1}^M \mu_i X_i p_{ij} \quad \text{for } j = 1, \dots, M.$$

and $G(N)$ is a normalizing constant chosen that the above probabilities sum to 1.^[1]

Buzen's algorithm is an efficient method to compute $G(N)$.^[1]

Algorithm description [\[edit\]](#)

Write $g(N, M)$ for the normalising constant of a closed queueing network with N circulating customers and M service stations. The algorithm starts by noting solving the above relations for the X_i and then setting starting conditions^[1]

$$\begin{aligned} g(0, m) &= 1 \text{ for } m = 1, 2, \dots, M \\ g(n, 1) &= (X_1)^n \text{ for } n = 0, 1, \dots, N. \end{aligned}$$

The recurrence relation^[1]

$$g(n, m) = g(n, m-1) + X_m g(n-1, m).$$

is used to compute a grid of values. The sought for value $G(N) = g(N, M)$.^[1]

Marginal distributions, expected number of customers [\[edit\]](#)

The coefficients $g(n, m)$, computed using Buzen's algorithm, can also be used to compute [marginal distributions](#) and [expected](#) number of customers at each node.

$$\mathbb{P}(n_i = k) = \frac{X_i^k}{G(N)}[G(N - k) - X_i G(N - k - 1)] \quad \text{for } k = 0, 1, \dots, N - 1,$$
$$\mathbb{P}(n_i = N) = \frac{X_i^N}{G(N)}[G(0)].$$

the expected number of customers at facility *i* by

$$\mathbb{E}(n_i) = \sum_{k=1}^N X_i^k \frac{G(N - k)}{G(N)}.$$

Implementation [\[edit\]](#)

It will be assumed that the *X_m* have been computed by solving the relevant equations and are available as an input to our routine. Although *g* is in principle a two dimensional matrix, it can be computed in a column by column fashion starting from the leftmost column. The routine uses a single column vector *C* to represent the current column of *g*.



```
C[0] := 1
for n := 1 step 1 until N do
    C[n] := 0;

for m := 1 step 1 until M do
    for n := 1 step 1 until N do
        C[n] := C[n] + X[m]*C[n-1];
```



At completion, *C* contains the desired values *G*(0), *G*(1) to *G*(*N*). ^[1]


References [\[edit\]](#)

1.


^{[a](#) [b](#) [c](#) [d](#) [e](#) [f](#) [g](#) [h](#)} Buzen, J. P. (1973). "Computational algorithms for closed queueing networks with exponential servers"  (PDF). *Communications of the ACM* **16** (9): 527. doi:10.1145/362342.362345 .

2.


^{[a](#) [b](#)} Gordon, W. J.; Newell, G. F. (1967). "Closed Queueing Systems with Exponential Servers". *Operations Research* **15** (2): 254. doi:10.1287/opre.15.2.254 . JSTOR 168557 .



Jain: The Convolution Algorithm (class handout)



Menasce: Convolution Approach to Queueing Algorithms (presentation)

v · t · e	Queueing theory	[hide]
Single queueing nodes	D/M/1 queue · MD/1 queue · MD/c queue · MM/1 queue (Burke's theorem) · MM/c queue · MM/∞ queue · M/G/1 queue (Pollaczek–Khinchine formula · Matrix analytic method) · M/G/k queue · G/M/1 queue · G/G/1 queue (Kingman's formula · Lindley equation) · Fork–join queue · Bulk queue	
Arrival processes	Poisson process · Markovian arrival process · Rational arrival process	
Queueing networks	Jackson network (Traffic equations) · Gordon–Newell theorem (Mean value analysis · Buzen's algorithm) · Kelly network · G-network · BCMP network	
Service policies	FIFO · LIFO · Processor sharing · Shortest job first · Shortest remaining time	
Key concepts	Continuous-time Markov chain · Kendall's notation · Little's law · Product-form solution (Balance equation · Quasireversibility · Flow-equivalent server method) · Arrival theorem · Decomposition method · Beneš method	
Limit theorems	Fluid limit · Mean field theory · Heavy traffic approximation (Reflected Brownian motion)	
Extensions	Fluid queue · Layered queueing network · Polling system · Adversarial queueing network · Loss network · Retrial queue	
Information systems	Data buffer · Erlang (unit) · Erlang distribution · Flow control (data) · Message queue · Network congestion · Network scheduler · Pipeline (software) · Quality of service · Scheduling (computing) · Teletraffic engineering	
 Category		

Categories: [Stochastic processes](#) | [Queueing theory](#) | [Statistical algorithms](#)

