



WIKIPEDIA
The Free Encyclopedia

[Main page](#)
[Contents](#)
[Featured content](#)
[Current events](#)
[Random article](#)
[Donate to Wikipedia](#)
[Wikipedia store](#)

Interaction
[Help](#)
[About Wikipedia](#)
[Community portal](#)
[Recent changes](#)
[Contact page](#)

Tools
[What links here](#)
[Related changes](#)
[Upload file](#)
[Special pages](#)
[Permanent link](#)
[Page information](#)
[Wikidata item](#)
[Cite this page](#)

Print/export
[Create a book](#)
[Download as PDF](#)
[Printable version](#)

Languages
[Deutsch](#)
[한국어](#)
[Српски / srpski](#)
[Edit links](#)

[Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)

R+ tree

From Wikipedia, the free encyclopedia

An **R+ tree** is a method for looking up data using a location, often (x, y) [coordinates](#), and often for locations on the [surface of the earth](#). Searching on one number is a solved problem; searching on two or more, and asking for locations that are nearby in both x and y directions, requires craftier algorithms.

Fundamentally, an R+ tree is a [tree data structure](#), a variant of the [R tree](#), used for [indexing spatial information](#).

Contents [hide]

- [1 Difference between R+ trees and R trees](#)
- [2 Advantages](#)
- [3 Disadvantages](#)
- [4 Notes](#)
- [5 References](#)

Difference between R+ trees and R trees [\[edit\]](#)

R+ trees are a compromise between [R-trees](#) and [kd-trees](#): they avoid overlapping of internal nodes by inserting an object into multiple leaves if necessary. **Coverage** is the entire area to cover all related rectangles.

Overlap is the entire area which is contained in two or more nodes.^[1] Minimal coverage reduces the amount of "dead space" (empty area) which is covered by the nodes of the R-tree. Minimal overlap reduces the set of search paths to the leaves (even more critical for the access time than minimal coverage). Efficient search requires minimal coverage and overlap.

R+ trees differ from R trees in that:

- Nodes are not guaranteed to be at least half filled
- The entries of any internal node do not overlap
- An object ID may be stored in more than one leaf node

Advantages [\[edit\]](#)

- Because nodes are not overlapped with each other, point query performance benefits since all spatial regions are covered by at most one node.
- A single path is followed and fewer nodes are visited than with the R-tree

Disadvantages [\[edit\]](#)

- Since rectangles are duplicated, an R+ tree can be larger than an R tree built on same data set.
- Construction and maintenance of R+ trees is more complex than the construction and maintenance of R trees and other variants of the R tree.

Notes [\[edit\]](#)

- [↑] Härder, Rahm, Theo, Erhard (2007). *Datenbanksysteme*. (2., überarb. Aufl. ed.). Berlin [etc.]: Gardners Books. pp. 285, 286. ISBN 3-540-42133-5.

References [\[edit\]](#)

- T. Sellis, N. Roussopoulos, and C. Faloutsos. [The R+-Tree: A dynamic index for multi-dimensional objects](#) . In VLDB, 1987.

 v · t · e	Tree data structures	[show]
 v · t · e	Data structures	[show]



This *algorithms* or *data structures*-related article is a *stub*. You can help Wikipedia by [expanding it](#).

[Categories: R-tree](#) | [Database index techniques](#) | [Algorithms and data structures stubs](#)
| [Computer science stubs](#)

This page was last modified on 22 July 2013, at 07:26.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

