



WIKIPEDIA
The Free Encyclopedia

[Main page](#)
[Contents](#)
[Featured content](#)
[Current events](#)
[Random article](#)
[Donate to Wikipedia](#)
[Wikipedia store](#)

Interaction

[Help](#)
[About Wikipedia](#)
[Community portal](#)
[Recent changes](#)
[Contact page](#)

Tools

[What links here](#)
[Related changes](#)
[Upload file](#)
[Special pages](#)
[Permanent link](#)
[Page information](#)
[Wikidata item](#)
[Cite this page](#)

Print/export

[Create a book](#)
[Download as PDF](#)
[Printable version](#)

Languages

[Deutsch](#)
[Español](#)
[Русский](#)

[Edit links](#)

[Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)

Cuthill–McKee algorithm

From Wikipedia, the free encyclopedia

In the [mathematical](#) subfield of [matrix theory](#), the **Cuthill–McKee algorithm** (**CM**), named for Elizabeth Cuthill and J. McKee ^[1] is an [algorithm](#) to permute a [sparse matrix](#) that has a [symmetric](#) sparsity pattern into a [band matrix](#) form with a small [bandwidth](#). The **reverse Cuthill–McKee algorithm** (**RCM**) due to Alan George is the same algorithm but with the resulting index numbers reversed. In practice this generally results in less [fill-in](#) than the CM ordering when Gaussian elimination is applied. ^[2]

The Cuthill McKee algorithm is a variant of the standard [breadth-first search](#) algorithm used in graph algorithms. It starts with a peripheral node and then generates [levels](#) R_i for $i = 1, 2, \dots$ until all nodes are exhausted. The set R_{i+1} is created from set R_i by listing all vertices adjacent to all nodes in R_i . These nodes are listed in increasing degree. This last detail is the only difference with the breadth-first search algorithm.

Algorithm ^[edit]

Given a symmetric $n \times n$ matrix we visualize the matrix as the [adjacency matrix](#) of a [graph](#). The Cuthill–McKee algorithm is then a relabeling of the [vertices](#) of the graph to reduce the bandwidth of the adjacency matrix.

The algorithm produces an ordered n -tuple R of vertices which is the new order of the vertices.

First we choose a [peripheral vertex](#) (the vertex with the lowest [degree](#)) x and set $R := (\{x\})$.

Then for $i = 1, 2, \dots$ we iterate the following steps while $|R| < n$

- Construct the adjacency set A_i of R_i (with R_i the i -th component of R) and exclude the vertices we already have in R

$$A_i := \text{Adj}(R_i) \setminus R$$

- Sort A_i with ascending vertex order ([vertex degree](#)).
- Append A_i to the Result set R .


In other words, number the vertices according to a particular [breadth-first traversal](#) where neighboring vertices are visited in order from lowest to highest vertex order.

See also ^[edit]


- [Graph bandwidth](#)
- [Sparse matrix](#)

References ^[edit]

- [↑] E. Cuthill and J. McKee. *Reducing the bandwidth of sparse symmetric matrices* [↗](#) In Proc. 24th Nat. Conf. [ACM](#), pages 157–172, 1969.
 - [↑] J. A. George and J. W-H. Liu, Computer Solution of Large Sparse Positive Definite Systems, Prentice-Hall, 1981
- [Cuthill–McKee documentation](#) [↗](#) for the [Boost C++ Libraries](#).
 - [A detailed description of the Cuthill–McKee algorithm](#) [↗](#).
 - [symrcm](#) [↗](#) MATLAB's implementation of RCM.



Cuthill-McKee ordering of a matrix



RCM ordering of the same matrix

Categories: [Matrix theory](#) | [Graph algorithms](#) | [Sparse matrices](#)

This page was last modified on 24 March 2015, at 16:30.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

