



WIKIPEDIA  
The Free Encyclopedia

[Main page](#)  
[Contents](#)  
[Featured content](#)  
[Current events](#)  
[Random article](#)  
[Donate to Wikipedia](#)  
[Wikipedia store](#)

[Interaction](#)  
[Help](#)  
[About Wikipedia](#)  
[Community portal](#)  
[Recent changes](#)  
[Contact page](#)

[Tools](#)  
[What links here](#)  
[Related changes](#)  
[Upload file](#)  
[Special pages](#)  
[Permanent link](#)  
[Page information](#)  
[Wikidata item](#)  
[Cite this page](#)

[Print/export](#)  
[Create a book](#)  
[Download as PDF](#)  
[Printable version](#)

[Languages](#)  
[Deutsch](#)  
[Français](#)  
[日本語](#)  
[Русский](#)  
[Edit links](#)

[Create account](#) [Log in](#)

[Article](#) [Talk](#)

[Read](#) [Edit](#) [View history](#)

# Interior point method

From Wikipedia, the free encyclopedia

**Interior point methods** (also referred to as **barrier methods**) are a certain class of [algorithms](#) that solves linear and nonlinear [convex optimization](#) problems.


[John von Neumann](#)<sup>[1]</sup> suggested an interior point method of linear programming which was neither a polynomial time method nor an efficient method in practice. In fact, it turned out to be slower in practice compared to [simplex method](#) which is not a polynomial time method. In 1984, [Narendra Karmarkar](#) developed a method for [linear programming](#) called [Karmarkar's algorithm](#) which runs in provably polynomial time and is also very efficient in practice. It enabled solutions of linear programming problems which were beyond the capabilities of simplex method. Contrary to the simplex method, it reaches a best solution by traversing the interior of the [feasible region](#). The method can be generalized to convex programming based on a [self-concordant barrier function](#) used to encode the [convex set](#).

Any convex optimization problem can be transformed into minimizing (or maximizing) a [linear function](#) over a convex set by converting to the [epigraph](#) form.<sup>[2]</sup> The idea of encoding the [feasible set](#) using a barrier and designing barrier methods was studied by Anthony V. Fiacco, Garth P. McCormick, and others in the early 1960s. These ideas were mainly developed for general [nonlinear programming](#), but they were later abandoned due to the presence of more competitive methods for this class of problems (e.g. [sequential quadratic programming](#)).

[Yurii Nesterov](#) and [Arkadi Nemirovski](#) came up with a special class of such barriers that can be used to encode any convex set. They guarantee that the number of [iterations](#) of the algorithm is bounded by a polynomial in the dimension and accuracy of the solution.<sup>[3]</sup>

Karmarkar's breakthrough revitalized the study of interior point methods and barrier problems, showing that it was possible to create an algorithm for linear programming characterized by [polynomial complexity](#) and, moreover, that was competitive with the simplex method. Already [Khachiyan's ellipsoid method](#) was a polynomial time algorithm; however, it was too slow to be of practical interest.

The class of primal-dual path-following interior point methods is considered the most successful. [Mehrotra's predictor-corrector algorithm](#) provides the basis for most implementations of this class of methods.<sup>[4]</sup>



Example solution

## Contents [\[hide\]](#)

- [1 Primal-dual interior point method for nonlinear optimization](#)
- [2 See also](#)
- [3 References](#)
- [4 Bibliography](#)

## Primal-dual interior point method for nonlinear optimization [\[edit\]](#)

The primal-dual method's idea is easy to demonstrate for constrained [nonlinear optimization](#). For simplicity consider the all-inequality version of a nonlinear optimization problem:

$$\begin{aligned} &\text{minimize } f(x) \text{ subject to } c_i(x) \geq 0 \text{ for } i = 1, \dots, m, \quad x \in \mathbb{R}^n, \text{ where} \\ &f : \mathbb{R}^n \rightarrow \mathbb{R}, c_i : \mathbb{R}^n \rightarrow \mathbb{R} \end{aligned} \quad (1)$$

The logarithmic [barrier function](#) associated with (1) is

$$B(x, \mu) = f(x) - \mu \sum_{i=1}^m \ln(c_i(x)) \quad (2)$$

Here  $\mu$  is a small positive scalar, sometimes called the "barrier parameter". As  $\mu$  converges to zero the minimum of  $B(x, \mu)$  should converge to a solution of (1).

The barrier function [gradient](#) is

$$g_b = g - \mu \sum_{i=1}^m \frac{1}{c_i(x)} \nabla c_i(x) \quad (3)$$

where  $g$  is the gradient of the original function  $f(x)$  and  $\nabla c_i$  is the gradient of  $c_i$ .

In addition to the original ("primal") variable  $x$  we introduce a [Lagrange multiplier](#) inspired [dual](#) variable  $\lambda \in \mathbb{R}^m$

$$c_i(x)\lambda_i = \mu, \forall i = 1, \dots, m \quad (4)$$

(4) is sometimes called the "perturbed complementarity" condition, for its resemblance to "complementary slackness" in [KKT conditions](#).

We try to find those  $(x_\mu, \lambda_\mu)$  for which the gradient of the barrier function is zero.

Applying (4) to (3) we get an equation for the gradient:

$$g - A^T \lambda = 0 \quad (5)$$

where the matrix  $A$  is the constraint  $c(x)$  [Jacobian](#).

The intuition behind (5) is that the gradient of  $f(x)$  should lie in the subspace spanned by the constraints' gradients. The "perturbed complementarity" with small  $\mu$  (4) can be understood as the condition that the solution should either lie near the boundary  $c_i(x) = 0$  or that the projection of the gradient  $g$  on the constraint component  $c_i(x)$  normal should be almost zero.

Applying [Newton's method](#) to (4) and (5) we get an equation for  $(x, \lambda)$  update  $(p_x, p_\lambda)$ :

$$\begin{pmatrix} W & -A^T \\ \Lambda A & C \end{pmatrix} \begin{pmatrix} p_x \\ p_\lambda \end{pmatrix} = \begin{pmatrix} -g + A^T \lambda \\ \mu 1 - C \lambda \end{pmatrix}$$

where  $W$  is the [Hessian matrix](#) of  $f(x)$  and  $\Lambda$  is a [diagonal matrix](#) of  $\lambda$  and  $C$  is a diagonal matrix where  $C_{ii}$  is  $c_i(x)$ .

Because of (1), (4) the condition

$$\lambda \geq 0$$

should be enforced at each step. This can be done by choosing appropriate  $\alpha$ :

$$(x, \lambda) \rightarrow (x + \alpha p_x, \lambda + \alpha p_\lambda).$$

See also [\[edit\]](#)

- [Augmented Lagrangian method](#)
- [Penalty method](#)
- [Karush–Kuhn–Tucker conditions](#)

References [\[edit\]](#)

- ↑ Dantzig, George B.; Thapa, Mukund N. (2003). *Linear Programming 2: Theory and Extensions*. Springer-Verlag.
- ↑ Boyd, Stephen; Vandenberghe, Lieven (2004). *Convex Optimization*. Cambridge: [Cambridge University Press](#). p. 143. ISBN 0-521-83378-7. MR 2061575 [↗](#).
- ↑ Wright, Margaret H. (2004). "The interior-point revolution in optimization: History, recent developments, and lasting consequences". *Bulletin of the American Mathematical Society* **42**: 39. doi:10.1090/S0273-0979-04-01040-7 [↗](#). MR 2115066 [↗](#).
- ↑ Potra, Florian A.; Stephen J. Wright (2000). "Interior-point methods". *Journal of Computational and Applied Mathematics* **124** (1–2): 281–302. doi:10.1016/S0377-0427(00)00433-7 [↗](#).


Bibliography [\[edit\]](#)

- Bonnans, J. Frédéric; Gilbert, J. Charles; Lemaréchal, Claude; Sagastizábal, Claudia A. (2006). *Numerical optimization: Theoretical and practical aspects* [↗](#). Universitext (Second revised ed. of translation of 1997 French ed.). Berlin: Springer-Verlag. pp. xiv+490. doi:10.1007/978-3-540-35447-5 [↗](#). ISBN 3-540-35445-X. MR 2265882 [↗](#).
- Karmarkar, N. (1984). "Proceedings of the sixteenth annual ACM symposium on Theory of computing - STOC '84" [↗](#) (PDF). p. 302. doi:10.1145/800057.808695 [↗](#). ISBN 0-89791-133-4. |chapter= ignored ([help](#))
- Mehrotra, Sanjay (1992). "On the Implementation of a Primal-Dual Interior Point Method". *SIAM Journal on Optimization* **2** (4): 575. doi:10.1137/0802028 [↗](#).
- Nocedal, Jorge; Stephen Wright (1999). *Numerical Optimization*. New York, NY: Springer. ISBN 0-387-

98793-2.

- Press, WH; Teukolsky, SA; Vetterling, WT; Flannery, BP (2007). "Section 10.11. Linear Programming: Interior-Point Methods" [↗](#). *Numerical Recipes: The Art of Scientific Computing* (3rd ed.). New York: Cambridge University Press. ISBN 978-0-521-88068-8.
- Wright, Stephen (1997). *Primal-Dual Interior-Point Methods*. Philadelphia, PA: SIAM. ISBN 0-89871-382-X.
- Boyd, Stephen; Vandenberghe, Lieven (2004). *Convex Optimization* [↗](#). Cambridge University Press.

v · t · e		<b>Optimization: Algorithms, methods, and heuristics</b>	[hide]
		<b>Unconstrained nonlinear: Methods calling ...</b>	[show]
		<b>Constrained nonlinear</b>	[show]
		<b>Convex optimization</b>	[hide]
<b>Convex minimization</b>	Cutting-plane method · Reduced gradient (Frank–Wolfe) · Subgradient method		
<b>Linear and quadratic</b>	<b>Interior point</b>	Ellipsoid algorithm of Khachiyan · Projective algorithm of Karmarkar	
	<b>Basis-Exchange</b>	Simplex algorithm of Dantzig · Revised simplex algorithm · Criss-cross algorithm · Principal pivoting algorithm of Lemke	
		<b>Combinatorial</b>	[show]
		<b>Metaheuristics</b>	[show]
Categories (Algorithms and methods · Heuristics) · <b>Software</b>			



Categories: Optimization algorithms and methods

This page was last modified on 11 July 2015, at 19:10.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

