



WIKIPEDIA  
The Free Encyclopedia

[Main page](#)  
[Contents](#)  
[Featured content](#)  
[Current events](#)  
[Random article](#)  
[Donate to Wikipedia](#)  
[Wikipedia store](#)

Interaction

[Help](#)  
[About Wikipedia](#)  
[Community portal](#)  
[Recent changes](#)  
[Contact page](#)

Tools

[What links here](#)  
[Related changes](#)  
[Upload file](#)  
[Special pages](#)  
[Permanent link](#)  
[Page information](#)  
[Wikidata item](#)  
[Cite this page](#)

Print/export

[Create a book](#)  
[Download as PDF](#)  
[Printable version](#)

Languages

[Deutsch](#)


 [Edit links](#)

[Create account](#) [Log in](#)

Article [Talk](#)

[Read](#) [Edit](#)

[More](#) ▾



# Difference list

From Wikipedia, the free encyclopedia



In [computer science](#), the term **difference list** may refer to one of two [data structures](#) for representing [lists](#). One of these data structures contains two lists, and represents the difference of those two lists. The second data structure is a [functional](#) representation of a list with an efficient [concatenation](#) operation. In the second approach, difference lists are implemented as single-argument [functions](#), which take a list as [argument](#) and prepend to that list. As a consequence, concatenation of difference lists of the second type is implemented essentially as [function composition](#), which is *O*(1). However, of course the list still has to be constructed eventually (assuming all of its elements are needed), which is plainly at least *O*(*n*).

## Difference lists as functions [\[edit\]](#)

A difference list of the second sort represents lists as a function *f*, which when given a list *x*, returns the list that *f* represents, prepended to *x*. It is typically used in functional programming languages such as [Haskell](#), although it could be used in imperative languages as well. Whether this kind of difference list is more efficient than another list representations depends on usage patterns. If an algorithm builds a list by concatenating smaller lists, which are themselves built by concatenating still smaller lists, then use of difference lists can improve performance by effectively "flattening" the list building computations.

Examples of use are in the *ShowS* type in the Prelude of Haskell, and in Donald Bruce Stewart's [difference list library for Haskell](#).

## External links [\[edit\]](#)

- [Open Lists and Difference Lists](#)  in [Prolog](#)
- [Difference Lists](#)  in [Haskell \(programming language\)](#)



*This [algorithms](#) or [data structures](#)-related article is a *stub*. You can help Wikipedia by [expanding it](#).*

Categories: [Algorithms and data structures stubs](#) | [Computer science stubs](#) | [Linked lists](#)

This page was last modified on 17 May 2013, at 20:57.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the [Wikimedia Foundation, Inc.](#), a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)



a  
WIKIMEDIA  
project



Powered By  
MediaWiki