



WIKIPEDIA  
The Free Encyclopedia

Main page  
Contents  
Featured content  
Current events  
Random article  
Donate to Wikipedia  
Wikipedia store

Interaction

Help  
About Wikipedia  
Community portal  
Recent changes  
Contact page

Tools

What links here  
Related changes  
Upload file  
Special pages  
Permanent link  
Page information  
Wikidata item  
Cite this page

Print/export

Create a book  
Download as PDF  
Printable version

Languages

Deutsch  
Español  
Français  
Italiano  
Latviešu  
Magyar  
日本語  
Norsk bokmål  
Polski  
Português  
Русский  
Suomi  
Українська

Edit links

Article **Talk**

Read **Edit** V More

Search

# Gouraud shading

From Wikipedia, the free encyclopedia



This article **relies too much on references to primary sources**. Please improve this article by adding **secondary or tertiary sources**. *(February 2014)*




This article **needs additional citations for verification**. Please help **improve this article** by **adding citations to reliable sources**. Unsourced material may be challenged and removed. *(March 2012)*

**Gouraud shading**, named after **Henri Gouraud**, is an **interpolation** method used in **computer graphics** to produce **continuous shading** of surfaces represented by polygon meshes. In practice, Gouraud shading is most often used to achieve continuous lighting on triangle surfaces by computing the lighting at the corners of each triangle and **linearly interpolating** the resulting colours for each **pixel** covered by the triangle. Gouraud first published the technique in 1971.<sup>[1][2][3]</sup>

**Contents** [hide]

- Description
- Comparison with other shading techniques
- See also
- References



Gouraud-shaded triangle mesh using the **Phong reflection model**

## Description [edit]


Gouraud shading works as follows: An estimate to the **surface normal** of each **vertex** in a polygonal 3D model is either specified for each vertex or found by averaging the surface normals of the polygons that meet at each vertex. Using these estimates, lighting computations based on a reflection model, e.g. the **Phong reflection model**, are then performed to produce colour intensities at the vertices. For each **screen pixel** that is covered by the polygonal mesh, colour intensities can then be **interpolated** from the colour values calculated at the vertices.

## Comparison with other shading techniques [edit]

Gouraud shading is considered superior to **flat shading** and requires significantly less processing than **Phong shading**, but usually results in a faceted look.


In comparison to Phong shading, Gouraud shading's strength and weakness lies in its interpolation. If a mesh covers more pixels in screen space than it has vertices, interpolating colour values from samples of expensive lighting calculations at vertices is less processor intensive than performing the lighting calculation for each pixel as in Phong shading. However, highly localized lighting effects (such as **specular highlights**, e.g. the glint of reflected light on the surface of an apple) will not be rendered correctly, and if a highlight lies in the middle of a polygon, but does not spread to the polygon's vertex, it will not be apparent in a Gouraud rendering; conversely, if a highlight occurs at the vertex of a polygon, it will be rendered correctly at this vertex (as this is where the lighting model is applied), but will be spread unnaturally across all neighboring polygons via the interpolation method.

The problem is easily spotted in a rendering which ought to have a specular highlight moving smoothly across the surface of a model as it rotates. Gouraud shading will instead produce a highlight continuously fading in and out across neighboring portions of the model, peaking in intensity when the intended specular highlight passes over a vertex of the model. For clarity, note that the problem just described can be improved by increasing the



Comparison of **flat shading** and Gouraud shading.

density of vertices in the object (or perhaps increasing them just near the problem area), but of course, this solution applies to any shading paradigm whatsoever - indeed, with an "incredibly large" number of vertices there would never be any need at all for shading concepts.



Gouraud-shaded sphere - note the poor behaviour of the specular highlight.

The same sphere rendered with a very high polygon count.

## See also [\[edit\]](#)

- [List of common shading algorithms](#)
- [Blinn–Phong shading model](#)
- [Phong shading](#)



## References [\[edit\]](#)

- ↑ Gouraud, Henri (1971). *Computer Display of Curved Surfaces, Doctoral Thesis* ↗. University of Utah.
- ↑ Gouraud, Henri (1971). "Continuous shading of curved surfaces" ↗ (PDF). *IEEE Transactions on Computers* **C-20** (6): 623–629. doi:10.1109/T-C.1971.223313 ↗.
- ↑ Gouraud, Henri (1998). "Continuous shading of curved surfaces". In Rosalee Wolfe (ed.). *Seminal Graphics: Pioneering efforts that shaped the field* ↗. ACM Press. ISBN 1-58113-052-X.

Categories: [Shading](#) | [Virtual reality](#) | [Computer graphics algorithms](#)

This page was last modified on 3 August 2015, at 17:17.

Text is available under the [Creative Commons Attribution-ShareAlike License](#); additional terms may apply. By using this site, you agree to the [Terms of Use](#) and [Privacy Policy](#). Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

[Privacy policy](#) [About Wikipedia](#) [Disclaimers](#) [Contact Wikipedia](#) [Developers](#) [Mobile view](#)

