

Main page
Contents
Featured content
Current events
Random article
Donate to Wkipedia
Wkipedia store

Interaction

Help

About Wikipedia

Community portal

Recent changes

Contact page

Tools

What links here

Related changes

Upload file

Special pages

Permanent link

Page information

Wikidata item

Cite this page

Print/export

Create a book

Download as PDF

Printable version

Languages

Español

Русский

Српски / srpski

Article Talk Read Edit View history Search Q

Cyrus-Beck algorithm

From Wikipedia, the free encyclopedia (Redirected from Cyrus–Beck)

The **Cyrus–Beck algorithm** is a generalized line clipping algorithm. It was designed to be more efficient than the **Sutherland–Cohen algorithm** which uses repetitive clipping.^[1] Cyrus–Beck is a general algorithm and can be used with a convex polygon clipping window unlike Sutherland-Cohen that can be used only on a rectangular clipping area.

Here the parametric equation of a line in the view plane is:

$$p(t) = tp_1 + (1-t)p_0$$

= $p_0 + t(p_1 - p_0)$

where 0 < t < 1.

Now to find intersection point with the clipping window we calculate value of dot product. Let p_E be a point on the clipping plane E.

Calculate $n \cdot (p(t) - p_E)$

if > 0 vector pointed towards interior

if = 0 vector pointed parallel to plane containing p

if < 0 vector pointed away from interior

Here *n* stands for normal of the current clipping plane (pointed away from interior).

By this we select the point of intersection of line and clipping window where (dot product = 0) and hence clip the line

Contents [hide]

1 Notes

2 See also

3 References

4 External links

Notes [edit]

- 1. ^ "Clipping" (presentation) &
- 1] Sutherland-Cohen can be used only on a rectangular clipping area.
- 2] Cyrus–Beck is a general algorithm and can be used with a convex polygon clipping window.

```
p(t) = p0 + t(p1-p0) /* it's parametric function */
```

3] if > 0; vector says p(t) is OUTSIDE && A < 90 degree.

```
if < 0; vector says p(t) is INSIDE && a > 90 degree.
```

if = 0 ; vector says p(t) is on edge E .. here outer normal edge is perpendicular to the E and p(t)-B

.. we will writing here a function code for it as given below :

```
/*
if( DtProd (N,P(t)-B) > 0)
{
```

```
p(t) OUTER & A < 90 degree ; /* P(t) is OUTSIDE ..
   else if ( DtProd (N,P(t)-B) < 0)
             p(t) INNER & A > 90 degree; /* P(t) is INSIDE ..
  else ( DtProd (N, P(t)-B) = 0)
             p(t) lies on to the edge E ; \phantom{a} /* where outer normal edge N would be
perpendicular to both E and p(t)-B..
```

See also [edit]

Algorithms used for the same purpose:

- Cohen-Sutherland
- Liang-Barsky
- Nicholl-Lee-Nicholl
- Fast-clipping

References in other media:

• Tron: Uprising

References [edit]

- Mike Cyrus, Jay Beck. "Generalized two- and three-dimensional clipping". Computers & Graphics, 1978: 23-
- James D. Foley. Computer graphics: principles and practice & Addison-Wesley Professional, 1996. p. 117.

External links [edit]

- http://cs1.bradley.edu/public/jcm/cs535CyrusBeck.html ₺
- http://softsurfer.com/Archive/algorithm_0111/algorithm_0111.htm @^[dead link]



Market I This computer graphics–related article is a stub. You can help Wikipedia by expanding it.

Categories: Clipping (computer graphics) | Computer graphics stubs

This page was last modified on 1 September 2014, at 21:40.

Text is available under the Creative Commons Attribution-ShareAlike License; additional terms may apply. By using this site, you agree to the Terms of Use and Privacy Policy. Wikipedia® is a registered trademark of the Wikimedia Foundation, Inc., a non-profit organization.

Privacy policy About Wikipedia Disclaimers Contact Wikipedia Developers Mobile view



