

```
127.0.0.1:6379> SET name Nitin
OK
127.0.0.1:6379> SET teamname Cosmos
OK
127.0.0.1:6379> SET college KIET
OK
127.0.0.1:6379> SET ID nitin.1923it1090@kiet.edu
OK
127.0.0.1:6379> KEYS *
1) "college"
2) "name"
3) "ID"
4) "teamname"
127.0.0.1:6379> ttl name
(integer) -1
127.0.0.1:6379> expire teamname
(error) ERR wrong number of arguments for 'expire' command
127.0.0.1:6379> expire teamname 5
(integer) 1
127.0.0.1:6379> ttl teamname
(integer) -2
127.0.0.1:6379> KEYS *
1) "college"
2) "name"
3) "ID"
127.0.0.1:6379> SETEX rollno 20 1900290130111
OK
127.0.0.1:6379> ttl rollno
(integer) 14
127.0.0.1:6379> KEYS *
1) "college"
2) "name"
3) "ID"
4) "rollno"
127.0.0.1:6379> ttl rollno
(integer) 2
127.0.0.1:6379> ttl rollno
(integer) -2
127.0.0.1:6379> KEYS *
```

Activities Terminal

Sep 1 9:00 PM

hp@hp-HP-245-G5-Notebook-PC: ~

```
(integer) 14
127.0.0.1:6379> KEYS *
1) "college"
2) "name"
3) "ID"
4) "rollno"
127.0.0.1:6379> ttl rollno
(integer) 2
127.0.0.1:6379> ttl rollno
(integer) -2
127.0.0.1:6379> KEYS *
1) "college"
2) "name"
3) "ID"
127.0.0.1:6379> ttl rollno
(integer) -2
127.0.0.1:6379> lpush name [RAJ,NITI,SIMRAM,]
(error) WRONGTYPE Operation against a key holding a value
127.0.0.1:6379> lpush name raj
(error) WRONGTYPE Operation against a key holding a value
127.0.0.1:6379> FLUSHALL
OK
127.0.0.1:6379> KEYS *
(empty list or set)
127.0.0.1:6379> lpush name Raj
(integer) 1
127.0.0.1:6379> lpush name kiran
(integer) 2
127.0.0.1:6379> lpush name simr
(integer) 3
127.0.0.1:6379> lpush name raj
(integer) 4
127.0.0.1:6379> LRANGE name 0 -1
1) "raj"
2) "simr"
3) "kiran"
4) "Raj"
127.0.0.1:6379>
```

Take Screenshot

Cancel Take Screenshot

Take Screenshot

☒ Grab the whole screen

☐ Grab the current window

☐ Select area to grab

Grab after a delay of seconds

Effects

☐ Include pointer

☒ Include the window border

Apply effect: