

Configuring Bluetooth in cisco packet tracer
Done By Samip Khadka



IoT0

Specifications Physical **Config** Attributes

GLOBAL
Settings
Algorithm Settings
Files
INTERFACE
Wireless0
Bluetooth

Wireless0	
Port Status	☐ On
Bandwidth	11 Mbps
MAC Address	00D0.FF23.5090
SSID	HomeGateway
Authentication	
☒ Disabled	☐ WEP
☐ WPA-PSK	☐ WPA2-PSK
☐ WPA	☐ WPA2
☐ 802.1X	Method:
	MD5
	User Name
	Password
	WEK Key
	PSK Pass Phrase
	User ID
	Password
Encryption Type	Disabled
IP Configuration	
☒ DHCP	
☐ Static	
IPv4 Address	
Subnet Mask	
IPv6 Configuration	
☒ Automatic	
☐ Static	
IPv6 Address	
Link Local Address:	FE80::2D0:FFFF:FE23:5090

Specifications Physical **Config** Attributes

GLOBAL

Settings

Algorithm Settings

Files

INTERFACE

Wireless0

Bluetooth

Bluetooth

Port Status ☒ On

MAC Address 0005.5E37.9286

Coverage Range (meters) 10.00

Discoverable ☒ On

Devices

Name	MAC Address	Status
------	-------------	--------

Discover Pair Unpair Tether Untether

Beacon Broadcasting

Broadcast ☐ On

Frequency (seconds) 10

UUID {7cef4389-6595-4053-92dc-0a5fafc66441}

Data

Specifications Physical **Config** Attributes

GLOBAL

Settings

Algorithm Settings

Files

INTERFACE

Wireless0

Bluetooth

Wireless0

Port Status ☐ On

Bandwidth 11 Mbps

MAC Address 00E0.F943.DE9A

SSID HomeGateway

Authentication

☒ Disabled ☐ WEP ☐ WPA-PSK ☐ WPA2-PSK ☐ WPA ☐ WPA2 ☐ 802.1X

Method:

WEP Key

PSK Pass Phrase

User ID

Password

MD5

User Name

Password

Encryption Type Disabled

Specifications Physical **Config** Attributes

GLOBAL	
Settings	
Algorithm Settings	
Files	
INTERFACE	
Wireless0	
Bluetooth	

Bluetooth

Port Status ☒ On

MAC Address 0000.0CBB.2161

Coverage Range (meters) 10.00

Discoverable ☒ On

Devices

Name	MAC Address	Status
------	-------------	--------

Discover Pair Unpair Tether Untether

Specifications Physical **Config** Attributes

GLOBAL	
Settings	
Algorithm Settings	
Files	
INTERFACE	
Wireless0	
Bluetooth	

Bluetooth

Port Status ☒ On

MAC Address 0000.0CBB.2161

Coverage Range (meters) 10.00

Discoverable ☒ On

Devices

Name	MAC Address	Status
IoT0	0005.5E37.9286	Unpaired

Discover Pair Unpair Tether Untether

Beacon Broadcasting

Broadcast ☐ On

Frequency (seconds) 10

UUID {0cd5f847-ab31-471a-afbd-4c6fc65e86fa}

Data

Specifications Physical **Config** Attributes

GLOBAL

Settings

Algorithm Settings

Files

INTERFACE

Wireless0

Bluetooth

Bluetooth

Port Status ☒ On

MAC Address 0000.0CBB.2161

Coverage Range (meters) 10.00

Discoverable ☒ On

Devices

Name	MAC Address	Status
IoT0	0005.5E37.9286	Paired, Connected

Discover Pair Unpair Tether Untether

Beacon Broadcasting

Broadcast ☐ On

Frequency (seconds) 10

UUID {0cd5f847-ab31-471a-afbd-4c6fc65e86fa}

Data

Configuring Bluetooth in cisco packet tracer
Done By Samip Khadka

