

AltEner Solutions



LITE

THE LITE ADVANTAGE

- High-tensile steel chassis frame for superior durability and structural integrity
- Aerodynamic body structure optimized for extended range and energy efficiency
- Thermally stable Lithium Iron Phosphate (LiFePO₄) battery pack for maximum safety
- 5.5 kW Permanent Magnet Synchronous Motor (PMSM) delivering 35 Nm torque for gradients
- Ingress Protection 65 (IP65) weather-sealed components for all-condition reliability
- Regenerative braking system recaptures kinetic energy during deceleration
- Advanced Internet of Things (IoT) ecosystem with real-time fleet telemetry and geofencing
- Driver analytics for operational optimization and running cost reduction
- Return on Investment (ROI) achievable within 18-24 months for Small and Medium Enterprises (SME)
- Future-proof solution for evolving logistics sector demands
- Low Total Cost of Ownership (TCO) with minimal scheduled maintenance requirements
- Zero tailpipe emissions contributing to cleaner urban environments
- Ergonomic driver cabin designed for extended shift comfort and reduced fatigue
- Intelligent Battery Management System (BMS) with cell-level monitoring and fault diagnostics
- Compact footprint enabling navigation through congested city lanes and narrow alleyways
- Scalable platform adaptable to diverse last-mile business requirements

CUSTOM BODY CONFIGURATIONS



FLATBED PLATFORM

Open deck design accommodates oversized cargo, construction materials, and heavy loads.

Max Capacity

Construction

CONTAINER BODY

Fully enclosed payload compartment with weather-sealed doors and anti-theft features.

Weather-proof

High Security



LOW BODY CHASSIS

Low-slung design for rapid loading/unloading with enhanced accessibility.

Fast Loading

Distribution

120

RANGE (KM)

40

SPEED (KM/H)

400

PAYLOAD (KG)

3-4

CHARGE (HRS)

35

TORQUE (NM)

5.5

POWER (KW)

INTELLIGENT FEATURES

SMART TECHNOLOGY



Digital Dashboard

4.3-inch high-contrast screen displaying speed, battery, and trip metrics.



Fleet Telematics

Dedicated app with live tracking, battery analytics, and route history.



Aviation Connector

High-grade waterproof connectors for reliable power transmission.



OTA Updates

Over-The-Air firmware updates keep your vehicle current without visits.

PERFORMANCE



PMSM Motor

5.5 kW permanent magnet motor with 35 Nm peak torque, IP65 sealed.



LiFePO4 Battery

Advanced 4.8kWh lithium iron phosphate cells for safety and longevity.



Smart Charging

Standard AC charging with compatible plug-in for quick turnaround.



Regen Braking

Recaptures kinetic energy to extend range and reduce brake wear.

MECHANICAL



Brake Pedal

Robust dual-circuit pedal linkage for precise stopping power.



Robust Chassis

High-tensile steel frame with reinforced underbody protection.



Heavy Suspension

Spring-loaded system designed for heavy load stability.



Handbrake

Mechanical parking lever with pedal linkage for secure holding.

TECHNICAL SPECIFICATIONS

BATTERY & CHARGING

Battery Type	LiFePO4
Capacity	4.8 kWh
Charge (0-80%)	~3 hrs
Charging Mode	Single Phase AC

PERFORMANCE

Top Speed	40 km/h
Range (Full)	120 km
0-20 km/h	~8 sec
Drive Modes	Drive/Eco/Rev

DIMENSIONS

Length	3565 mm
Width	1530 mm
Height	1860 mm
GVW	750 kg

POWERTRAIN

Motor Type	PMSM, IP65
Peak Power	5.5 kW
Peak Torque	35 Nm
Transmission	Single Speed

CONNECTIVITY

GPS Tracking	Real-time
Fleet Mgmt	Cloud Panel
Mobile App	iOS/Android
OTA Updates	Auto

CHASSIS & SUSP.

Frame	Hi-Tensile Steel
Front Susp.	Hydraulic Telesc.
Rear Susp.	Semi-Elliptic
Tyres	8" Steel Rim

WEIGHT DATA

Kerb Weight	350 kg
Payload	400 kg
GVW	750 kg
Wheelbase	2100 mm

GENERAL FEATURES

Display	Digital Gauge
Lighting	LED All Round
Braking	Hydraulic Dual
Handbrake	Mechanical

SERVICE & WARRANTY

Warranty	3 years or 60000 kms
Service Network	Pan India
Spare Parts	Available

* Specifications subject to change. Performance under standard test conditions.

CHOOSE YOUR CONFIGURATION

DIMENSIONS	CONTAINER	FLATBED	LOWER DECK
PREVIEW			
HEIGHT (mm)	1110	-	-
LENGTH (mm)	1300	1348	1342
WIDTH (mm)	1200	1209	1200
WHEELBASE (mm)	2100	2100	2100
GROUND CLEARANCE (mm)	180	180	180
CUBIC CAPACITY (m³)	1.7	1.5	1.6

READY TO ELECTRIFY YOUR FLEET

Join the electrification movement with ALTENER LITE. Experience sustainable, cost-effective, and intelligent cargo transport.

BOOK A TEST DRIVE

ADDRESS

Bangalore, Karnataka,
India

CONTACT

PHONE
+91 XXXXX XXXXX
EMAIL
i---