

Homework-5

Group 4

6/11/2020

Problem 1

The file ToyotaCorolla.xlsx contains the data on used cars (Toyota Corolla) on sale during late summer of 2004 in The Netherlands. It has 1436 records containing details on 38 attributes, including Price, Age, Kilometers, HP, and other specifications. The goal is to predict the price of a used Toyota Corolla based on its specifications.

Data Preprocessing: Create dummy variables for the categorical predictors (Fuel Type and Color). Split the data into training (50%), validation (30%), and test (20%) datasets.

```
library(dplyr)

##
## Attaching package: 'dplyr'

## The following objects are masked from 'package:stats':
##
##   filter, lag

## The following objects are masked from 'package:base':
##
##   intersect, setdiff, setequal, union

library(readxl)
library(ggplot2)
library(caret)

## Loading required package: lattice

library(tree)
library(rpart)
library(rpart.plot)
library(OneR)
library(reshape2)

ToyotaCorolla <- read_xlsx("ToyotaCorolla.xlsx", sheet = "data")

dummies <- dummyVars(~ Fuel_Type + Color, data = ToyotaCorolla, sep = ".")
dummies <- predict(dummies, ToyotaCorolla)

ToyotaCorolla <- cbind(select(ToyotaCorolla, -c("Fuel_Type", "Color")),
                       as.data.frame(dummies))

set.seed(20)
split_sample <- sample(1:3,
```

```

size = nrow(ToyotaCorolla),
prob = c(0.50, 0.30, 0.20),
replace = TRUE)

train_data <- ToyotaCorolla[split_sample == 1, ]
validation_data <- ToyotaCorolla[split_sample == 2, ]
test_data <- ToyotaCorolla[split_sample == 3, ]

```

(a) Run a regression tree (RT) with the output variable Price and input variables


Age_08_04, KM, Fuel_Type, HP, Automatic, Doors, Quarterly_Tax, Mfg_Guarantee, Guarantee_Period, Airco, Automatic_Airco, CD Player, Powered_Windows, Sport_Model, and Tow_Bar.

```


reg.tree <- rpart(Price ~ Age_08_04 + KM + Fuel_TypeCNG + Fuel_TypeDiesel +
  Fuel_TypePetrol + HP + Automatic + Doors +
  Quarterly_Tax + Mfr_Guarantee + Guarantee_Period + Airco +
  Tow_Bar,
  data = train_data,
  method = "anova")

rpart.plot(reg.tree)

```



```
plotcp(reg.tree)
```



```
print(reg.tree$variable.importance)
```

```
##      Age_08_04 Automatic_airco      KM      Quarterly_Tax
##      7716864493      2456255799      1812651349      837860826
##      HP Guarantee_Period      CD_Player Fuel_TypeDiesel
##      811189489      336999867      219398681      34185858
## Fuel_TypePetrol      Doors      Airco Powered_Windows
##      34185858      31068708      27966026      18322568
## Mfr_Guarantee      Sport_Model
##      17358223      3107805
```

- (i) Which appear to be the three or four most important car specifications for predicting the car's price?
 - The most important car specifications for predicting the car's price are Age_08_04, KM and Automatic_airco.
- (ii) Compare the prediction errors of the training, validation, and test sets by examining their RMS error and by plotting the three boxplots. What is happening with the training set predictions? How does the predictive performance of the test set compare to the other two? Why does this occur?

```
train_preds <- predict(reg.tree, train_data)
validation_preds <- predict(reg.tree, validation_data)
test_preds <- predict(reg.tree, test_data)

train_error <- RMSE(train_preds, train_data$Price)
validation_error <- RMSE(validation_preds, validation_data$Price)
test_error <- RMSE(test_preds, test_data$Price)
```

```

cat("Train Data RMSE", train_error, "\n")

## Train Data RMSE 1345.008

cat("Validation Data RMSE", validation_error, "\n")


## Validation Data RMSE 1397.415

cat("Test Data RMSE", test_error, "\n")

## Test Data RMSE 1591.446

df <- melt(as.data.frame(cbind(train_preds, validation_preds, test_preds)))
ggplot(data = df, aes(x = variable, y = value, fill = variable)) +
  geom_boxplot() +
  theme(legend.position = "none") +
  ggtitle("Price Predictions Box Plot") +
  labs(x = "", y = "Price")

```



We can see from the RMSE error that the model performs the best on the train_data but that is to be expected. It performs slightly worse on the validation data. It performs the worst on the test data.

We can see that the training set predictions are similar to the actual Price values of the train data with a mean of approx \$10000. There are 2 samples which are outliers in all three of the sets.

- (iv) If we used the full tree instead of the best pruned tree to score the validation set, how would this affect the predictive performance for the validation set? (Hint: Does the full tree use the validation data?)

```

full.tree <- rpart(Price ~ Age_08_04 + KM + Fuel_TypeCNG + Fuel_TypeDiesel +
  Fuel_TypePetrol + HP + Automatic + Doors +

```


```

Quarterly_Tax + Mfr_Guarantee + Guarantee_Period + Airco +
Tow_Bar,
data = train_data,
method = "anova",
control = list(cp = 0))


```

```
rpart.plot(full.tree)
```

Warning: labs do not fit even at cex 0.15, there may be some overplotting



```
plotcp(full.tree)
```



```

train_preds <- predict(full.tree, train_data)
validation_preds <- predict(full.tree, validation_data)
test_preds <- predict(full.tree, test_data)

train_error <- RMSE(train_preds, train_data$Price)
validation_error <- RMSE(validation_preds, validation_data$Price)
test_error <- RMSE(test_preds, test_data$Price)

cat("Train Data RMSE", train_error, "\n")

## Train Data RMSE 971.6847

cat("Validation Data RMSE", validation_error, "\n")

## Validation Data RMSE 1202.67

cat("Test Data RMSE", test_error, "\n")

## Test Data RMSE 1497.919

```

Using the full tree, we significantly reduce the RMSE error on both the validation and the test sets. Although the full tree doesn't use the validation data, it has more decision boundaries which are correctly separating the validation data hence reducing its error.

- (b) Let us see the effect of turning the price variable into a categorical variable. First, create a new variable that categorizes price into 20 bins of equal counts. Now repartition the data keeping Binned Price instead of Price. Run a classification tree (CT) with the same set of input variables as in the RT, and with Binned Price as the output variable.

```
ToyotaCorolla$Price <- cut(ToyotaCorolla$Price, breaks = seq(4300, 32500, by = 1410))
```

```
set.seed(20)
```


```
split_sample <- sample(1:3,  
  size = nrow(ToyotaCorolla),  
  prob = c(0.50, 0.30, 0.20),  
  replace = TRUE)
```

```
train_data <- ToyotaCorolla[split_sample == 1, ]  
validation_data <- ToyotaCorolla[split_sample == 2, ]  
test_data <- ToyotaCorolla[split_sample == 3, ]
```


```
class.tree <- rpart(Price ~ Age_08_04 + KM + Fuel_TypeCNG + Fuel_TypeDiesel +  
  Fuel_TypePetrol + HP + Automatic + Doors +  
  Quarterly_Tax + Mfr_Guarantee + Guarantee_Period + Airco +  
  Tow_Bar,  
  data = train_data)
```

```
rpart.plot(class.tree)
```

Warning: All boxes will be white (the box.palette argument will be ignored) because
the number of classes in the response 20 is greater than length(box.palette) 6.
To silence this warning use box.palette=0 or trace=-1.



```
plotcp(class.tree)
```



```
print(class.tree$variable.importance)
```

```
##      Age_08_04      KM      Airco      Automatic_airco
##      127.3907916      53.2246381      19.4035608      18.5668915
##      CD_Player      Sport_Model      Quarterly_Tax      Mfr_Guarantee
##      18.2603264      15.7928942      7.3889731      6.7235932
##      Powered_Windows      HP      Fuel_TypePetrol      Guarantee_Period
##      6.5573410      3.8118783      1.1929470      0.9997784
##      Doors      Fuel_TypeDiesel      Fuel_TypeCNG      Automatic
##      0.8981243      0.7550886      0.3205369      0.1602685
```

- (i) Compare the tree generated by the CT with the one generated by the RT. Are they different? (Look at structure, the top predictors, size of tree, etc.) Why?
 - The top predictors of both the classification and regression trees remain more or less the same except of Quarterly_Tax which is only important in the regression tree.
 - The classification tree is both structurally more complex as well bigger than the regression tree. This difference is created because in a regression tree, the response value is the mean of all the other values in the particular region however in the classification tree, the response is the majority class of the region.
 - The difference in shape is so apparent because decision trees are sensitive to change in training data.
- (ii) Predict the price, using the RT and the CT, of a used Toyota Corolla with the specifications listed in Table below.


```

df <- data.frame(Age_08_04 = 77,
                 KM = 117000,
                 Fuel_TypePetrol = 1,
                 Fuel_TypeDiesel = 0,
                 Fuel_TypeCNG = 0,
                 HP = 110,
                 Automatic = 0,
                 Doors = 5,
                 Quarterly_Tax = 100,
                 Mfr_Guarantee = 0,
                 Guarantee_Period = 3,
                 Airco = 1,
                 Automatic_airco = 0,
                 CD_Player = 0,
                 Powered_Windows = 0,
                 Sport_Model = 0,
                 Tow_Bar = 1)

df.pred.reg <- predict(reg.tree, df)
df.pred.class <- as.data.frame(predict(class.tree, df))
df.pred.class <- attributes(which.max(df.pred.class))$names

cat("Prediction of Regression Tree:", df.pred.reg, "\n")

## Prediction of Regression Tree: 7906.141
cat("Prediction of Classification Tree:", df.pred.class, "\n")

## Prediction of Classification Tree: (7.12e+03,8.53e+03]

```

(iii) Compare the predictions in terms of the predictors that were used, the magnitude of the difference between the two predictions, and the advantages and disadvantages of the two methods.

- The Regression Tree predicts the new data Price to be \$7906.141. While the classification tree predicts that the price will be in the category/bin/range \$7120-\$8530.
 - The advantage of using regression trees is that we can obtain an exact numerical prediction of our data.
 - However classification trees can prove to be more useful in predicting numerical data in situations where we are more concerned with the range estimation of the data rather than it's average value.
-