FOCP II Assignment - GitHub S | mankcheebu-rgb/FOCP-II-Assi | AI Roast Generator

Ask Gemini

chatgpt.com/c/69f7665e-f520-8323-b574-e0d6f1eaa65d

School

ChatGPT

Share

New chat

Search chats

Projects

Codex

More

Recents

AI Roast Generator

ESP32 Project Ideas

Live Wallpaper Creation Guide

Course Status Abbreviations

Stethoscope and Ear Damage

Mank cheebu
Free

Claim offer

I want to create a simple C++ program that generates funny roast messages.
It should take the user's name as input and print a roast using that name.
Can you give me a basic version of this program?

Here's a **basic beginner-friendly C++ program** that generates a simple roast using the user's name:

✅ Basic Version (Single Roast)

C++

```
#include <iostream>
#include <string>
using namespace std;
```

Ask anything

ChatGPT can make mistakes. Check important info. See Cookie Preferences.

Light rain
Tomorrow

Search

100%

9:26 PM
5/3/2026

FOCP II Assignment - GitHub S | mankcheebu-rgb/FOCP-II-Assi | AI Roast Generator | Ask Gemini

chatgpt.com/c/69f7665e-f520-8323-b574-e0d6f1eaa65d

ChatGPT | Share

New chat
Search chats
Projects
Codex
More

Recents
AI Roast Generator
ESP32 Project Ideas
Live Wallpaper Creation Guide
Course Status Abbreviations
Stethoscope and Ear Damage

Mank cheebu
Free
Claim offer

Can you improve the previous C++ program by storing multiple roast templates in a vector?
Each template should include a placeholder like {name}.
The program should randomly select one roast each time it runs.

Nice—this is exactly the kind of improvement your assignment wants 👌

Here's the upgraded version with:

- ✅ Multiple roast templates (using `vector`)
- ✅ `{name}` placeholder
- ✅ Random selection

✅ Improved C++ Program

Ask anything

ChatGPT can make mistakes. Check important info. See Cookie Preferences.

Light rain
Tomorrow
Search
100%
9:26 PM
5/3/2026

FOCP II Assignment - GitHub S | mankcheebu-rgb/FOCP-II-Assi | AI Roast Generator | Ask Gemini

chatgpt.com/c/69f7665e-f520-8323-b574-e0d6f1eaa65d

ChatGPT | Share

New chat
Search chats
Projects
Codex
More

Recents
- AI Roast Generator
- ESP32 Project Ideas
- Live Wallpaper Creation Guide
- Course Status Abbreviations
- Stethoscope and Ear Damage

Mank cheebu
Free
Claim offer

The program works, but I want to replace {name} in the selected roast with the actual user input.
Can you help me implement that in C++?
Also explain the logic simply.

You're on the right track—this is the key step that makes your program dynamic.

✅ C++ Code (with `{name}` replacement)

C++

```
#include <iostream>
#include <vector>
#include <string>
#include <cstdlib>
#include <ctime>
```

Ask anything

ChatGPT can make mistakes. Check important info. See Cookie Preferences.

Light rain Tomorrow | Search | 100% | 9:27 PM 5/3/2026

New chat
Search chats
Projects
Codex
More

Recents
AI Roast Generator
ESP32 Project Ideas
Live Wallpaper Creation Guide
Course Status Abbreviations
Stethoscope and Ear Damage

My program gives the same roast every time I run it.
I am using rand() but it doesn't seem random.
What is the issue and how can I fix it?

This is a **classic C++ mistake**—and actually perfect for your "bug fixing" requirement 👌

❌ The Problem

`rand()` is **not truly random by default.**

If you don't initialize it, it uses the **same starting seed every time**, so:

👉 You get the **same sequence of numbers**
👉 Which means the **same roast every run**

Mank cheebu
Free
Claim offer

Ask anything

ChatGPT can make mistakes. Check important info. See Cookie Preferences.

FOCP II Assignment - GitHub S | mankcheebu-rgb/FOCP-II-Assig | AI Roast Generator | Ask Gemini

chatgpt.com/c/69f7665e-f520-8323-b574-e0d6f1eaa65d

School

ChatGPT

Share

New chat

Search chats

Projects

Codex

More

Recents

AI Roast Generator

ESP32 Project Ideas

Live Wallpaper Creation Guide

Course Status Abbreviations

Stethoscope and Ear Damage

Mank cheebu
Free

Claim offer

How can I handle cases where the user enters an empty name in my C++ program?
I don't want the program to crash or behave incorrectly.

Good thinking—this is exactly the kind of edge case your teacher expects 👍

✅ Simple Solution: Check for Empty Input

After taking input, just validate it before continuing.

🔧 Updated Code Snippet

C++

```
string name;

cout << "Enter your name: ";
```

Ask anything

ChatGPT can make mistakes. Check important info. See Cookie Preferences.

37°C
Clear

Search

100%

9:28 PM
5/3/2026

File Edit Selection View Go Run ···

Search

EXPLORER

NO FOLDER OPENED

You have not yet opened a folder.

Open Folder

Opening a folder will close all currently open editors. To keep them open, add a folder instead.

cpp | random_shyt2.cpp | Movie_Tickets.cpp | Bank_Balance.cpp | AI_Roast_generator.cpp | Student_Excuse_Generator.cpp

C: > Users > HOME > Desktop > FOCP II - Assignments > AI_Roast_generator.cpp > main()

```
        "{name} doesn't debug code — they negotiate with bugs.",
        "{name}'s code runs so slowly that even dial-up internet feels fast."
    };

    // Seed random number generator (IMPORTANT for randomness)
    srand(time(0));

    // Generate random index
    int randomIndex = rand() % roasts.size();

    // Generate final roast
    string finalRoast = generateRoast(roasts[randomIndex], name);

    cout << "\n=== Roast Generator ===" << endl;
```

OUTPUT DEBUG CONSOLE TERMINAL PORTS PROBLEMS

Code

```
PS C:\Users\HOME> cd "c:\Users\HOME\Desktop\FOCP II - Assignments\" ; if ($?) { g++ AI_Roast_generator.cpp -o AI_Roast_generator } ; if ($?)
 { .\AI_Roast_generator }
Enter your name: mayank

=== Roast Generator ===
If laziness had a brand ambassador, it would be mayank.
PS C:\Users\HOME\Desktop\FOCP II - Assignments>
```

OUTLINE

TIMELINE

0 0 Live Share

Ln 22, Col 13 Spaces: 4 UTF-8 CRLF { } C++ Win32

37°C Clear

Search

100%

9:44 PM 5/3/2026

File Edit Selection View Go Run ··· Search

EXPLORER

NO FOLDER OPENED

You have not yet opened a folder.

Open Folder

Opening a folder will close all currently open editors. To keep them open, add a folder instead.

cpp | random_shyt2.cpp | Movie_Tickets.cpp | Bank_Balance.cpp | AI_Roast_generator.cpp 9 | Student_Excuse_Generator.cpp

C: > Users > HOME > Desktop > FOCP II - Assignments > AI_Roast_generator.cpp > ...

```cpp
string generateRoast(string roastTemplate, string name) {
    size_t pos = roastTemplate.find("{name}");

    // Replace all occurrences of {name}
    while (pos != string::npos) {
        roastTemplate.replace(pos, 6, name);
        pos = roastTemplate.find("{name}");
    }

    return roastTemplate;
}

int main()
    string name;
```

OUTPUT | DEBUG CONSOLE | TERMINAL | PORTS | PROBLEMS 9

```
      |                                                         ^~~~
      |                                                         tzname
AI_Roast_generator.cpp:57:4: error: 'cout' does not name a type
   57 |     cout << "\n=== Roast Generator ===" << endl;
      |     ^~~~
AI_Roast_generator.cpp:58:5: error: 'cout' does not name a type
   58 |     cout << finalRoast << endl;
      |     ^~~~
AI_Roast_generator.cpp:60:5: error: expected unqualified-id before 'return'
   60 |     return 0;
      |     ^~~~~~
AI_Roast_generator.cpp:61:1: error: expected declaration before '}' token
   61 | }
      | ^
PS C:\Users\HOME\Desktop\FOCP II - Assignments>
```

OUTLINE

TIMELINE

9 0 Live Share | Ln 22, Col 12 | Spaces: 4 | UTF-8 | CRLF | { } C++ | Win32

37°C Clear | Search | 100% | 9:43 PM 5/3/2026