

EECS16A: Homework 3

Problem 4: Image Stitching

This section of the notebook continues the image stitching problem. Be sure to have a `figures` folder in the same directory as the notebook. The `figures` folder should contain the files:

```
Berkeley_banner_1.jpg  
Berkeley_banner_2.jpg  
stacked_pieces.jpg  
lefthalfpic.jpg  
righthalfpic.jpg
```

Note: This structure is present in the provided HW3 zip file.

Run the next block of code before proceeding

```
In [1]: import numpy as np  
import numpy.matlib  
import matplotlib.pyplot as plt  
from mpl_toolkits.mplot3d import Axes3D  
from numpy import pi, cos, exp, sin  
import matplotlib.image as mpimg  
import matplotlib.transforms as mtransforms  
  
%matplotlib inline  
  
#loading images  
image1=mpimg.imread('figures/Berkeley_banner_1.jpg')  
image1=image1/255.0  
image2=mpimg.imread('figures/Berkeley_banner_2.jpg')  
image2=image2/255.0  
image_stack=mpimg.imread('figures/stacked_pieces.jpg')  
image_stack=image_stack/255.0  
  
image1_marked=mpimg.imread('figures/lefthalfpic.jpg')  
image1_marked=image1_marked/255.0  
image2_marked=mpimg.imread('figures/righthalfpic.jpg')  
image2_marked=image2_marked/255.0
```

```

def euclidean_transform_2to1(transform_mat,translation,image,position,LL,UL):
    new_position=np.round(transform_mat.dot(position)+translation)
    new_position=new_position.astype(int)

    if (new_position>=LL).all() and (new_position<UL).all():
        values=image[new_position[0][0],new_position[1][0],:]
    else:
        values=np.array([2.0,2.0,2.0])

    return values

def euclidean_transform_1to2(transform_mat,translation,image,position,LL,UL):
    transform_mat_inv=np.linalg.inv(transform_mat)
    new_position=np.round(transform_mat_inv.dot(position-translation))
    new_position=new_position.astype(int)

    if (new_position>=LL).all() and (new_position<UL).all():
        values=image[new_position[0][0],new_position[1][0],:]
    else:
        values=np.array([2.0,2.0,2.0])

    return values

def solve(A,b):
    try:
        z = np.linalg.solve(A,b)
    except:
        raise ValueError('Rows are not linearly independent. Cannot solve')
    return z

```

We will stick to a simple example and just consider stitching two images (if you can stitch two pictures, then you could conceivably stitch more by applying the same technique over and over again).

Daniel decided to take an amazing picture of the Campanile overlooking the bay. Unfortunately, the field of view of his camera was not large enough to capture the entire scene, so he decided to take two pictures and stitch them together.

The next block will display the two images.

```
In [2]: plt.figure(figsize=(20,40))

plt.subplot(311)
plt.imshow(image1)

plt.subplot(312)
plt.imshow(image2)

plt.subplot(313)
plt.imshow(image_stack)

plt.show()
```





Once you apply Marcela's algorithm on the two images you get the following result (run the next block):


```
In [3]: plt.figure(figsize=(20,30))

plt.subplot(211)
plt.imshow(image1_marked)

plt.subplot(212)
plt.imshow(image2_marked)
```

```
Out[3]: <matplotlib.image.AxesImage at 0x120bd48d0>
```





As you can see Marcela's algorithm was able to find four common points between the two images. These points expressed in the coordinates of the first image and second image are

$$\begin{array}{cccc} \vec{p}_1 = \begin{bmatrix} 200 \\ 700 \end{bmatrix} & \vec{p}_2 = \begin{bmatrix} 310 \\ 620 \end{bmatrix} & \vec{p}_3 = \begin{bmatrix} 390 \\ 660 \end{bmatrix} & \vec{p}_4 = \begin{bmatrix} 465.7 \\ 455.0 \end{bmatrix} \\ \vec{q}_1 = \begin{bmatrix} 162.2976 \\ 565.8862 \end{bmatrix} & \vec{q}_2 = \begin{bmatrix} 285.4283 \\ 458.7469 \end{bmatrix} & \vec{q}_3 = \begin{bmatrix} 385.2465 \\ 498.1973 \end{bmatrix} & \vec{q}_4 = \begin{bmatrix} 465.7 \\ 455.0 \end{bmatrix} \end{array}$$

It should be noted that in relation to the image the positive x-axis is down and the positive y-axis is right. This will have no bearing as to how you solve the problem, however it helps in interpreting what the numbers mean relative to the image you are seeing.

Using the points determine the parameters R_{11} , R_{12} , R_{21} , R_{22} , T_x , T_y that map the points from the first image to the points in the second image by solving an appropriate system of equations. Hint: you do not need all the points to recover the parameters.



```

In [4]: # Note that the following is a general template for solving for 6 unknowns
# You do not have to use the following code exactly.
# All you need to do is to find parameters R_11, R_12, R_21, R_22, T_x,
# If you prefer finding them another way it is fine.

# fill in the entries
A = np.array([[200, 700, 0, 0, 1, 0],
              [0, 0, 200, 700, 0, 1],
              [310, 620, 0, 0, 1, 0],
              [0, 0, 310, 620, 0, 1],
              [390, 660, 0, 0, 1, 0],
              [0, 0, 390, 660, 0, 1]])

# fill in the entries
b = np.array([[162.2976],[565.8862],[285.4283],[458.7469],[385.2465],[49

A = A.astype(float)
b = b.astype(float)

# solve the linear system for the coefficients
z = solve(A,b)

#Parameters for our transformation
R_11 = z[0,0]
R_12 = z[1,0]
R_21 = z[2,0]
R_22 = z[3,0]
T_x = z[4,0]
T_y = z[5,0]

```

Stitch the images using the transformation you found by running the code below.

Note that it takes about 40 seconds for the block to finish running on a modern laptop.

```

In [5]: matrix_transform=np.array([[R_11,R_12],[R_21,R_22]])
translation=np.array([T_x,T_y])

#Creating image canvas (the image will be constructed on this)
num_row,num_col,blah=image1.shape
image_rec=1.0*np.ones((int(num_row),int(num_col),3))

#Reconstructing the original image

LL=np.array([[0],[0]]) #lower limit on image domain
UL=np.array([[num_row],[num_col]]) #upper limit on image domain

```


```

for row in range(0,int(num_row)):
    for col in range(0,int(num_col)):
        #notice that the position is in terms of x and y, so the c
        position=np.array([[row],[col]])
        if image1[row,col,0] > 0.995 and image1[row,col,1] > 0.995 and i
            temp = euclidean_transform_2tol(matrix_transform,translation
            image_rec[row,col,:] = temp
        else:
            image_rec[row,col,:] = image1[row,col,:]

plt.figure(figsize=(20,20))
plt.imshow(image_rec)
plt.axis('on')
plt.show()

```

Clipping input data to the valid range for imshow with RGB data ([0..1] for floats or [0..255] for integers).



Part E: Failure Mode Points

$$\begin{aligned}
 \vec{p}_1 &= \begin{bmatrix} 390 \\ 660 \end{bmatrix} & \vec{p}_2 &= \begin{bmatrix} 425 \\ 645 \end{bmatrix} & \vec{p}_3 &= \begin{bmatrix} 460 \\ 630 \end{bmatrix} \\
 \vec{q}_1 &= \begin{bmatrix} 385 \\ 450 \end{bmatrix} & \vec{q}_2 &= \begin{bmatrix} 425 \\ 480 \end{bmatrix} & \vec{q}_3 &= \begin{bmatrix} 465 \\ 510 \end{bmatrix}
 \end{aligned}$$

To solve: # Note that the following is a general template for solving for 6 unknown


```

11 [0]: # NOTE that the following is a general template for solving for unknown
# You do not have to use the following code exactly.
# All you need to do is to find parameters R_11, R_12, R_21, R_22, T_x,
# If you prefer finding them another way it is fine.

# fill in the entries
A = np.array([[390, 660, 0, 0, 1, 0],
              [0, 0, 390, 660, 0, 1],
              [425, 645, 0, 0, 1, 0],
              [0, 0, 425, 645, 0, 1],
              [460, 630, 0, 0, 1, 0],
              [0, 0, 460, 630, 0, 1]])

# fill in the entries
b = np.array([[385],[450],[425],[480],[465],[510]])

A = A.astype(float)
b = b.astype(float)

# solve the linear system for the coefficients
z = solve(A,b)

#Parameters for our transformation
R_11 = z[0,0]
R_12 = z[1,0]
R_21 = z[2,0]
R_22 = z[3,0]
T_x  = z[4,0]
T_y  = z[5,0]

```

```

-----
LinAlgError                                Traceback (most recent call
last)
<ipython-input-1-4ee2c81e8dee> in solve(A, b)
     51     try:
--> 52         z = np.linalg.solve(A,b)
     53     except:

~/miniconda3/lib/python3.7/site-packages/numpy/linalg/linalg.py in solve
(a, b)
     402     extobj = get_linalg_error_extobj(_raise_linalgerror_singular
ar)
--> 403     r = gufunc(a, b, signature=signature, extobj=extobj)
     404

~/miniconda3/lib/python3.7/site-packages/numpy/linalg/linalg.py in _ra
ise_linalgerror_singular(err, flag)
     96 def _raise_linalgerror_singular(err, flag):
--> 97     raise LinAlgError("Singular matrix")
     98

```


LinAlgError: Singular matrix

During handling of the above exception, another exception occurred:

```
ValueError                                Traceback (most recent call
last)
<ipython-input-6-85bd29877f64> in <module>
    19
    20 # solve the linear system for the coefficients
--> 21 z = solve(A,b)
    22
    23 #Parameters for our transformation

<ipython-input-1-4ee2c81e8dee> in solve(A, b)
    52         z = np.linalg.solve(A,b)
    53     except:
--> 54         raise ValueError('Rows are not linearly independent. C
annot solve system of linear equations uniquely. :)')
    55     return z
```

ValueError: Rows are not linearly independent. Cannot solve system of linear equations uniquely. :)

In []: