INSTRUCTION SET OF 8085

Some Common Notations:

1) Addr   →   16 bit address.
2) Data   →   8 bit data.
3) Data 16   →   16 bit data.
4) R, r1, r2   →   one of the registers.
5) Rp   →   register pair. BC pair is called B, DE → D and HL → L
6) Port   →   8 bit IO addres

Data Transfer Group

1) MOV r1, r2
The contents of register r2 is moved into register r1.
Eg: MOV A,B   ; A ← B

Addr. Mode	Flags Affected	Cycles	T-States
Register	None	1	4

2) MOV r1, M
The contents of the memory location pointed by HL (memory pointer) is moved into register r1.
Eg: MOV B,M   ; B ← [[HL]] i.e. B ← M

Addr. Mode	Flags Affected	Cycles	T-States
Indirect	None	2	7

3) MOV M, r2
The contents of register r2 is moved into the memory location pointed by HL (memory pointer).
Eg: MOV M,B   ; [[HL]] ← B i.e. M ← B

Addr. Mode	Flags Affected	Cycles	T-States
Register	None	2	7

4) MVI r1, 8-bit data
The 8-bit data is immidiately moved into the register specified in the instruction.
Eg: MVI C, 23   ; C ← 23H

Addr. Mode	Flags Affected	Cycles	T-States
Immidiate	None	2	7

5) LXI rp, 16-bit data
The 16-bit data is immidiately moved into the register pair specified in the instruction.
Eg: MVI B, 2300H   ; BC ← 2300H i.e. B← 23, C← 00

Addr. Mode	Flags Affected	Cycles	T-States
Immidiate	None	3	10

6) MVI M, 8-bit data
The 8-bit data is immidiately moved into the memory location pointed by HL (memory pointer).
Eg: MVI M, 23   ; [[HL]] ← 23H

Addr. Mode	Flags Affected	Cycles	T-States
Immediate	None	3	10

7) LDA 16-bit address
The accumulator is loaded withb the contents of the memory location having the given address.
Eg: LDA 2000H ; A ← [2000]

Addr. Mode	Flags Affected	Cycles	T-States
Direct	None	4	13

8) STA 16-bit address
The accumulator is stored into the memory location having the given address.
Eg: STA 2000H ; [2000] ← A

Addr. Mode	Flags Affected	Cycles	T-States
Direct	None	4	13

9) LHLD 16-bit address
The HL pair is loaded with the contents of the loactions ppointed by the given address and address + 1. ☺ In case of doubts, contact Bharat Sir: - 98204 08217.
Eg: LHLD 2000 ; HL ← [2000] & [2001] i.e. L ← [2000], H ← [2001]

Addr. Mode	Flags Affected	Cycles	T-States
Direct	None	5	16

10)   SHLD 16-bit address
The HL pair is stored into the loactions ppointed by the given address and address + 1.
Eg: SHLD 2000 ; [2000] & [2001] ← HL i.e. [2000] ← L, [2001] ← H

Addr. Mode	Flags Affected	Cycles	T-States
Direct	None	5	16

11)   LDAX rp
The accumulator is loaded with the contents of memory location pointed by value of the given register.
Eg: LDAX B   ; A ← [[BC]] i.e. if [BC] = 2000, A gets the value from location
                    ; 2000 i.e. A ← [2000]

Addr. Mode	Flags Affected	Cycles	T-States
Indirect	None	2	7

12)   STAX rp
The accumulator is stored into the location pointed by value of the given register.
Eg: STAX B   ; [[BC]] ← A i.e. if [BC] = 2000, location 2000 will get the
                    ; value of A i.e. [2000] ← A.

Addr. Mode	Flags Affected	Cycles	T-States
Indirect	None	2	7

13)   PCHL
The Program Counter gets the contents of the HL register pair.
This statement causes a branch in the sequence of the program.
Eg: PCHL   ; PC ← HL

Addr. Mode	Flags Affected	Cycles	T-States
Register	None	1	**6**

14)   SPHL
The Stack Pointer gets the contents of the HL register pair.
This statement reloates the stack in the 64 KB memory.

Eg: SPHL   ; SP ← HL

Addr. Mode	Flags Affected	Cycles	T-States
Register	None	1	**6**

15) XCHG
This instruction exchanges the contents of HL pair and DE pair.
Eg: XCHG   ; HL ←→ DE
#Please refer Bharat Sir's Lecture Notes for this ...

Addr. Mode	Flags Affected	Cycles	T-States
Register	None	1	4

16) XTHL
This instruction exchanges the DE pair with the contents of location pointed by the SP and SP+1.
Eg: XTHL   ; HL ←→ [[SP]] and [[SP]+1]
                          ; i.e. if [SP]=2000 then L ←→ [2000] and H ←→ [2001]
#Please refer Bharat Sir's Lecture Notes for this ...

Addr. Mode	Flags Affected	Cycles	T-States
Register	None	5	16

Arithmetic Group

Addition

1) ADD R
This instruction adds the contents of register R with the accumulator, stores result in the accumulator.
Eg: ADD B   ; A ← A + B

Addr. Mode	Flags Affected	Cycles	T-States
Register	All	1	**4**

2) ADD M
This instruction adds the contents of the memory location pointed by HL, with the accumulator, and stores the result in the accumulator.
Eg: ADD M   ; A ← A + [[HL]]

Addr. Mode	Flags Affected	Cycles	T-States
Indirect	All	2	**7**

3) ADI 8-bit data
This instruction adds the immidiate data with the accumulator, and stores the result in the accumulator.
Eg: ADI 25   ; A ← A + 25

Addr. Mode	Flags Affected	Cycles	T-States
Immediate	All	2	**7**

4) ADC R
This instruction adds the contents of the register R with the accumulator, and also adds the carry flag, and stores the result in the accumulator. It is used while adding large numbers.
Eg: ADD B   ; A ← A + B + Cy

Addr. Mode	Flags Affected	Cycles	T-States
Register	All	1	**4**

5) ADC M