1. Program ▾   ⓘ   ‹ 1 › ▦ 💾

Attempted: 1/1

Question 1

🔖 Revisit Later

How to Attempt?

Addition using Strings: Write a function that takes two numbers in string format and forms a string containing the sum (addition) of these two numbers.

Assumption(s):
- The input strings will contain only numeric digits
- The input strings can be of any large lengths
- The lengths of the two input string need not be the same
- The input strings will represent only positive numbers

For example –
- If input strings are "1234" and "56", the output string should be "1290"
- If input strings are "56" and "1234", the output string should be "1290"
- If input strings are "123456732128989543219" and "987612673489652", the output string should be "123457719741663032871"

NOTE: In Java & C#, this logic can be easily implemented using BigInteger. However for the sake of enhancing your programming skills, you are recommended to solve this question without using BigInteger.

JAVA7 ▾   Compiler: Java - 1.7   🕘 ☾ </> ⤢ ⋮

```java
import java.io.*;
import java.util.*;

// Read only region start
class UserMainCode
{

    public String addNumberStrings(String input1,String input2){
        // Read only region end
        // Write code here...
        int carry=0;
    if(input1.length()<input2.length())
    {
      String temp="";
      temp=input1;
      input1=input2;
      input2=temp;
    }
    int len1=input1.length();
    int len2=input2.length();
    String str="";
    int j=len2-1;
    for(int i=0;i<len1;i++)
    {
     int a=Character.getNumericValue(input1.charAt(len1-1-i));
     int b=0;
     if(j>=0)
     {
      b=Character.getNumericValue(input2.charAt(j));
      j--;
     }
     int sum=a+b+carry;
     carry=sum/10;
     int init=sum%10;
     str=Integer.toString(init)+str;
     if(i==len1-1 && carry>0)
     {
             str=Integer.toString(carry)+str;
```

☐ Use Custom Input   ⓘ   **Compile and Test**   **Submit Code**

Mettl Online Assessment © 2021-2031 🛜

Need Help? Contact us: 🇺🇸 +1 (800) 265-6038   🇮🇳 +91 80471-90902

Powered By Mercer | mettl

1. Program ▼   ⓘ

‹ **1** ›   ⊞   ⊟

Attempted: 1/1

☐ Use Custom Input   ⓘ   **Compile and Test**   **Submit Code**

Question 1   ⬚ Revisit Later

How to Attempt?

Addition using Strings: Write a function that takes two numbers in string format and forms a string containing the sum (addition) of these two numbers.

Assumption(s):
- The input strings will contain only numeric digits
- The input strings can be of any large lengths
- The lengths of the two input string need not be the same
- The input strings will represent only positive numbers

For example –
- If input strings are "1234" and "56", the output string should be "1290"
- If input strings are "56" and "1234", the output string should be "1290"
- If input strings are "123456732128989543219" and "987612673489652", the output string should be "123457719741663032871"

NOTE: In Java & C#, this logic can be easily implemented using BigInteger. However for the sake of enhancing your programming skills, you are recommended to solve this question without using BigInteger.

Code Execution   Code History

0/2 - Sample Test Cases Failed

✅ **default**   ⌃

🕐 **CODE EXECUTION DETAILS**
Time: 169 ms
Memory: 103812 kb

</> **TEST CASE INFORMATION**
Input
123456732128989543219,987612673489652

Expected Output
123457719741663032871

Actual Output
123457719741663032871

>_ **CONSOLE OUTPUT**

⬚ **STANDARD ERROR/WARNING**
None

✅ **default**   ⌄

Mettl Online Assessment © 2021-2031 📶

Need Help? Contact us: 🇺🇸 +1 (800) 265-6038   🇮🇳 +91 80471-90902

Powered By ❦ Mercer | mettl

1. Program ▾   ⓘ

< **1** >   ▦   🖫

Question 1

How to Attempt?

Addition using Strings: Write a function that takes two numbers in string format and forms a string containing the sum (addition) of these two numbers.

Assumption(s):
- The input strings will contain only numeric digits
- The input strings can be of any large lengths
- The lengths of the two input string need not be the same
- The input strings will represent only positive numbers

For example –
- If input strings are "1234" and "56", the output string should be "1290"
- If input strings are "56" and "1234", the output string should be "1290"
- If input strings are "123456732128989543219" and "987612673489652", the output string should be "123457719741663032871"

NOTE: In Java & C#, this logic can be easily implemented using BigInteger. However for the sake of enhancing your programming skills, you are recommended to solve this question without using BigInteger.

🔖 Revisit Later

```
Attempted: 1/1
29              er.getNumericValue(input2.charAt(j));
30        j--;
31     }
32     int sum=a+b+carry;
33     carry-sum/10;
34     int init=sum%10;
35     str=Integer.toString(init)+str;
36     if(i==len1-1 && carry>0)
37     {
38              str=Integer.toString(carry)+str;
39     }
40   }
41   return str;
42     }
43 }
```

☐ Use Custom Input   ⓘ │ **Compile and Test**   Submit Code

Code Execution   Code History

0/5 - Graded Test Cases Failed

✅ TC 5

✅ TC 4

✅ TC 3

✅ TC 2

✅ TC 1