

1. Installing Express

Express use garna sabai bhanda pahila aafno project folder ko terminal ma gayera npm bata yesari install garnuparchha: [\[1\]](#), [\[2\]](#), [\[3\]](#)

bash

```
npm init -y
npm install express
Use code with caution.
```

- **npm init -y**: Yesle default `package.json` file banauchha.
 - **npm install express**: Yesle `node_modules` bhitra Express library download garchha. [\[1\]](#), [\[2\]](#)
-

2. First Express Server & `app.listen()`

Server create garna ra yeslai aafno computer ko kunai specific **Port** ma run garna yo minimal code chahinchha.

javascript

```
// index.js
const express = require('express'); // Express module import gareko
const app = express(); // Express app initialize gareko
const PORT = 3000; // Server chalaune port number

// app.listen() le server lai 3000 port ma active/live banauchha
app.listen(PORT, () => {
  console.log(`Server successfully started on
http://localhost:${PORT}`);
});
Use code with caution.
```

3. Routing Methods (GET, POST, PUT, PATCH, DELETE)

Express ma endpoints (URLs) handle garna HTTP methods use gariyanthha. Harek method ko aafnai kaam hunchha: [\[1\]](#)

javascript

```
// Express lai JSON data read garna middleware chahinchha (yo thapnu hola)
app.use(express.json());

// ● app.get(): Server bata data lina
app.get('/api/users', (req, res) => {
  res.send("Sabai user ko list yahan chha.");
});

// ● app.post(): Naya data थप्न (Create)
app.post('/api/users', (req, res) => {
  const newData = req.body; // Client le pathako data req.body ma
  hunchha
  res.send("Naya user successfully create bhayo!");
});

// ● app.put(): Bhairakheko data poora badlina (Replace)
app.put('/api/users', (req, res) => {
  res.send("User ko sabai details poora update bhayo.");
});

// ● app.patch(): Data ko kehi bhaag matra ferne (Partial Update)
app.patch('/api/users', (req, res) => {
  res.send("User ko password matra update bhayo.");
});

// ● app.delete(): Data hatauna (Delete)
app.delete('/api/users', (req, res) => {
  res.send("User account delete bhayo.");
});
Use code with caution.
```



4. Sending Responses (JSON vs HTML)

Client le request garesi server le reaction (Response) dinaiparchha. Express ma hami farak-farak format ma data firta pathauna sakchhaũ. [\[1\]](#), [\[2\]](#)



HTML Response (`res.send`)

Browser ma direct design ba text dekhauna:

javascript

```
app.get('/', (req, res) => {
  res.send('<h1>Welcome to Nepal Backend Server</h1><p>Yo HTML response
ho.</p>');
});
```

Use code with caution.

JSON Response (`res.json()`) [\[1\]](#), [\[2\]](#)

Mobile apps ba React/Vue jasta Frontend framework sanga kura garna JSON format use hunchha (API ko lagi yo sabai bhandha dherai use hunchha): [\[1\]](#)

javascript

```
app.get('/api/status', (req, res) => {
  res.json({
    success: true,
    message: "Server masta chaldaichha",
    code: 200
  });
});
```

Use code with caution.

5. Route Parameters (`req.params`)

Jaba URL ma dynamic data pathauna parchha (jastai specific user ko ID), taba hami **Route Parameters** use garchhaũ. URL ma : (colon) use garera variable banainchha. [\[1\]](#), [\[2\]](#)

javascript

```
// URL: http://localhost:3000/api/users/8848
app.get('/api/users/:userId', (req, res) => {
  // URL ko ':' pachhadi bhako naam req.params ma aunchha
  const id = req.params.userId;

  res.json({
    searchedId: id,
    name: `User number ${id} ko details`
  });
});
```

Use code with caution.

If multiple params chahiyo bhane yesari pani garna sakinchha:

```
/api/products/:category/:productId
```

1 Thau ma Complete Boilerplate Code

Yo mathika sabai topic lai sametera banayeko euta unified `index.js` file:

javascript

```
const express = require('express');
const app = express();
const PORT = 3000;

app.use(express.json());

// 1. Home Route (HTML Response)
app.get('/', (req, res) => {
  res.send('<h1>Express Basics Masterclass!</h1>');
});

// 2. Data Route (JSON Response + Route Params)
app.get('/api/items/:itemId', (req, res) => {
  const itemId = req.params.itemId;
  res.json({
    status: "success",
    requestedItem: itemId,
    data: { name: "Laptop", price: 95000 }
  });
});

// 3. Post Route
app.post('/api/items', (req, res) => {
  console.log(req.body); // Terminal ma check garna client le k pathayo
  res.status(201).json({ message: "Item added!" });
});

app.listen(PORT, () => {
  console.log(`Server running on port ${PORT}`);
});
```