ASP.NET Web API v2 Security Architecture

Dominick Baier http://leastprivilege.com @leastprivilege





Agenda

Overview of architecture


- Hosting
- Message handlers
- Authentication filters
- Authorization filters

Accessing the client identity

Do Not Place Anything in This Space

(Add watermark during editing)


ASP.NET Web API: the big picture



Do Not Place Anything in This Space

(Add watermark during editing)


Authentication & Authorization in Web API v1



Do Not Place Anything in This Space

(Add watermark during editing)

The new Pipeline in Web API v2



http://www.asp.net/vnext/overview/owin-and-katana/an-overview-of-project-katana

Do Not Place Anything in This Space

(Add watermark during editing)

Classic hosting

Web API

Web API

Web Host

Self Host

ASP.NET

WCF

IIS

.NET Process

Do Not Place Anything in This Space

(Add watermark during editing)

OWIN "System.Web" hosting

Web API (+ OWIN Adapter)

OWIN

ASP.NET (+ OWIN Bridge)

IIS

Do Not Place Anything in This Space

(Add watermark during editing)

Pure OWIN hosting


Web API (+ OWIN Adapter)

OWIN

Process/Host (+ OWIN Bridge)

Do Not Place Anything in This Space

(Add watermark during editing)



OWIN Middleware

Global

```
public class AuthenticationMiddleware
{
   private readonly Func<IDictionary<string, object>, Task> _next;
    public AuthenticationMiddleware(Func<IDictionary<string, object>, Task> next)
       next = next;
    public async Task Invoke(IDictionary<string, object> env)
       // inspect env and do credential validation, then set principal
       env["server.User"] = CreatePrincipal();
        await next(env);
```

Do Not Place Anything in This Space

(Add watermark during editing)

Katana Authentication Middleware

```
public class Startup
    public void Configuration(IAppBuilder app)
        app.UseCookieAuthentication(new CookieAuthenticationOptions
                AuthenticationType = "Cookies",
                // more options
            });
        app.UseGoogleAuthentication(new GoogleAuthenticationOptions
            {
                AuthenticationType = "Google",
                // more options
            });
        app.UseOAuthBearerAuthentication(new OAuthBearerAuthenticationOptions
            {
                AuthenticationType = "Bearer"
                // more options
            });
```

ything

ng



MessageHandler



Web API, global or per-route

```
public class MyHandler : DelegatingHandler
{
    protected async override Task<HttpResponseMessage> SendAsync(
        HttpRequestMessage request, CancellationToken cancellationToken)
    {
        // inspect request

        var response = await base.SendAsync(request, cancellationToken);

        // inspect response
        return response;
    }
}
```

Do Not Place Anything in This Space

(Add watermark during editing)

Thinktecture Authentication Handler

http://thinktecture.github.com/Thinktecture.ldentityModel/

incoming credential

mapping credential to token handler

Header

Query String

Client Certificate

Cookie



AuthenticationHandler

: DelegatingHandler



- 1. Authentication
- 2. Claims Transformation
- 3. (Session handling)
- 4. Set Thread.CurrentPrincipal

Do Not Place Anything in This Space

(Add watermark during editing)

Authentication filter

1

WebApiConfig.cs

```
config.Filters.Add(new HostAuthenticationFilter("Bearer"));
```

```
[HostAuthentication("Bearer")]
public class TestController : ApiController
{
    [HostAuthentication("Google")]
    public HttpResponseMessage Get()
    { }

    [OverrideAuthentication]
    [HostAuthentication("Cookies")]
    public HttpResponseMessage Delete()
    { }
}
```

ot Place Anything

in This Space

(Add watermark during editing)

Authorization filter



- Determines if a resource needs authentication
 - [AllowAnonymous] to skip authorization for an action
 - emits the 401 status code, if unsuccessful

```
// minimum requirement is successful authentication
[Authorize]
public DataController : ApiController
{
    [AllowAnonymous]
    public Data Get()
    { ... }

    [Authorize(Role = "Foo")]
    public HttpResponseMessage Delete(int id)
    { ... }
}
```

Do Not Place Anything in This Space

(Add watermark during editing)

Accessing the client identity

- Previous versions of Web API used Thread. CurrentPrincipal to access client identity
 - ApiController.User was a shortcut to T.CP
- v2 uses a new concept: RequestContext
 - hangs off the HttpRequestMessage
 - ApiController.User is now a shortcut to the request context
 - □ could be *null*

(Add watermark during editing)

Summary

- Web API security extensibility is a pipeline
 - Katana middleware
 - message handlers (not encouraged anymore)
 - authentication filters
 - authorization filters
- Avoid host (e.g. IIS) specific dependencies

- HttpRequestMessage.GetRequestContext().Principal
 - is the one stop shopping for client identity

Do Not Place Anything in This Space

(Add watermark during editing)

Resources

PluralSight:

- Scott Allen MVC5 Fundamentals (OWIN and Katana)
- □ Dominick Baier Introduction to Identity & Access Control in .NET 4.5

Do Not Place Anything in This Space

(Add watermark during editing)