

Sliding Doors





ALUMINIUM DOORS – VIC










The Dowell Sliding Door is as attractive as it is sturdy, making it a versatile solution.



Size Range (n1-n5)

| STUD OPENING | 1510 | 1870 | 2110 | 2470 |
|--------------|---|---|---|---|
| DOOR | 1450 | 1810 | 2050 | 2410 |
| 2140 (N1-N4) | | | | |
| 2100 (N1-N4) | | | | |
| 2175 (N5) | | | | |
| 2135 (N5) | | | | |
| |  |  |  |  |
| | DSD2115-2 | DSD2118-2 | DSD2121-2 | DSD2124-2 |

| STUD OPENING | 2784 | 3144 | 3684 |
|--------------|---|---|---|
| DOOR | 2724 | 3084 | 3624 |
| 2140 (N1-N4) | | | |
| 2100 (N1-N4) | | | |
| 2175 (N5) | | | |
| 2135 (N5) | | | |
| |  |  |  |
| | DSD2127-3 | DSD2130-3 | DSD2136-3 |






| STUD OPENING | 2950 | 3670 | 4150 | 4870 |
|--------------|--|--|---|--|
| DOOR | 2890 | 3610 | 4090 | 4810 |
| 2140 (N1-N4) | | | | |
| 2100 (N1-N4) | | | | |
| 2175 (N5) | | | | |
| 2135 (N5) | | | | |
| |  |  |  |  |
| | DSD2129-4 | DSD2136-4 | DSD2141-4 | DSD2148-4 |

Note: An option for double glazed doors for enhanced thermal performance is available.

Standard handling may vary from state to state. Please consult your nearest sales office for clarification.

* Some features and options may vary from state to state, please check with your local Dowell representative.

Optional Alternatives

| | | | | | |
|---|---|---|---|--|---|
|  |  |  |  |  | Key M Midrail 4 4mm thick glass 5 5mm thick glass |
| Reverse Hand | Colonial C1 | Barrier Grille Screen Door | Screen Door (Midrail Optional) | Reverse Hand Panel | |

Features

- Durable low maintenance, easy-clean aluminium profiles.
- Reveal flashing fins on jambs and head for weather protection.
- Patented sill valve draining system for excellent performance.
- Optional Sump Sill for demanding exposure conditions.
- Fully adjustable, noncorrosive ball bearing roller system for smooth panel operation.

- Available in 2 panel sliding (X0), 3 panel (X00, 0X0 or 00X) and bi-parting sliding (0XX0) combinations.
- Reversal of sliding panel configuration on all 2 panel sliding combinations possible after installation.
- High quality corner gaskets at frame joints for superior sealing.
- Optional fly doors and barrier grilles available.
- Easy coupling to the Dowell range of windows.

Hardware Options

- Keyed deadlock fitted as standard.
- Snib Latch available on request